

Package ‘eurlex’

July 27, 2021

Type Package

Title Retrieve Data on European Union Law

Version 0.3.6

Description Access to data on European Union laws and court decisions made easy with pre-defined 'SPARQL' queries and 'GET' requests.

License GPL-3

Encoding UTF-8

Depends R (>= 3.4.0)

Imports magrittr, dplyr, xml2, tidyr, httr, curl, rvest, rlang, stringr, readr, pdftools, antiword

RoxygenNote 7.1.0

Suggests knitr, rmarkdown, tidytext, wordcloud, purrr, ggplot2

URL <https://michalovadek.github.io/eurlex/>

VignetteBuilder knitr

NeedsCompilation no

Author Michal Ovadek [aut, cre, cph] (<<https://orcid.org/0000-0002-2552-2580>>)

Maintainer Michal Ovadek <michal.ovadek@gmail.com>

Repository CRAN

Date/Publication 2021-07-27 13:30:01 UTC

R topics documented:

elx_council_votes	2
elx_curia_list	2
elx_fetch_data	3
elx_label_eurovoc	4
elx_make_query	4
elx_run_query	6

Index	8
--------------	----------

elx_council_votes	<i>Retrieve Council votes on EU acts</i>
-------------------	--

Description

Executes a SPARQL query to the Council's endpoint.

Usage

```
elx_council_votes()
```

Value

A data frame with Council votes on EU acts.

Examples

```
votes <- elx_council_votes()
```

elx_curia_list	<i>Scrape list of court cases from Curia</i>
----------------	--

Description

Harvests data from lists of EU court cases from curia.europa.eu. CELEX identifiers are extracted from hyperlinks where available.

Usage

```
elx_curia_list(  
  data = c("all", "ecj_old", "ecj_new", "gc_all", "cst_all"),  
  parse = TRUE  
)
```

Arguments

data	Data to be scraped from four separate lists of cases maintained by Curia, defaults to "all" which contains cases from Court of Justice, General Court and Civil Service Tribunal.
parse	If 'TRUE', references to cases and appeals are parsed out from 'case_info' into separate columns

Value

A data frame containing case identifiers and information as character columns. Where the case id contains a hyperlink to Eur-Lex, the CELEX identifier is retrieved as well. Hyperlinks to Eur-Lex disappeared from more recent cases.

Examples

```
elx_curia_list(data = "cst_all")
```

elx_fetch_data	<i>Retrieve additional data on EU documents</i>
----------------	---

Description

Wraps `httr::GET` with pre-specified headers to retrieve data.

Usage

```
elx_fetch_data(
  url,
  type = c("title", "text", "ids"),
  language_1 = "en",
  language_2 = "fr",
  language_3 = "de",
  include_breaks = TRUE
)
```

Arguments

<code>url</code>	A valid url as character vector of length one based on a resource identifier such as CELEX or Cellar URI.
<code>type</code>	The type of data to be retrieved. When <code>type = "text"</code> , the returned list contains named elements reflecting the source of each text.
<code>language_1</code>	The priority language in which the data will be attempted to be retrieved, in ISO 639 2-char code
<code>language_2</code>	If data not available in <code>'language_1'</code> , try <code>'language_2'</code>
<code>language_3</code>	If data not available in <code>'language_2'</code> , try <code>'language_3'</code>
<code>include_breaks</code>	If TRUE, text includes tags showing where pages (" <code>—pagebreak—</code> ", for pdfs) and documents (" <code>—documentbreak—</code> ") were concatenated

Value

A character vector of length one containing the result.

Examples

```
elx_fetch_data(url = "http://publications.europa.eu/resource/celex/32014R0001", type = "title")
```

```
elx_label_eurovoc      Label EuroVoc concepts
```

Description

Create a look-up table with labels for EuroVoc concept URIs. Only unique identifiers are returned.

Usage

```
elx_label_eurovoc(uri_eurovoc = "", alt_labels = FALSE, language = "en")
```

Arguments

uri_eurovoc	Character vector with valid EuroVoc URIs
alt_labels	If 'TRUE', results include comma-separated alternative labels in addition to the preferred label
language	Language in which to return the labels, in ISO 639 2-char code

Value

A 'tibble' containing EuroVoc unique concept identifiers and labels.

Examples

```
elx_label_eurovoc(uri_eurovoc = "http://eurovoc.europa.eu/5760", alt_labels = TRUE, language = "fr")
elx_label_eurovoc(uri_eurovoc = c("http://eurovoc.europa.eu/5760", "http://eurovoc.europa.eu/576"))
```

```
elx_make_query      Create SPARQL queries
```

Description

Generates pre-defined or manual SPARQL queries to retrieve document ids from Cellar. List of available resource types: <http://publications.europa.eu/resource/authority/resource-type> . Note that not all resource types are compatible with default parameter values.

Usage

```

elx_make_query(
  resource_type = c("directive", "regulation", "decision", "recommendation", "integr",
    "caselaw", "manual", "proposal", "national_impl", "any"),
  manual_type = "",
  directory = NULL,
  sector = NULL,
  include_corrigenda = FALSE,
  include_celex = TRUE,
  include_lbs = FALSE,
  include_date = FALSE,
  include_date_force = FALSE,
  include_date_endvalid = FALSE,
  include_date_transpos = FALSE,
  include_date_lodged = FALSE,
  include_force = FALSE,
  include_eurovoc = FALSE,
  include_author = FALSE,
  include_citations = FALSE,
  include_court_procedure = FALSE,
  include_directory = FALSE,
  include_sector = FALSE,
  order = FALSE,
  limit = NULL
)

```

Arguments

resource_type	Type of resource to be retrieved via SPARQL query
manual_type	Define manually the type of resource to be retrieved
directory	Restrict the results to a given directory code
sector	Restrict the results to a given sector code
include_corrigenda	If 'TRUE', results include corrigenda
include_celex	If 'TRUE', results include CELEX identifier for each resource URI
include_lbs	If 'TRUE', results include legal bases of legislation
include_date	If 'TRUE', results include document date
include_date_force	If 'TRUE', results include date of entry into force
include_date_endvalid	If 'TRUE', results include date of end of validity
include_date_transpos	If 'TRUE', results include date of transposition deadline for directives
include_date_lodged	If 'TRUE', results include date a court case was lodged with the court

include_force If 'TRUE', results include whether legislation is in force
 include_eurovoc
 If 'TRUE', results include EuroVoc descriptors of subject matter
 include_author If 'TRUE', results include document author(s)
 include_citations
 If 'TRUE', results include citations (CELEX-labelled)
 include_court_procedure
 If 'TRUE', results include type of court procedure and outcome
 include_directory
 If 'TRUE', results include the Eur-Lex directory code
 include_sector If 'TRUE', results include the Eur-Lex sector code
 order Order results by ids
 limit Limit the number of results, for testing purposes mainly

Value

A character string containing the SPARQL query

Examples

```

elx_make_query(resource_type = "directive", include_date = TRUE, include_force = TRUE)
elx_make_query(resource_type = "regulation", include_corrigena = TRUE, order = TRUE)
elx_make_query(resource_type = "caselaw")
elx_make_query(resource_type = "manual", manual_type = "SWD")

```

elx_run_query	<i>Execute SPARQL queries</i>
---------------	-------------------------------

Description

Executes cURL request to a pre-defined endpoint of the EU Publications Office. Relies on elx_make_query to generate valid SPARQL queries

Usage

```

elx_run_query(
  query = "",
  endpoint = "http://publications.europa.eu/webapi/rdf/sparql"
)

```

Arguments

query A valid SPARQL query specified by 'elx_make_query' or manually
 endpoint SPARQL endpoint

Value

A data frame containing the results of the SPARQL query. Column 'work' contains the Cellar URI of the resource. Rows with even one missing variable are dropped.

Examples

```
elx_run_query(elx_make_query("directive", include_force = TRUE))
```

Index

`elx_council_votes`, 2
`elx_curia_list`, 2
`elx_fetch_data`, 3
`elx_label_eurovoc`, 4
`elx_make_query`, 4
`elx_run_query`, 6