

Package ‘gllvm’

April 30, 2021

Type Package

Title Generalized Linear Latent Variable Models

Version 1.3.0

Date 2021-4-26

Maintainer Jenni Niku <jenni.m.e.niku@jyu.fi>

Description Analysis of multivariate data using generalized linear latent variable models (gllvm). Estimation is performed using either Laplace approximation method or variational approximation method implemented via TMB (Kristensen et al., (2016), <doi:10.18637/jss.v070.i05>). For details see Niku et al. (2019a) <doi:10.1371/journal.pone.0216129> and Niku et al. (2019b) <doi:10.1111/2041-210X.13303>.

License GPL-2

Imports MASS, Matrix, mvtnorm, statmod, fishMod, mgcv

Depends R (>= 3.5.0), TMB, mvabund

Encoding UTF-8

LazyData true

LinkingTo TMB, RcppEigen

RoxygenNote 7.1.1

NeedsCompilation yes

URL <https://github.com/JenniNiku/gllvm>

BugReports <https://github.com/JenniNiku/gllvm/issues>

Suggests knitr, rmarkdown, testthat, gclus, corrplot, lattice

VignetteBuilder knitr

Author Jenni Niku [aut, cre],
Wesley Brooks [aut],
Riki Herliansyah [aut],
Francis K.C. Hui [aut],
Sara Taskinen [aut],
David I. Warton [aut],
Bert van der Veen [aut]

Repository CRAN

Date/Publication 2021-04-30 17:40:03 UTC

R topics documented:

AICc	2
anova.gllvm	3
coefplot.gllvm	4
confint.gllvm	6
getLV.gllvm	7
getPredictErr.gllvm	7
getResidualCor.gllvm	8
getResidualCov.gllvm	9
gllvm	12
logLik.gllvm	20
microbialdata	21
optima	21
ordiplot.gllvm	22
plot.gllvm	24
predict.gllvm	26
predictLVs.gllvm	28
randomCoefplot.gllvm	29
residuals.gllvm	30
se.gllvm	31
simulate.gllvm	32
sim_bacteria	33
summary.gllvm	33
vcov.gllvm	34
Index	35

AICc

Corrected Akaike information criterion and number of observations

Description

Calculates corrected Akaike information criterion for small sample sizes, and extracts number of observations.

Usage

```
## S3 method for class 'gllvm'
AICc(object, ...)

## S3 method for class 'gllvm'
nobs(object, ...)
```

Arguments

object an object of class 'gllvm'.
 ... Not used.

Author(s)

Jenni Niku, Bert van der Veen

 anova.gllvm

Analysis Of Deviance for gllvm

Description

Computes an analysis of deviance table for two generalized linear latent variable model fits.

Usage

```
## S3 method for class 'gllvm'
anova(object, ..., which = "multi", method = "holm")
```

Arguments

object an object of class 'gllvm'.
 ... one or more objects of class 'gllvm'
 which either "multi" or "uni". If "uni", performs anova for each species separately.
 method method used to adjust p-values for multiple testing when which="uni". One of "holm" (default), "hochberg", "hommel", "bonferonni", "BH", "BY", "fdr", or "none". See [p.adjust](#) for more information.

Details

Computes likelihood-ratio test for two or more gllvm models. Test results makes sense only for nested models. Notice also that this test is not designed for testing models which have degrees of freedom difference larger than 20. For such models the P-value should be treated as very approximate.

Author(s)

Jenni Niku, Bert van der Veen

Examples

```
## Load a dataset from the mvabund package
data(antTraits)
y <- antTraits$abund
X <- antTraits$env
TR <- antTraits$traits
# Fit gllvm model
fit1 <- gllvm(y, X, TR, formula = ~ Bare.ground + Shrub.cover, family = poisson())
fit2 <- gllvm(y, X, TR, formula = ~ Bare.ground + Shrub.cover +
  (Bare.ground + Shrub.cover) : Webers.length, family = poisson())
# Test if the model with fourth corner interaction terms is significantly
# better using likelihood-ratio test:
anova(fit1, fit2)
```

coefplot.gllvm

Plot covariate coefficients and confidence intervals

Description

Plots covariate coefficients and their confidence intervals.

Usage

```
## S3 method for class 'gllvm'
coefplot(
  object,
  y.label = TRUE,
  which.Xcoef = NULL,
  order = TRUE,
  cex.ylab = 0.5,
  mfrow = NULL,
  mar = c(4, 6, 2, 1),
  xlim.list = NULL,
  ...
)
```

Arguments

object	an object of class 'gllvm'.
y.label	logical, if TRUE (default) colnames of y with respect to coefficients are added to plot.
which.Xcoef	vector indicating which covariate coefficients will be plotted. Can be vector of covariate names or numbers. Default is NULL when all covariate coefficients are plotted.
order	logical, whether or not coefficients are ordered, defaults to TRUE.

cex.ylab	the magnification to be used for axis annotation relative to the current setting of cex.
mfrow	same as mfrow in par. If NULL (default) it is determined automatically.
mar	vector of length 4, which defines the margin sizes: c(bottom, left, top, right). Defaults to c(4, 5, 2, 1).
xlim.list	list of vectors with length of two to define the intervals for an x axis in each covariate plot. Defaults to NULL when the interval is defined by the range of point estimates and confidence intervals
...	additional graphical arguments.

Author(s)

Jenni Niku <jenni.m.e.niku@jyu.fi>, Francis K.C. Hui, Sara Taskinen

Examples

```
# Extract subset of the microbial data to be used as an example
data(microbialdata)
X <- microbialdata$Xenv
y <- microbialdata$Y[, order(colMeans(microbialdata$Y > 0),
                              decreasing = TRUE)[21:40]]
fit <- gllvm(y, X, formula = ~ pH + Phosp, family = poisson())
coefplot(fit)
## Not run:
## Load a dataset from the mvabund package
data(antTraits)
y <- as.matrix(antTraits$abund)
X <- as.matrix(antTraits$env)
# Fit model with environmental covariates
fit <- gllvm(y, X, formula = ~ Bare.ground + Shrub.cover,
            family = poisson())
coefplot.gllvm(fit)

# Fit model with all environmental covariates
fitx <- gllvm(y, X, family = "negative.binomial")
coefplot(fitx, mfrow = c(3,2))
coefplot(fitx, which.Xcoef = 1:2)

# Fit gllvm model with environmental and trait covariates
TR <- antTraits$traits
fitT <- gllvm(y = y, X = X, TR = TR, family = "negative.binomial")
coefplot(fitT)

## End(Not run)
```

`confint.gllvm`*Confidence intervals for model parameters*

Description

Computes confidence intervals for parameters in a fitted gllvm model.

Usage

```
## S3 method for class 'gllvm'  
confint(object, parm = NULL, level = 0.95, ...)
```

Arguments

<code>object</code>	an object of class 'gllvm'.
<code>parm</code>	a specification of which parameters are to be given confidence intervals, a vector of names. Examples of options are "beta0", "Xcoef", "theta", "phi". If missing, all parameters are considered.
<code>level</code>	the confidence level. Scalar between 0 and 1.
<code>...</code>	not used.

Author(s)

Jenni Niku <jenni.m.e.niku@jyu.fi>

Examples

```
## Not run:  
## Load a dataset from the mvabund package  
data(antTraits)  
y <- as.matrix(antTraits$abund)  
X <- as.matrix(antTraits$env[,1:2])  
# Fit gllvm model  
fit <- gllvm(y = y, X = X, family = poisson())  
# 95 % confidence intervals for coefficients of X variables  
confint(fit, level = 0.95, parm = "Xcoef")  
  
## End(Not run)
```

getLV.gllvm	<i>Extract latent variables</i>
-------------	---------------------------------

Description

Extract latent variables from gllvm object.

Usage

```
## S3 method for class 'gllvm'
getLV(object)
```

Arguments

object an object of class 'gllvm'.

getPredictErr.gllvm	<i>Extract prediction errors for latent variables from gllvm object</i>
---------------------	---

Description

Calculates the prediction errors for latent variables for gllvm model.

Usage

```
## S3 method for class 'gllvm'
getPredictErr(object, CMSEP = TRUE, ...)
```

Arguments

object	an object of class 'gllvm'.
CMSEP	logical, if TRUE conditional mean squared errors for predictions are calculated. If FALSE, prediction errors are based on covariances of the variational distributions for method = "VA".
...	not used

Details

Calculates conditional mean squared errors for predictions. If variational approximation is used, prediction errors can be based on covariances of the variational distributions, and therefore they do not take into account the uncertainty in the estimation of (fixed) parameters.

Value

Function returns following components:

lvs	prediction errors for latent variables
row.effects	prediction errors for random row effects if included

Author(s)

Francis K.C. Hui, Jenni Niku, David I. Warton

Examples

```
## Not run:  
# Load a dataset from the mvabund package  
data(antTraits)  
y <- as.matrix(antTraits$abund)  
# Fit gllvm model  
fit <- gllvm(y = y, family = poisson())  
# prediction errors for latent variables:  
getPredictErr(fit)  
  
## End(Not run)
```

getResidualCor.gllvm *Extract residual correlations from gllvm object*

Description

Calculates the residual correlation matrix for gllvm model.

Usage

```
## S3 method for class 'gllvm'  
getResidualCor(object, adjust = 1)
```

Arguments

object	an object of class 'gllvm'.
adjust	The type of adjustment used for negative binomial and binomial distribution when computing residual correlation matrix. Options are 0 (no adjustment), 1 (the default adjustment) and 2 (alternative adjustment for NB distribution). See details.

Details

Residual correlation matrix is calculated based on the residual covariance matrix, see details from [getResidualCov.gllvm](#).

Author(s)

Francis K.C. Hui, Jenni Niku, David I. Warton

Examples

```

## Extract subset of the microbial data to be used as an example
data(microbialdata)
y <- microbialdata$Y[, order(colMeans(microbialdata$Y > 0),
                             decreasing = TRUE)[21:40]]
fit <- gllvm(y, family = poisson())
fit$logL
cr <- getResidualCor(fit)
cr[1:5,1:5]
## Not run:
# Load a dataset from the mvabund package
data(antTraits)
y <- as.matrix(antTraits$abund)
# Fit gllvm model
fit <- gllvm(y = y, family = poisson())
# residual correlations:
cr <- getResidualCor(fit)
# Plot residual correlations:
install.packages("corrplot", "gclus")
library(corrplot)
library(gclus)
corrplot(cr[order.single(cr), order.single(cr)], diag = F,
         type = "lower", method = "square", tl.cex = 0.8, tl.srt = 45, tl.col = "red")

## End(Not run)

```

getResidualCov.gllvm *Extract residual covariance matrix from gllvm object*

Description

Calculates the residual covariance matrix for gllvm model.

Usage

```

## S3 method for class 'gllvm'
getResidualCov(object, adjust = 1)

```

Arguments

object	an object of class 'gllvm'.
adjust	The type of adjustment used for negative binomial, binomial and normal distribution when computing residual correlation matrix. Options are 0 (no adjustment), 1 (the default adjustment) and 2 (alternative adjustment for NB distribution), see details.

Details

Residual covariance matrix, storing information on species co-occurrence that is not explained by the environmental variables (if included), is calculated using the matrix of latent variables loadings, that is, $\Theta\Theta'$.

When the responses are modelled using the negative binomial distribution, the residual variances for each species must be adjusted for overdispersion. The two possible adjustment terms are $\log(\phi_j + 1)$ (adjust = 1) and $\psi^{(1)}(1/\phi_j)$ (adjust = 2), where $\psi^{(1)}$ is the trigamma function.

The negative binomial model can be written using different parametrizations. The residual covariance with adjust = 1 can be obtained using the lognormal-Poisson parametrization, that is,

$$Y_{ij} \sim \text{Poisson}(\mu_{ij}\lambda_j),$$

where $\lambda_j \sim \text{lognormal}(-\sigma^2/2, \sigma^2)$ and $\sigma^2 = \log(\phi_j + 1)$ and $\log(\mu_{ij}) = \eta_{ij}$. Now $E[Y_{ij}] = \mu_{ij}$ and variance $V(\mu_{ij}) = \mu_{ij} + \mu_{ij}^2(\exp(\sigma^2) - 1) = \mu_{ij} + \mu_{ij}^2\phi_j$, which are the same as for the NB distribution. Therefore, on linear predictor scale, we have the variance

$$V(\log(\mu_{ij}\lambda_j)) = V(\log\mu_{ij}) + V(\log\lambda_j) = V(u_i'\theta_j) + \sigma^2 = \theta_j'\theta_j + \log(\phi_j + 1).$$

which leads to the residual covariance matrix $\Theta\Theta' + \Psi$, where Ψ is the diagonal matrix with $\log(\phi_j + 1)$ as diagonal elements (adjust = 1).

Or, for a GLLVM where species are a quadratic function of the latent variables, we instead have

$$V(\log(\mu_{ij}\lambda_j)) = V(\log\mu_{ij}) + V(\log\lambda_j) = V(u_i'\theta_j - u_i'D_ju_i) + \sigma^2 = \theta_j'\theta_j + 2\text{diag}(D_j)'\text{diag}(D_j)\log(\phi_j + 1).$$

which leads to the residual covariance matrix $\Theta\Theta' + 2\Gamma_j\Gamma_j' + \text{diag}(\Phi)$, where Γ_j holds the quadratic coefficients. Since the quadratic coefficients are constrained to be positive, the residual covariance in the latter case is, given the same coefficients on the linear term, equal or more positive than in the linear case.

The residual covariance matrix with adjust = 2 can be obtained by using Poisson-Gamma parametrization

$$Y_{ij} \sim \text{Poisson}(\mu_{ij}\lambda_j),$$

where $\lambda_j \sim \text{Gamma}(1/\phi_j, 1/\phi_j)$ and μ_{ij} is as above. The mean and the variance are of similar form as above and we have that

$$V(\log(\mu_{ij}\lambda_j)) = V(\log\mu_{ij}) + V(\log\lambda_j) = \theta_j'\theta_j + \psi^{(1)}(1/\phi_j),$$

where $\psi^{(1)}$ is the trigamma function.

In the case of binomial distribution, the adjustment terms (adjust = 1) are 1 for probit link and $\pi^2/3$ for logit link. These are obtained by treating binomial model as latent variable model. Assume

$$Y_{ij}^* = \eta_{ij} + e_{ij},$$

where $e_{ij} \sim N(0, 1)$ for probit model, and $e_{ij} \sim \text{logistic}(0, 1)$ for logit model. Then binary response is defined as $Y_{ij} = 1$, if $Y_{ij}^* > 0$ and 0 otherwise. Now we have that $\mu_{ij} = P(Y_{ij} = 1) = P(Y_{ij}^* > 0) = P(\eta_{ij} > -e_{ij}) = P(e_{ij} < \eta_{ij})$ which leads to probit and logit models. On linear predictor scale we then have that

$$V(\eta_{ij} + e_{ij}) = V(\eta_{ij}) + V(e_{ij}).$$

For the probit model, the residual covariance matrix is then $\Theta\Theta' + I_m$, and for the logit model $\Theta\Theta' + \pi^2/3I_m$. Similarly as above, for a GLLVM where species are a quadratic function of the latent variables, the term $2\Gamma_j\Gamma_j'$ is added to the residual covariance matrix.

For normal distribution, we can write

$$Y_{ij} = \eta_{ij} + e_{ij},$$

where $e_{ij} \sim N(0, \phi_j^2)$ and thus we have that

$$V(\eta_{ij} + e_{ij}) = V(\eta_{ij}) + V(e_{ij}).$$

For the gaussian model, the residual covariance matrix is then $\Theta\Theta' + \text{diag}(\Phi^2)$.

Value

Function returns following components:

cov	residual covariance matrix
trace	trace of the residual covariance matrix
trace.q	trace of the residual covariance matrix per latent variable

Author(s)

Francis K.C. Hui, Jenni Niku, David I. Warton, Bert van der Veen

Examples

```
## Not run:
# Load a dataset from the mvabund package
data(antTraits)
y <- as.matrix(antTraits$abund)
# Fit gllvm model
fit <- gllvm(y = y, family = poisson())
# residual covariance:
rescov <- getResidualCov(fit)
rescov$cov
# Trace of the covariance matrix
rescov$trace
# Trace per latent variable
rescov$trace.q

## End(Not run)
```

Description

Fits generalized linear latent variable model for multivariate data. The model can be fitted using Laplace approximation method or variational approximation method.

Usage

```
gllvm(
  y = NULL,
  X = NULL,
  TR = NULL,
  data = NULL,
  formula = NULL,
  num.lv = 2,
  family,
  row.eff = FALSE,
  offset = NULL,
  quadratic = FALSE,
  sd.errors = TRUE,
  method = "VA",
  randomX = NULL,
  dependent.row = FALSE,
  beta0com = FALSE,
  zeta.struc = "species",
  plot = FALSE,
  link = "probit",
  Power = 1.1,
  seed = NULL,
  scale.X = TRUE,
  return.terms = TRUE,
  gradient.check = FALSE,
  control = list(reltol = 1e-10, TMB = TRUE, optimizer = "optim", max.iter = 200, maxit
    = 4000, trace = FALSE, optim.method = NULL),
  control.va = list(Lambda.struc = "unstructured", Ab.struc = "unstructured",
    diag.iter = 1, Ab.diag.iter = 0, Lambda.start = c(0.3, 0.3, 0.3)),
  control.start = list(starting.val = "res", n.init = 1, jitter.var = 0, start.fit =
    NULL, start.lvs = NULL, randomX.start = "zero", quad.start = 0.01, start.struc =
    "LV"),
  ...
)
```

Arguments

`y` (n x m) matrix of responses.

X	matrix or data.frame of environmental covariates.
TR	matrix or data.frame of trait covariates.
data	data in long format, that is, matrix of responses, environmental and trait covariates and row index named as "id". When used, model needs to be defined using formula. This is alternative data input for y, X and TR.
formula	an object of class "formula" (or one that can be coerced to that class): a symbolic description of the model to be fitted.
num.lv	number of latent variables, d, in gllvm model. Non-negative integer, less than number of response variables (m). Defaults to 2.
family	distribution function for responses. Options are <code>poisson(link = "log")</code> , <code>"negative.binomial"</code> (with log link), <code>binomial(link = "probit")</code> (and also <code>binomial(link = "logit")</code> when <code>method = "LA"</code>), <code>zero.inflated.poisson("ZIP")</code> , <code>gaussian(link = "identity")</code> , <code>"gamma"</code> (with log link), <code>"exponential"</code> (with log link), <code>Tweedie("tweedie")</code> (with log link, for "LA" and "EVA"-method), <code>beta("beta")</code> (with logit and probit link, for "LA" and "EVA"-method) and <code>"ordinal"</code> (only with "VA"-method).
row.eff	FALSE, fixed or "random", Indicating whether row effects are included in the model as a fixed or as a random effects. Defaults to FALSE when row effects are not included.
offset	vector or matrix of offset terms.
quadratic	either FALSE(default), TRUE, or LV. If FALSE models species responses as a linear function of the latent variables. If TRUE models species responses as a quadratic function of the latent variables. If LV assumes species all have the same quadratic coefficient per latent variable.
sd.errors	logical. If TRUE (default) standard errors for parameter estimates are calculated.
method	model can be fitted using Laplace approximation method (<code>method = "LA"</code>) or variational approximation method (<code>method = "VA"</code>), or with extended variational approximation method (<code>method = "EVA"</code>) when VA is not applicable. If particular model has not been implemented using the selected method, model is fitted using the alternative method as a default. Defaults to "VA".
randomX	formula for species specific random effects of environmental variables in fourth corner model. Defaults to NULL, when random slopes are not included.
dependent.row	logical, whether or not random row effects are correlated (dependent) with the latent variables. Defaults to FALSE when correlation terms are not included.
beta0com	logical, if FALSE column-specific intercepts are assumed. If TRUE, a common intercept is used which is allowed only for fourth corner models.
zeta.struc	Structure for cut-offs in the ordinal model. Either "common", for the same cut-offs for all species, or "species" for species-specific cut-offs. For the latter, classes are arbitrary per species, each category per species needs to have at least one observations. Defaults to "species".
plot	logical, if TRUE ordination plots will be printed in each iteration step when TMB = FALSE. Defaults to FALSE.
link	link function for binomial family if <code>method = "LA"</code> and beta family. Options are "logit" and "probit".

Power	fixed power parameter in Tweedie model. Scalar from interval (1,2). Defaults to 1.1.
seed	a single seed value, defaults to NULL.
scale.X	if TRUE, covariates are scaled when fourth corner model is fitted.
return.terms	logical, if TRUE 'terms' object is returned.
gradient.check	logical, if TRUE gradients are checked for large values (>0.01) even if the optimization algorithm did converge.
control	<p>A list with the following arguments controlling the optimization:</p> <ul style="list-style-type: none"> • <i>reltol</i>: convergence criteria for log-likelihood, defaults to 1e-8. • <i>TMB</i>: logical, if TRUE model will be fitted using Template Model Builder (TMB). TMB is always used if method = "LA". Defaults to TRUE. • <i>optimizer</i>: if TMB=TRUE, log-likelihood can be optimized using "optim" (default) or "nlminb". • <i>max.iter</i>: maximum number of iterations when TMB = FALSE or for optimizer = "nlminb" when TMB = TRUE, defaults to 200. • <i>maxit</i>: maximum number of iterations for optimizer, defaults to 4000. • <i>trace</i>: logical, if TRUE in each iteration step information on current step will be printed. Defaults to FALSE. Only with TMB = FALSE. • <i>optim.method</i>: optimization method to be used if optimizer is "optim". Defaults to "BFGS", and "L-BFGS-B" to Tweedie family due the limited-memory use.
control.va	<p>A list with the following arguments controlling the variational approximation method:</p> <ul style="list-style-type: none"> • <i>Lambda.struc</i>: covariance structure of VA distributions for latent variables when method = "VA", "unstructured" or "diagonal". • <i>Ab.struc</i>: covariance structure of VA distributions for random slopes when method = "VA", "unstructured" or "diagonal". • <i>diag.iter</i>: non-negative integer which can sometimes be used to speed up the updating of variational (covariance) parameters in VA method. Can sometimes improve the accuracy. If TMB = TRUE either 0 or 1. Defaults to 1. • <i>Ab.diag.iter</i>: As above, but for variational covariance of random slopes. • <i>Lambda.start</i>: starting values for variances in VA distributions for latent variables, random row effects and random slopes in variational approximation method. Defaults to 0.2.
control.start	<p>A list with the following arguments controlling the starting values:</p> <ul style="list-style-type: none"> • <i>starting.val</i>: starting values can be generated by fitting model without latent variables, and applying factorial analysis to residuals to get starting values for latent variables and their coefficients (<i>starting.val</i> = "res"). Another options are to use zeros as a starting values (<i>starting.val</i> = "zero") or initialize starting values for latent variables with (n x num.lv) matrix. Defaults to "res", which is recommended. • <i>n.init</i>: number of initial runs. Uses multiple runs and picks up the one giving highest log-likelihood value. Defaults to 1.

- *start.fit*: object of class 'gllvm' which can be given as starting parameters for count data (poisson, NB, or ZIP).
 - *start.lvs*: initialize starting values for latent variables with (n x num.lv) matrix. Defaults to NULL.
 - *jitter.var*: jitter variance for starting values of latent variables. Defaults to 0, meaning no jittering.
 - *randomX.start*: Starting value method for the random slopes. Options are "zero" and "res". Defaults to "zero".
 - *start.struc*: Starting value method for the quadratic term. Options are "LV" (default) and "all".
 - *quad.start*: Starting values for quadratic coefficients. Defaults to 0.01.
- ... Not used.

Details

Fits generalized linear latent variable models as in Hui et al. (2015 and 2017) and Niku et al. (2017). Method can be used with two types of latent variable models depending on covariates. If only site related environmental covariates are used, the expectation of response Y_{ij} is determined by

$$g(\mu_{ij}) = \eta_{ij} = \alpha_i + \beta_{0j} + x'_i \beta_j + u'_i \theta_j,$$

where $g(\cdot)$ is a known link function, u_i are d -variate latent variables ($d \ll m$), α_i is an optional row effect at site i , and it can be fixed or random effect, β_{0j} is an intercept term for species j , β_j and θ_j are column specific coefficients related to covariates and the latent variables, respectively.

Alternatively, a more complex version of the model can be fitted with `quadratic = TRUE`, where species are modeled as a quadratic function of the latent variables:

$$g(\mu_{ij}) = \eta_{ij} = \alpha_i + \beta_{0j} + x'_i \beta_j + u'_i \theta_j - u'_i D_j u_i$$

. Here, D_j is a diagonal matrix of positive only quadratic coefficients, so that the model generates concave shapes only. This implementation follows the ecological theoretical model where species are generally recognized to exhibit non-linear response curves. For a model with quadratic responses, quadratic coefficients are assumed to be the same for all species:

$$D_j = D$$

. This model requires less information per species and can be expected to be more applicable to most datasets. The quadratic coefficients D can be used to calculate the length of ecological gradients.

An alternative model is the fourth corner model (Brown et al., 2014, Warton et al., 2015) which will be fitted if also trait covariates are included. The expectation of response Y_{ij} is

$$g(\mu_{ij}) = \alpha_i + \beta_{0j} + x'_i(\beta_x + b_j) + TR'_j \beta_t + \text{vec}(B) * \text{kroncker}(TR_j, X_i) + u'_i \theta_j - u'_i D_j u_i$$

where $g(\cdot)$, u_i , β_{0j} and θ_j are defined as above. Vectors β_x and β_t are the main effects or coefficients related to environmental and trait covariates, respectively, matrix B includes interaction terms. Vectors b_j are optional species-specific random slopes for environmental covariates. The interaction/fourth corner terms are optional as well as are the main effects of trait covariates.

The method is sensitive for the choices of initial values of the latent variables. Therefore it is recommendable to use multiple runs and pick up the one giving the highest log-likelihood value. However, sometimes this is computationally too demanding, and default option `starting.val = "res"` is recommended. For more details on different starting value methods, see Niku et al., (2018).

For quadratic responses, it can be useful to provide the latent variables estimated with a GLLVM with linear responses, or estimated with (Detrended) Correspondence Analysis. The latent variables can then be passed to the `start.lvs` argument inside the `control.start` list, which in many cases gives good results. For a GLLVM with quadratic responses and poisson distribution, it is recommended to fit GLLVM with linear responses and a negative binomial distribution, or using a Poisson distribution with random row-effects, instead. This is because the quadratic term can account for overdispersion in the Poisson case, which needs to be separately accounted for with linear responses. As a result, it should rarely be required to fit a GLLVM with quadratic responses and negative binomial distribution (or row-effects).

Models are implemented using TMB (Kristensen et al., 2015) applied to variational approximation (Hui et al., 2017) and Laplace approximation (Niku et al., 2017).

With ordinal family response classes must start from 0 or 1.

Distributions:

Mean and variance for distributions are defined as follows.

- For count data family = `poisson()`: Expectation $E[Y_{ij}] = \mu_{ij}$, variance $V(\mu_{ij}) = \mu_{ij}$, or
- family = "negative.binomial": Expectation $E[Y_{ij}] = \mu_{ij}$, variance $V(\mu_{ij}) = \mu_{ij} + \mu_{ij}^2 \phi_j$, or
- family = "ZIP": Expectation $E[Y_{ij}] = (1-p)\mu_{ij}$, variance $V(\mu_{ij}) = \mu_{ij}(1-p)(1 + \mu_{ij}p)$.
- For binary data family = `binomial()`: Expectation $E[Y_{ij}] = \mu_{ij}$, variance $V(\mu_{ij}) = \mu_{ij}(1 - \mu_{ij})$.
- For percent cover data $0 < Y_{ij} < 1$ family = "beta": Expectation $E[Y_{ij}] = \mu_{ij}$, variance $V(\mu_{ij}) = \mu_{ij}(1 - \mu_{ij}) / (1 + \phi_j)$.
- For positive continuous data family = "gamma": Expectation $E[Y_{ij}] = \mu_{ij}$, variance $V(\mu_{ij}) = \mu_{ij}^2 / \phi_j$, where ϕ_j is species specific shape parameter.
- For non-negative continuous data family = "exponential": Expectation $E[Y_{ij}] = \mu_{ij}$, variance $V(\mu_{ij}) = \mu_{ij}^2$.
- For non-negative continuous or biomass data family = "tweedie" Expectation $E[Y_{ij}] = \mu_{ij}$, variance $V(\mu_{ij}) = \phi_j * \mu_{ij}^\nu$, where ν is a power parameter of Tweedie distribution. See details Dunn and Smyth (2005).
- For ordinal data family = "ordinal": Cumulative probit model, see Hui et.al. (2016).
- For normal distributed data family = `gaussian()`: Expectation $E[Y_{ij}] = \mu_{ij}$, variance $V(y_{ij}) = \phi_j^2$.

Value

An object of class "gllvm" includes the following components:

<code>call</code>	function call
<code>logL</code>	log likelihood
<code>lvs</code>	latent variables

params	list of parameters <ul style="list-style-type: none"> • theta coefficients related to latent variables • beta0 column specific intercepts • Xcoef coefficients related to environmental covariates X • B coefficients in fourth corner model • row.params row-specific intercepts • phi dispersion parameters ϕ for negative binomial or Tweedie family, probability of zero inflation for ZIP family, standard deviation for gaussian family or shape parameter for gamma family • inv.phi dispersion parameters $1/\phi$ for negative binomial
Power	power parameter ν for Tweedie family
sd	list of standard errors of parameters
prediction.errors	list of prediction covariances for latent variables and variances for random row effects when method "LA" is used
A, Ar	covariance matrices for variational densities of latent variables and variances for random row effects

Note

If function gives warning: 'In f(x, order = 0) : value out of range in 'lgamma'', optimizer have visited an area where gradients become too big. It is automatically fixed by trying another step in the optimization process, and can be ignored if errors do not occur.

Author(s)

Jenni Niku <jenni.m.e.niku@jyu.fi>, Wesley Brooks, Riki Herliansyah, Francis K.C. Hui, Sara Taskinen, David I. Warton, Bert van der Veen

References

- Brown, A. M., Warton, D. I., Andrew, N. R., Binns, M., Cassis, G., and Gibb, H. (2014). The fourth-corner solution - using predictive models to understand how species traits interact with the environment. *Methods in Ecology and Evolution*, 5:344-352.
- Dunn, P. K. and Smyth, G. K. (2005). Series evaluation of tweedie exponential dispersion model densities. *Statistics and Computing*, 15:267-280.
- Hui, F. K. C., Taskinen, S., Pledger, S., Foster, S. D., and Warton, D. I. (2015). Model-based approaches to unconstrained ordination. *Methods in Ecology and Evolution*, 6:399-411.
- Hui, F. K. C., Warton, D., Ormerod, J., Haapaniemi, V., and Taskinen, S. (2017). Variational approximations for generalized linear latent variable models. *Journal of Computational and Graphical Statistics*. *Journal of Computational and Graphical Statistics*, 26:35-43.
- Kasper Kristensen, Anders Nielsen, Casper W. Berg, Hans Skaug, Bradley M. Bell (2016). TMB: Automatic Differentiation and Laplace Approximation. *Journal of Statistical Software*, 70(5), 1-21.
- Niku, J., Warton, D. I., Hui, F. K. C., and Taskinen, S. (2017). Generalized linear latent variable models for multivariate count and biomass data in ecology. *Journal of Agricultural, Biological, and Environmental Statistics*, 22:498-522.

Niku, J., Brooks, W., Herliansyah, R., Hui, F. K. C., Taskinen, S., and Warton, D. I. (2018). Efficient estimation of generalized linear latent variable models. *PLoS One*, 14(5):1-20.

Warton, D. I., Guillaume Blanchet, F., O'Hara, R. B., Ovaskainen, O., Taskinen, S., Walker, S. C. and Hui, F. K. C. (2015). So many variables: Joint modeling in community ecology. *Trends in Ecology & Evolution*, 30:766-779.

See Also

[coefplot.gllvm](#), [confint.gllvm](#), [ordiplot.gllvm](#), [plot.gllvm](#), [residuals.gllvm](#), [summary.gllvm](#).

Examples

```
# Extract subset of the microbial data to be used as an example
data(microbialdata)
X <- microbialdata$Xenv
y <- microbialdata$Y[, order(colMeans(microbialdata$Y > 0),
                             decreasing = TRUE)[21:40]]
fit <- gllvm(y, X, formula = ~ pH + Phosp, family = poisson())
fit$logL
ordiplot(fit)
coefplot(fit)

## Load a dataset from the mvabund package
library(mvabund)
data(antTraits)
y <- as.matrix(antTraits$abund)
X <- as.matrix(antTraits$env)
TR <- antTraits$traits
# Fit model with environmental covariates Bare.ground and Shrub.cover
fit <- gllvm(y, X, formula = ~ Bare.ground + Shrub.cover,
            family = poisson())
ordiplot(fit)
coefplot(fit)

## Example 1: Fit model with two latent variables
# Using variational approximation:
fitv0 <- gllvm(y, family = "negative.binomial", method = "VA")
ordiplot(fitv0)
plot(fitv0, mfrow = c(2,2))
summary(fitv0)
confint(fitv0)
# Using Laplace approximation: (this line may take about 30 sec to run)
fitl0 <- gllvm(y, family = "negative.binomial", method = "LA")
ordiplot(fitl0)

# Poisson family:
fit.p <- gllvm(y, family = poisson(), method = "LA")
ordiplot(fit.p)
# Use poisson model as a starting parameters for ZIP-model, this line may take few minutes to run
fit.z <- gllvm(y, family = "ZIP", method = "LA", control.start = list(start.fit = fit.p))
ordiplot(fit.z)
```

```

## Example 2: gllvm with environmental variables
# Fit model with two latent variables and all environmental covariates,
fitvX <- gllvm(formula = y ~ X, family = "negative.binomial")
ordiplot(fitvX, biplot = TRUE)
coefplot(fitvX)
# Fit model with environmental covariates Bare.ground and Shrub.cover
fitvX2 <- gllvm(y, X, formula = ~ Bare.ground + Shrub.cover,
  family = "negative.binomial")
ordiplot(fitvX2)
coefplot(fitvX2)
# Use 5 initial runs and pick the best one
fitvX_5 <- gllvm(y, X, formula = ~ Bare.ground + Shrub.cover,
  family = "negative.binomial", control.start=list(n.init = 5, jitter.var = 0.1))
ordiplot(fitvX_5)
coefplot(fitvX_5)

## Example 3: Data in long format
# Reshape data to long format:
datalong <- reshape(data.frame(cbind(y,X)), direction = "long",
  varying = colnames(y), v.names = "y")
head(datalong)
fitvLong <- gllvm(data = datalong, formula = y ~ Bare.ground + Shrub.cover,
  family = "negative.binomial")

## Example 4: Fourth corner model
# Fit fourth corner model with two latent variables
fitF1 <- gllvm(y = y, X = X, TR = TR, family = "negative.binomial")
coefplot(fitF1)
# Fourth corner can be plotted also with next lines
#fourth = fitF1$fourth.corner
#library(lattice)
#a = max( abs(fourth) )
#colort = colorRampPalette(c("blue","white","red"))
#plot.4th = levelplot(t(as.matrix(fourth)), xlab = "Environmental Variables",
#  ylab = "Species traits", col.regions = colort(100),
#  at = seq( -a, a, length = 100), scales = list( x = list(rot = 45)))
#print(plot.4th)

# Specify model using formula
fitF2 <- gllvm(y = y, X = X, TR = TR,
  formula = ~ Bare.ground + Canopy.cover * (Pilosity + Webers.length),
  family = "negative.binomial")
ordiplot(fitF2)
coefplot(fitF2)

## Include species specific random slopes to the fourth corner model
fitF3 <- gllvm(y = y, X = X, TR = TR,
  formula = ~ Bare.ground + Canopy.cover * (Pilosity + Webers.length),
  family = "negative.binomial", randomX = ~ Bare.ground + Canopy.cover,
  control.start = list(n.init = 3))
ordiplot(fitF3)

```

```
coefplot(fitF3)

## Example 5: Fit Tweedie model
# Load coral data
data(tikus)
ycoral <- tikus$abund
# Let's consider only years 1981 and 1983
ycoral <- ycoral[((tikus$time == 81) + (tikus$time == 83)) > 0, ]
# Exclude species which have observed at less than 4 sites
ycoral <- ycoral[-17, (colSums(ycoral > 0) > 4)]
# Fit Tweedie model for coral data (this line may take few minutes to run)
fit.twe <- gllvm(y = ycoral, family = "tweedie", method = "LA")
ordiplot(fit.twe)

## Example 6: Random row effects
fitRand <- gllvm(y, family = "negative.binomial", row.eff = "random")
ordiplot(fitRand, biplot = TRUE)
```

logLik.gllvm

Log-likelihood of gllvm

Description

Extracts Log-likelihood from 'gllvm' objects.

Usage

```
## S3 method for class 'gllvm'
logLik(object, ...)
```

Arguments

object	an object of class 'gllvm'.
...	not used.

Author(s)

David I. Warton, Jenni Niku

Examples

```
## Not run:
## Load a dataset from the mvabund package
data(antTraits)
y <- as.matrix(antTraits$abund)
# Fit gllvm model
fit <- gllvm(y = y, family = poisson())
```

```
# log-Likelihood:
logLik(fit)

## End(Not run)
```

microbialdata	<i>Microbial community data</i>
---------------	---------------------------------

Description

Microbial community data consist of abundances of 985 bacteria species measured at 56 soil sample sites from three regions, Kilpisjarvi (Finland), Ny-Alesund (Norway), and Mayrhofen (Austria). In addition to bacteria counts, three continuous environmental variables (pH, available phosphorous and soil organic matter) were measured from each soil sample.

Usage

```
data(microbialdata)
```

Format

- Y** A data frame with abundances of 985 bacteria species measured at 56 soil sample sites
- X** Environmental variables SOM: soil organic matter, pH: soil pH value and Phosp: available phosphorus and information from the samples, including Region: sampling region (Kilpisjarvi (Finland), Ny-Alesund (Norway), and Mayrhofen (Austria).), Site: sampling site and Soiltype: soil sample type (top soil (T) or bottom soil (B))

References

- Kumar, M., Brader, G., Sessitsch, A., Mäki, A., van Elsas, J.D., and Nissinen, R. (2017). Plants Assemble Species Specific Bacterial Communities from Common Core Taxa in Three Arcto-Alpine Climate Zones. *Frontiers in Microbiology*, 8:12.
- Niku, J., Warton, D. I., Hui, F. K. C., and Taskinen, S. (2017). Generalized linear latent variable models for multivariate count and biomass data in ecology. *Journal of Agricultural, Biological, and Environmental Statistics*, 22:498-522.

optima	<i>Functions to extract ecological quantities of the latent variables from a GLLVM, if species are a quadratic function of the latent variables.</i>
--------	--

Description

Extracts species optima, tolerances or gradient lengths, potentially with standard errors (derived with the Delta method).

Usage

```
## S3 method for class 'gllvm'  
optima(object, sd.errors = TRUE, ...)  
  
## S3 method for class 'gllvm'  
tolerances(object, sd.errors = TRUE, ...)  
  
## S3 method for class 'gllvm'  
gradient.length(object, sd.errors = TRUE, ...)
```

Arguments

object	an object of class 'gllvm'.
sd.errors	logical. If TRUE, also returns standard errors.
...	Not used.

Author(s)

Bert van der Veen

ordiplot.gllvm

Plot latent variables from gllvm model

Description

Plots latent variables and their corresponding coefficients (biplot).

Usage

```
## S3 method for class 'gllvm'  
ordiplot(  
  object,  
  biplot = FALSE,  
  ind.spp = NULL,  
  alpha = 0.5,  
  main = NULL,  
  which.lvs = c(1, 2),  
  predict.region = FALSE,  
  level = 0.95,  
  jitter = FALSE,  
  jitter.amount = 0.2,  
  s.colors = 1,  
  symbols = FALSE,  
  cex.spp = 0.7,  
  spp.colors = "blue",  
  lwd.ellips = 0.5,
```

```

    col.ellips = 4,
    lty.ellips = 1,
    ...
)

```

Arguments

object	an object of class 'gllvm'.
biplot	TRUE if both latent variables and their coefficients are plotted, FALSE if only latent variables.
ind.spp	the number of response variables (usually, species) to include on the biplot. The default is none, or all if biplot = TRUE.
alpha	a numeric scalar between 0 and 1 that is used to control the relative scaling of the latent variables and their coefficients, when constructing a biplot.
main	main title.
which.lvs	indices of two latent variables to be plotted if number of the latent variables is more than 2. A vector with length of two. Defaults to c(1, 2).
predict.region	logical, if TRUE prediction regions for the predicted latent variables are plotted, defaults to FALSE.
level	level for prediction regions.
jitter	if TRUE, jittering is applied on points.
jitter.amount	numeric, positive value indicating an amount of jittering for each point, defaults to 0.2 (jitter range).
s.colors	colors for sites
symbols	logical, if TRUE sites are plotted using symbols, if FALSE (default) site numbers are used
cex.spp	size of species labels in biplot
spp.colors	colors for sites, defaults to "blue"
lwd.ellips	line width for prediction ellipses. See graphical parameter lwd.
col.ellips	colors for prediction ellipses.
lty.ellips	line type for prediction ellipses. See graphical parameter lty.
...	additional graphical arguments.

Details

Function constructs a scatter plot of two latent variables, i.e. an ordination plot. If only one latent variable is in the fitted model, latent variables are plotted against their corresponding row indices. The latent variables are labeled using the row index of the response matrix y .

Coefficients related to latent variables are plotted in the same figure with the latent variables if `biplot = TRUE`. They are labeled using the column names of y . The number of latent variable coefficients to be plotted can be controlled by `ind.spp`. An argument `alpha` is used to control the relative scaling of the latent variables and their coefficients. If `alpha = 0.5`, the latent variables and their coefficients are on the same scale. For details for constructing a biplot, see Gabriel (1971).

Note

- If error is occurred when using ordiplot(), try full name of the function ordiplot.gllvm() as functions named 'ordiplot' might be found in other packages as well.

Author(s)

Jenni Niku <jenni.m.e.niku@jyu.fi>, Francis K.C. Hui

References

Gabriel, K. R. (1971). The biplot graphic display of matrices with application to principal component analysis. *Biometrika*, 58, 453-467.

Examples

```
## Extract subset of the microbial data to be used as an example
data(microbialdata)
y <- microbialdata$Y[, order(colMeans(microbialdata$Y > 0),
                             decreasing = TRUE)[21:40]]
fit <- gllvm(y, family = poisson())
fit$logL
ordiplot(fit, predict.region = TRUE)
## Not run:
### Load a dataset from the mvabund package
data(antTraits)
y <- as.matrix(antTraits$abund)
fit <- gllvm(y, family = poisson())
# Ordination plot:
ordiplot(fit)
# Biplot with 10 species
ordiplot(fit, biplot = TRUE, ind.spp = 10)

## End(Not run)
```

plot.gllvm

Plot Diagnostics for an gllvm Object

Description

Five plots (selectable by which) are currently available: a plot of residuals against linear predictors of fitted values, a Normal Q-Q plot of residuals with a simulated point-wise 95% confidence interval envelope, residuals against row index and column index and scale location plot.

Usage

```
## S3 method for class 'gllvm'
plot(
  x,
```

```

    which = 1:5,
    caption = c("Residuals vs linear predictors", "Normal Q-Q", "Residuals vs row index",
               "Residuals vs column index", "Scale-Location"),
    var.colors = NULL,
    add.smooth = TRUE,
    envelopes = TRUE,
    reps = 150,
    envelope.col = c("blue", "lightblue"),
    n.plot = NULL,
    ...
  )

```

Arguments

x	an object of class 'gllvm'.
which	if a subset of the plots is required, specify a subset of the numbers 1:5, see caption below.
caption	captions to appear above the plots.
var.colors	colors for responses, vector with length of number of response variables or 1. Defaults to NULL, when different responses have different colors.
add.smooth	logical indicating if a smoother should be added.
envelopes	logical, indicating if simulated point-wise confidence interval envelope will be added to Q-Q plot, defaults to TRUE
reps	number of replications when simulating confidence envelopes for normal Q-Q plot
envelope.col	colors for envelopes, vector with length of two
n.plot	number of species (response variables) to be plotted. Defaults to NULL when all response variables are plotted. Might be useful when data is very high dimensional.
...	additional graphical arguments.

Details

plot.gllvm is used for model diagnostics. Dunn-Smyth residuals (randomized quantile residuals) (Dunn and Smyth, 1996) are used in plots. Colors indicate different species.

Author(s)

Jenni Niku <jenni.m.e.niku@jyu.fi>

References

Dunn, P. K., and Smyth, G. K. (1996). Randomized quantile residuals. *Journal of Computational and Graphical Statistics*, 5, 236-244.

Hui, F. K. C., Taskinen, S., Pledger, S., Foster, S. D., and Warton, D. I. (2015). Model-based approaches to unconstrained ordination. *Methods in Ecology and Evolution*, 6:399-411.

See Also

[gllvm, residuals.gllvm](#)

Examples

```
## Not run:
## Load a dataset from the mvabund package
data(antTraits)
y <- as.matrix(antTraits$abund)
# Fit gllvm model with Poisson family
fit <- gllvm(y, family = poisson())
# Plot residuals
plot(fit, mfrow = c(3,2))

\donttest{
# Fit gllvm model with negative binomial family
fitnb <- gllvm(y = y, family = "negative.binomial")
# Plot residuals
plot(fitnb, mfrow = c(3,2))
# Plot only two first plots
plot(fitnb, which = 1:2, mfrow = c(1,2))
}

## End(Not run)
```

predict.gllvm

Predict Method for gllvm Fits

Description

Obtains predictions from a fitted generalized linear latent variable model object.

Usage

```
## S3 method for class 'gllvm'
predict(object, newX = NULL, newTR = NULL, newLV = NULL, type = "link", ...)
```

Arguments

object	an object of class 'gllvm'.
newX	A new data frame of environmental variables. If omitted, the original matrix of environmental variables is used.
newTR	A new data frame of traits for each response taxon. If omitted, the original matrix of traits is used.
newLV	A new matrix of latent variables. If omitted, the original matrix of latent variables is used.

type	the type of prediction required. The default ("link") is on the scale of the linear predictors; the alternative "response" is on the scale of the response variable. that is, the predictions for the binomial model are predicted probabilities. In case of ordinal data, type = "response" gives predicted probabilities for each level of ordinal variable.
...	not used.

Details

If newX, newTR and newLV are omitted the predictions are based on the data used for fitting the model. Notice that newTR need to match with the number of species in the original data. Instead, new sites can be specified in newX. If predictors newX (and newTR) are given, and newLV is not, latent variables are not used in the predictions.

Value

A matrix containing requested predictor types.

Author(s)

Jenni Niku <jenni.m.e.niku@jyu.fi>, David Warton

Examples

```
# Load a dataset from the mvabund package
data(antTraits)
y <- as.matrix(antTraits$abund)
X <- scale(antTraits$env[, 1:3])
# Fit gllvm model
fit <- gllvm(y = y, X, family = poisson())
# fitted values
predfit <- predict(fit, type = "response")

# linear predictors
predlin <- predict(fit)
# Predict new sites:
# Generate matrix of environmental variables for 10 new sites
xnew <- cbind(rnorm(10), rnorm(10), rnorm(10))
colnames(xnew) <- colnames(X)
predfit <- predict(fit, newX = xnew, type = "response")

TR <- (antTraits$tr[, 1:3])
fitt <- gllvm(y = y, X, TR, family = poisson())
# linear predictors
predlin <- predict(fitt)
# Predict new sites:
# Generate matrix of environmental variables for 10 new sites
xnew <- cbind(rnorm(10), rnorm(10), rnorm(10))
colnames(xnew) <- colnames(X)
# Generate matrix of traits for species
```

```
trnew <- data.frame(Femur.length = rnorm(41), No.spines = rnorm(41),
  Pilosity = factor(sample(0:3, 41, replace = TRUE)))
predfit <- predict(fitt, newX = xnew, newTR = trnew, type = "response")
```

predictLVs.gllvm *Predict latent variables for gllvm Fits*

Description

Obtains predictions for latent variables from a fitted generalized linear latent variable model object. Currently works only for the variational approximation method.

Usage

```
## S3 method for class 'gllvm'
predictLVs(object, newX = NULL, newY = object$y, ...)
```

Arguments

object	an object of class 'gllvm'.
newX	A new data frame of environmental variables. If omitted, the original matrix of environmental variables is used.
newY	A new response data. Defaults to the dataset used for original model fit.
...	not used.

Details

Obtains predictions for latent variables from a fitted generalized linear latent variable model object.

Value

A matrix containing requested predictor types.

Author(s)

David Warton, Jenni Niku <jenni.m.e.niku@jyu.fi>

Examples

```
# Load a dataset from the mvabund package
data(antTraits)
y <- as.matrix(antTraits$abund)
X <- scale(antTraits$env[, 1:3])
# Fit gllvm model
fit <- gllvm(y = y, X, family = poisson())
# fitted values
predLVs <- predictLVs.gllvm(fit)
```

randomCoefplot.gllvm *Plot random slope coefficients*

Description

Plots random slopes and their prediction intervals.

Usage

```
## S3 method for class 'gllvm'
randomCoefplot(
  object,
  y.label = TRUE,
  cex.ylab = 0.5,
  mfrow = NULL,
  mar = c(4, 6, 2, 1),
  xlim.list = NULL,
  order = FALSE,
  ...
)
```

Arguments

object	an object of class 'gllvm'.
y.label	logical, if TRUE (default) colnames of y with respect to coefficients are added to plot.
cex.ylab	the magnification to be used for axis annotation relative to the current setting of cex.
mfrow	same as mfrow in par. If NULL (default) it is determined automatically.
mar	vector of length 4, which defines the margin sizes: c(bottom, left, top, right). Defaults to c(4, 5, 2, 1).
xlim.list	list of vectors with length of two to define the intervals for x axis in each covariate plot. Defaults to NULL when the interval is defined by the range of point estimates and confidence intervals
order	logical, if TRUE (default), coefficients are sorted according to the point estimates
...	additional graphical arguments.

Author(s)

Jenni Niku <jenni.m.e.niku@jyu.fi>, Francis K.C. Hui, Sara Taskinen

Examples

```
## Not run:
## Load a dataset from the mvabund package
data(antTraits)
y <- as.matrix(antTraits$abund)
X <- as.matrix(antTraits$env)
TR <- antTraits$traits
# Fit model with random slopes
fitF <- gllvm(y = y, X = X, TR = TR,
  formula = ~ Bare.ground + Bare.ground : Webers.length,
  family = poisson(), randomX = ~ Bare.ground)
randomCoeplot(fitF)

## End(Not run)
```

residuals.gllvm

*Dunn-Smyth residuals for gllvm model***Description**

Calculates Dunn-Smyth residuals for gllvm model.

Usage

```
## S3 method for class 'gllvm'
residuals(object, ...)
```

Arguments

object	an object of class 'gllvm'.
...	not used.

Details

Computes Dunn-Smyth residuals (randomized quantile residuals, Dunn and Smyth, 1996) for gllvm model. For the observation Y_{ij} Dunn-Smyth residuals are defined as

$$r_{ij} = \Phi^{-1}(u_{ij}F_{ij}(y_{ij}) + (1 - u_{ij})F_{ij}^-(y_{ij})),$$

where $\Phi(\cdot)$ and $F_{ij}(\cdot)$ are the cumulative probability functions of the standard normal distribution, $F_{ij}^-(y)$ is the limit as $F_{ij}(y)$ is approached from the negative side, and u_{ij} has been generated at random from the standard uniform distribution.

Value

residuals	matrix of residuals
linpred	matrix of linear predictors

Author(s)

Jenni Niku <jenni.m.e.niku@jyu.fi>

References

Dunn, P. K., and Smyth, G. K. (1996). Randomized quantile residuals. *Journal of Computational and Graphical Statistics*, 5, 236-244.

Hui, F. K. C., Taskinen, S., Pledger, S., Foster, S. D., and Warton, D. I. (2015). Model-based approaches to unconstrained ordination. *Methods in Ecology and Evolution*, 6:399-411.

Examples

```
## Not run:
# Load a dataset from the mvabund package
data(antTraits)
y <- as.matrix(antTraits$abund)
# Fit gllvm model
fit <- gllvm(y = y, family = poisson())
# residuals
res <- residuals(fit)

## End(Not run)
```

se.gllvm

Standard errors for gllvm model

Description

Calculates Hessian and standard errors for gllvm model.

Usage

```
## S3 method for class 'gllvm'
se(object, ...)
```

Arguments

object	an object of class 'gllvm'.
...	not used.

Details

Computes Hessian and standard errors for gllvm model.

Value

sd	list of standard errors of parameters
Hess	list including Hessian matrix and approximative covariance matrix of parameters

Author(s)

Jenni Niku <jenni.m.e.niku@jyu.fi>

References

- Dunn, P. K., and Smyth, G. K. (1996). Randomized quantile residuals. *Journal of Computational and Graphical Statistics*, 5, 236-244.
- Hui, F. K. C., Taskinen, S., Pledger, S., Foster, S. D., and Warton, D. I. (2015). Model-based approaches to unconstrained ordination. *Methods in Ecology and Evolution*, 6:399-411.

simulate.gllvm	<i>Simulate data from gllvm fit</i>
----------------	-------------------------------------

Description

Generate new data using the fitted values of the parameters

Usage

```
## S3 method for class 'gllvm'
simulate(object, nsim = 1, seed = NULL, conditional = FALSE, ...)
```

Arguments

object	an object of class 'gllvm'.
nsim	an optional positive integer specifying the number of simulated datasets. Defaults to 1.
seed	an optional integer to set seed number, passed to set.seed. Defaults to a random seed number.
conditional	if conditional = FALSE simulates marginally over the latent variables.
...	not used.

Details

simulate function for gllvm objects.

Value

A matrix containing generated data.

Author(s)

David Warton, Jenni Niku <jenni.m.e.niku@jyu.fi>

Examples

```
# Load a dataset from the mvabund package
data(antTraits)
y <- as.matrix(antTraits$abund)
X <- scale(antTraits$env[, 1:3])
# Fit gllvm model
fit <- gllvm(y = y, X, family = poisson())
# Simulate data
newdata <- simulate(fit)
```

sim_bacteria	<i>Simulated bacteria data</i>
--------------	--------------------------------

Description

Simulated dataset of size 56 x 985 that can be used to illustrate the methods in Section 5.1 of Niku et al., (2017).

Usage

```
data(sim_bacteria)
```

Format

y A data frame with abundances of 985 species measured at 56 sites
X Environmental variables soil organic matter, pH and phosphorus and region variables

References

Niku, J., Warton, D. I., Hui, F. K. C., and Taskinen, S. (2017). Generalized Linear Latent Variable Models for Multivariate Count and Biomass Data in Ecology. *Journal of Agricultural, Biological, and Environmental Statistics*, 22, 498-522.

summary.gllvm	<i>Summarizing gllvm model fits</i>
---------------	-------------------------------------

Description

A summary of the fitted 'gllvm' object, including function call, distribution family and model parameters.

Usage

```
## S3 method for class 'gllvm'
summary(object, ...)
```

Arguments

object an object of class 'gllvm'
 ... not used.

Author(s)

Jenni Niku <jenni.m.e.niku@jyu.fi>

Examples

```
## Not run:
## Load a dataset from the mvabund package
data(antTraits)
y <- as.matrix(antTraits$abund)
# Fit gllvm model
fit <- gllvm(y = y, family = poisson())
summary(fit)

## End(Not run)
```

vcov.gllvm

Returns variance-covariance matrix of coefficients in a GLLVM.

Description

Returns the variance-covariance matrix of the parameters from a GLLVM. If the variance-covariance matrix was not calculated after model fitting, this function will have to calculate the variance-covariance matrix, which may be computational intensive for a large number of species and/or sites.

Usage

```
## S3 method for class 'gllvm'
vcov(object)
```

Arguments

object an object of class 'gllvm'.

Details

Calculates the variance-covariance matrix of a GLLVM object using [se.gllvm](#), which may be computational intensive with many parameters. The parameters might have unintuitive names. Fixed-effects coefficients are labeled "b", and are ordered per species as: 1) intercepts 2) fixed-effects slopes. Coefficients of the latent variables are labeled "lambda" (linear coefficients) or "lambda2".

Author(s)

Bert van der Veen

Index

AICc, 2
anova.gllvm, 3

coefplot (coefplot.gllvm), 4
coefplot.gllvm, 4, 18
confint.gllvm, 6, 18

getLV (getLV.gllvm), 7
getLV.gllvm, 7
getPredictErr (getPredictErr.gllvm), 7
getPredictErr.gllvm, 7
getResidualCor (getResidualCor.gllvm), 8
getResidualCor.gllvm, 8
getResidualCov (getResidualCov.gllvm), 9
getResidualCov.gllvm, 8, 9
gllvm, 12, 26
gradient.length (optima), 21

logLik.gllvm, 20

microbialdata, 21

nlminb, 14
nobs (AICc), 2

optim, 14
optima, 21
ordiplot (ordiplot.gllvm), 22
ordiplot.gllvm, 18, 22

p.adjust, 3
plot.gllvm, 18, 24
predict (predict.gllvm), 26
predict.gllvm, 26
predictLVs (predictLVs.gllvm), 28
predictLVs.gllvm, 28

randomCoefplot (randomCoefplot.gllvm),
29
randomCoefplot.gllvm, 29
residuals.gllvm, 18, 26, 30

se (se.gllvm), 31
se.gllvm, 31, 34
sim_bacteria, 33
simulate (simulate.gllvm), 32
simulate.gllvm, 32
summary.gllvm, 18, 33

tolerances (optima), 21

vcov (vcov.gllvm), 34
vcov.gllvm, 34