

Package ‘migrate’

December 7, 2020

Type Package

Title Create Credit State Migration (Transition) Matrices

Version 0.3.0

Description Tools to help convert credit risk data at two time points into traditional credit state migration (aka, “transition”) matrices. At a higher level, ‘migrate’ is intended to help an analyst understand how risk moved in their credit portfolio over a time interval.

References to this methodology include:

1. Schuermann, T. (2008) <doi:10.1002/9780470061596.risk0409>.
2. Perederiy, V. (2017) <arXiv:1708.00062>.

License MIT + file LICENSE

URL <https://github.com/mthomas-ketchbrook/migrate>

BugReports <https://github.com/mthomas-ketchbrook/migrate/issues>

Encoding UTF-8

LazyData true

Suggests testthat (>= 2.1.0), knitr, rmarkdown

Depends R (>= 3.1)

Imports dplyr (>= 1.0.2), tidyr (>= 1.1.0), crayon (>= 1.3.4), stringr (>= 1.4.0), tibble (>= 3.0.1), rlang, utils, magrittr

VignetteBuilder knitr

Language en-US

RoxygenNote 7.1.1

NeedsCompilation no

Author Michael Thomas [aut, cre],
Brad Lindblad [ctb]

Maintainer Michael Thomas <mthomas@ketchbrookanalytics.com>

Repository CRAN

Date/Publication 2020-12-07 17:10:02 UTC

R topics documented:

build_matrix	2
migrate	3
mock_credit	5

Index	6
--------------	----------

build_matrix	<i>Build a migration (transition) matrix</i>
--------------	--

Description

‘build_matrix()’ creates a credit migration (i.e., "transition") matrix from summarized data representing each credit risk state & a continuous metric at two distinct points in time.

Usage

```
build_matrix(data, state_start = NULL, state_end = NULL, metric = NULL)
```

Arguments

data	A data frame or data frame extension (e.g., a tibble or data.table) containing a minimum of three (3) column variables representing a starting credit risk state, an ending credit risk state, and a metric containing values representing the movement (i.e., "transition") in that metric between the starting credit risk state point in time and the ending credit risk state point in time. This style of data frame is output by the ‘migrate()’ function within this package.
state_start	(Optional) A symbol or string, representing the column variable of the ‘data’ data frame argument that contains the starting credit risk state values. If left null, function will attempt to find it for you.
state_end	(Optional) A symbol or string, representing the column variable of the ‘data’ data frame argument that contains the starting credit risk state values. If left null, function will attempt to find it for you.
metric	(Optional) A symbol or string, representing the column variable of the ‘data’ data frame argument that contains the metric for which the grouped difference in value between the starting credit risk state period and ending credit risk state period was computed.

Value

A matrix object, where the first (row) dimension represents the starting credit risk state, the second (column) dimension represents the ending credit risk state, and the values within the matrix represent the transitioned amount based upon the values in the ‘metric’ continuous column variable from the ‘data’ data frame.

Note: A matrix object can be coerced to a data frame using ‘as.data.frame()’.

Examples

```
# Let `build_matrix()` guess which column variables represent `state_start`,
# `state_end` and `metric`
mock_credit %>%
  migrate(
    date = date,
    state = risk_rating,
    id = customer_id,
    metric = principal_balance
  ) %>%
  build_matrix()

# Specify which column variables represent `state_start`, `state_end` and
# `metric`
mock_credit %>%
  migrate(
    date = date,
    state = risk_rating,
    id = customer_id,
    percent = FALSE
  ) %>%
  build_matrix(
    state_start = risk_rating_start,
    state_end = risk_rating_end,
    metric = count
  )
```

migrate

Summarize the migration of a data frame

Description

‘migrate()’ summarizes the transition amount (or percentage) of a continuous variable from each beginning credit risk state category to each ending credit risk state, given a data frame input.

Usage

```
migrate(
  data,
  date,
  state,
  id = NULL,
  metric = NULL,
  percent = TRUE,
  rating = NULL
)
```

Arguments

data	A data frame or data frame extension (e.g., a tibble or data.table) containing a minimum of three (3) column variables representing a date, a credit risk state, and an ID identifying the credit facility (we would expect to see most unique values in this column variable appear twice in the dataset; once at the first date and again at the second date, unless the credit only existed at one of those two dates).
date	A symbol or string, representing the column variable of the 'data' data frame argument that contains the two unique date values.
state	A symbol or string, representing the column variable of the 'data' data frame argument that contains the credit risk state values.
id	(Optional) a symbol or string, representing the column variable of the 'data' data frame argument that contains the unique identifier to track where a particular credit facility migrated to/from. If left null, 'migrate()' will attempt to use the first column variable from the data frame provided in the 'data' argument.
metric	(Optional) a symbol or string, representing the column variable of the 'data' data frame argument that contains the continuous metric values.
percent	If 'FALSE', will calculate the migration on an absolute basis (rather than a percentage basis, which is the default).
rating	Deprecated; please use 'state' instead.

Value

A data frame containing three (3) column variables representing the unique combinations of starting & ending credit risk states and the calculated migration observed during the period.

Examples

```
# Return the percent migration of the number of credit facilities
migrate(
  data = mock_credit,
  date = date,
  state = risk_rating,
  id = customer_id
)

# Return the absolute migration in `principal_balance`
migrate(
  data = mock_credit,
  date = date,
  state = risk_rating,
  id = customer_id,
  metric = principal_balance,
  percent = FALSE
)
```

mock_credit	<i>Mock dataset containing credit statistics by customer at two time intervals. Some customers only exist in one time interval (they either became a customer after the first time interval, or discontinued being a customer before the second time interval).</i>
-------------	---

Description

Mock dataset containing credit statistics by customer at two time intervals. Some customers only exist in one time interval (they either became a customer after the first time interval, or discontinued being a customer before the second time interval).

Usage

```
mock_credit
```

Format

A data frame with columns:

customer_id Customer ID for 497 unique customers.

date Date of the observation; there are two unique dates in the dataset.

risk_rating Factor representing risk level on a 1-14 scale.

principal_balance Principal balance outstanding on the loan.

Source

Developed by Ketchbrook Analytics

Examples

```
## Not run:  
mock_credit  
  
## End(Not run)
```

Index

* **datasets**

mock_credit, 5

build_matrix, 2

migrate, 3

mock_credit, 5