

Package ‘openairmaps’

January 9, 2023

Type Package

Title Create Interactive Web Maps of Air Pollution Data

Version 0.6.1

Description Combine the air quality data analysis methods of 'openair' with the JavaScript 'Leaflet' (<<https://leafletjs.com/>>) library. Functionality includes plotting site maps, ``directional analysis'' figures such as polar plots, and air mass trajectories.

License GPL (>= 3)

Encoding UTF-8

LazyData true

Depends R (>= 3.2.0)

Imports openair (>= 2.13), dplyr, leaflet, purrr, magrittr, rlang, lubridate, tibble, stringr, forcats, tidyr, cli, tidyselect

Suggests worldmet

RoxygenNote 7.2.3

Language en-GB

NeedsCompilation no

Author Jack Davison [cre, aut],
David Carslaw [aut]

Maintainer Jack Davison <davison.jack.jd@gmail.com>

Repository CRAN

Date/Publication 2023-01-09 10:30:06 UTC

R topics documented:

addPolarMarkers	2
addTrajPaths	4
annulusMap	6
buildPopup	10
freqMap	11

networkMap	14
percentileMap	16
polarMap	18
polar_data	24
pollroseMap	25
quickTextHTML	27
trajLevelMap	28
trajMap	30
traj_data	31
windroseMap	32

Index	37
--------------	-----------

addPolarMarkers	<i>Add polar markers to leaflet map</i>
-----------------	---

Description

This function is similar (but not identical to) the `leaflet::addMarkers()` and `leaflet::addCircleMarkers()` functions in `leaflet`, which allows users to add `openair` directional analysis plots to any `leaflet` map and have more control over groups and `layerIds` than in "all-in-one" functions like `polarMap()`.

Usage

```
addPolarMarkers(
  map,
  lng = NULL,
  lat = NULL,
  layerId = NULL,
  group = NULL,
  popup = NULL,
  label = NULL,
  data,
  fun = openair::polarPlot,
  pollutant,
  iconWidth = 200,
  iconHeight = 200,
  fig.width = 3.5,
  fig.height = 3.5,
  ...
)
```

Arguments

<code>map</code>	a map widget object created from <code>leaflet::leaflet()</code> .
<code>lng</code>	The decimal longitude.
<code>lat</code>	The decimal latitude.

layerId	The layer id.
group	the name of the group the newly created layers should belong to (for <code>leaflet::clearGroup()</code> and <code>leaflet::addLayersControl()</code> purposes). Human-friendly group names are permitted—they need not be short, identifier-style names. Any number of layers and even different types of layers (e.g. markers and polygons) can share the same group name.
popup	A column of data to be used as a popup.
label	A column of data to be used as a label.
data	A data frame. The data frame must contain the data to plot your choice of openair directional analysis plot, which includes wind speed (ws), wind direction (wd), and the column representing the concentration of a pollutant. In addition, data must include a decimal latitude and longitude.
fun	An openair directional analysis plotting function. Supported functions include <code>openair::polarPlot()</code> (the default), <code>openair::polarAnnulus()</code> , <code>openair::polarFreq()</code> , <code>openair::percentileRose()</code> , <code>openair::pollutionRose()</code> and <code>openair::windRose()</code> .
pollutant	The name of the pollutant to be plot. Note that, if <code>fun = openair::windRose</code> , you must set <code>pollutant = "ws"</code> .
iconWidth	The actual width of the plot on the map in pixels.
iconHeight	The actual height of the plot on the map in pixels.
fig.width	The width of the plots to be produced in inches.
fig.height	The height of the plots to be produced in inches.
...	Other arguments for the plotting function (e.g. <code>period</code> for <code>openair::polarAnnulus()</code>).

Value

A leaflet object.

Examples

```
## Not run:
library(leaflet)
library(openair)

leaflet() %>%
  addTiles() %>%
  addPolarMarkers(
    data = polar_data,
    lat = "latitude",
    lng = "longitude",
    pollutant = "ws",
    fun = windRose,
    group = "Wind Rose"
  ) %>%
  addPolarMarkers(
    data = polar_data,
    lat = "latitude",
    lng = "longitude",
```

```

    pollutant = "nox",
    group = "Polar Plot"
  ) %>%
  addLayersControl(
    baseGroups = c("Wind Rose", "Polar Plot")
  )

## End(Not run)

```

 addTrajPaths

Add trajectory paths to leaflet map

Description

This function is similar (but not identical to) the `leaflet::addMarkers()` function in `leaflet`, which allows users to add trajectory paths to any leaflet map and have more control over groups and layerIds than in "all-in-one" functions like `trajMap()`.

Usage

```

addTrajPaths(
  map,
  lng = "lon",
  lat = "lat",
  layerId = NULL,
  group = NULL,
  data,
  npoints = 12,
  ...
)

```

Arguments

<code>map</code>	a map widget object created from <code>leaflet::leaflet()</code> .
<code>lng</code>	The decimal longitude.
<code>lat</code>	The decimal latitude.
<code>layerId</code>	The layer id.
<code>group</code>	the name of the group the newly created layers should belong to (for <code>leaflet::clearGroup()</code> and <code>leaflet::addLayersControl()</code> purposes). Human-friendly group names are permitted—they need not be short, identifier-style names. Any number of layers and even different types of layers (e.g. markers and polygons) can share the same group name.
<code>data</code>	Data frame, the result of importing a trajectory file using <code>openair::importTraj()</code> .

`npoints` A dot is placed every `npoints` along each full trajectory. For hourly back trajectories points are plotted every `npoints` hours. This helps to understand where the air masses were at particular times and get a feel for the speed of the air (points closer together correspond to slower moving air masses). Defaults to 12.

`...` Other arguments to pass to both `leaflet::addCircleMarkers()` and `leaflet::addPolylines()`. If you use the `color` argument, it is important to ensure the vector you supply is of length one to avoid issues with `leaflet::addPolylines()` (i.e., use `color = ~ pal(nox)[1]`). Note that `opacity` controls the opacity of the lines and `fillOpacity` the opacity of the markers.

Details

`addTrajPaths()` can be a powerful way of quickly plotting trajectories on a leaflet map, but users should take some care due to any additional arguments being passed to both `leaflet::addCircleMarkers()` and `leaflet::addPolylines()`. In particular, users should be wary of the use of the `color` argument. Specifically, if `color` is passed a vector of length greater than one, multiple polylines will be drawn on top of one another. At best this will affect opacity, but at worst this will significantly impact the performance of R and the final leaflet map.

To mitigate this, please ensure that any vector passed to `color` is of length one. This is simple if you want the whole path to be the same colour, but more difficult if you want to colour by a pollutant, for example. The easiest way to achieve this is to write a for loop or use another iterative approach (e.g. the `purrr` package) to add one path per arrival date. An example of this is provided in the Examples.

Value

A leaflet object.

Examples

```
## Not run:
library(leaflet)
library(openairmaps)

pal <- colorNumeric(palette = "viridis", domain = traj_data$nox)

map <- leaflet() %>%
  addTiles()

for (i in seq(length(unique(traj_data$date)))) {
  data <- dplyr::filter(traj_data, date == unique(traj_data$date)[i])

  map <- map %>%
    addTrajPaths(
      data = data,
      color = pal(data$nox)[1]
    )
}

map
```

```
## End(Not run)
```

annulusMap

Polar annulus plots on interactive leaflet maps

Description

`annulusMap()` creates a leaflet map using polar annulus plots as markers. Any number of pollutants can be specified using the `pollutant` argument, and multiple layers of markers can be added and toggled between using `control`. See `openair::polarAnnulus()` for more information.

Usage

```
annulusMap(
  data,
  pollutant = NULL,
  period = "hour",
  limits = NULL,
  latitude = NULL,
  longitude = NULL,
  control = NULL,
  popup = NULL,
  label = NULL,
  provider = "OpenStreetMap",
  cols = "turbo",
  key = FALSE,
  draw.legend = TRUE,
  collapse.control = FALSE,
  iconWidth = 200,
  iconHeight = 200,
  fig.width = 3.5,
  fig.height = 3.5,
  type = NULL,
  ...
)
```

Arguments

<code>data</code>	A data frame. The data frame must contain the data to plot the directional analysis marker, which includes wind speed (<code>ws</code>), wind direction (<code>wd</code>), and the column representing the concentration of a pollutant. In addition, <code>data</code> must include a decimal latitude and longitude.
<code>pollutant</code>	The column name(s) of the pollutant(s) to plot. If multiple pollutants are specified, they can be toggled between using a "layer control" interface.

period	This determines the temporal period to consider. Options are "hour" (the default, to plot diurnal variations), "season" to plot variation throughout the year, "weekday" to plot day of the week variation and "trend" to plot the trend by wind direction.
limits	By default, each individual polar marker has its own colour scale. The <code>limits</code> argument will force all markers to use the same colour scale. The limits are set in the form <code>c(lower, upper)</code> , so <code>limits = c(0, 100)</code> would force the plot limits to span 0-100.
latitude, longitude	The decimal latitude/longitude. If not provided, will be automatically inferred from data by looking for a column named "lat"/"latitude" or "lon"/"lng"/"long"/"longitude" (case-insensitively).
control	Column to be used for splitting the input data into different groups which can be selected between using a "layer control" interface. Appropriate columns could be those added by <code>openair::cutData()</code> or <code>openair::splitByDate()</code> . <code>control</code> cannot be used if multiple pollutant columns have been provided.
popup	Column to be used as the HTML content for marker popups. Popups may be useful to show information about the individual sites (e.g., site names, codes, types, etc.).
label	Column to be used as the HTML content for hover-over labels. Labels are useful for the same reasons as popups, though are typically shorter.
provider	The base map(s) to be used. See http://leaflet-extras.github.io/leaflet-providers/preview/ for a list of all base maps that can be used. If multiple base maps are provided, they can be toggled between using a "layer control" interface.
cols	The colours used for plotting.
key	Should a key for each marker be drawn? Default is FALSE.
draw.legend	When <code>limits</code> are specified, should a shared legend be created at the side of the map? Default is TRUE.
collapse.control	Should the "layer control" interface be collapsed? Defaults to FALSE.
iconWidth	The actual width of the plot on the map in pixels.
iconHeight	The actual height of the plot on the map in pixels.
fig.width	The width of the plots to be produced in inches.
fig.height	The height of the plots to be produced in inches.
type	Deprecated. Please use <code>label</code> and/or <code>popup</code> to label different sites.
...	Arguments passed on to <code>openair::polarAnnulus</code>
resolution	Two plot resolutions can be set: "normal" and "fine" (the default).
local.tz	Should the results be calculated in local time that includes a treatment of daylight savings time (DST)? The default is not to consider DST issues, provided the data were imported without a DST offset. Emissions activity tends to occur at local time e.g. rush hour is at 8 am every day. When the clocks go forward in spring, the emissions are effectively released into the atmosphere typically 1 hour earlier during the summertime

i.e. when DST applies. When plotting diurnal profiles, this has the effect of “smearing-out” the concentrations. Sometimes, a useful approach is to express time as local time. This correction tends to produce better-defined diurnal profiles of concentration (or other variables) and allows a better comparison to be made with emissions/activity data. If set to FALSE then GMT is used. Examples of usage include `local.tz = "Europe/London"`, `local.tz = "America/New_York"`. See `cutData` and `import` for more details.

- statistic** The statistic that should be applied to each wind speed/direction bin. Can be “mean” (default), “median”, “max” (maximum), “frequency”, “stdev” (standard deviation), “weighted.mean” or “cpf” (Conditional Probability Function). Because of the smoothing involved, the colour scale for some of these statistics is only to provide an indication of overall pattern and should not be interpreted in concentration units e.g. for `statistic = "weighted.mean"` where the bin mean is multiplied by the bin frequency and divided by the total frequency. In many cases using `polarFreq` will be better. Setting `statistic = "weighted.mean"` can be useful because it provides an indication of the concentration * frequency of occurrence and will highlight the wind speed/direction conditions that dominate the overall mean.
- percentile** If `statistic = "percentile"` or `statistic = "cpf"` then `percentile` is used, expressed from 0 to 100. Note that the percentile value is calculated in the wind speed, wind direction ‘bins’. For this reason it can also be useful to set `min.bin` to ensure there are a sufficient number of points available to estimate a percentile. See `quantile` for more details of how percentiles are calculated.
- width** The width of the annulus; can be “normal” (the default), “thin” or “fat”.
- min.bin** The minimum number of points allowed in a wind speed/wind direction bin. The default is 1. A value of two requires at least 2 valid records in each bin and so on; bins with less than 2 valid records are set to NA. Care should be taken when using a value > 1 because of the risk of removing real data points. It is recommended to consider your data with care. Also, the `polarFreq` function can be of use in such circumstances.
- exclude.missing** Setting this option to TRUE (the default) removes points from the plot that are too far from the original data. The smoothing routines will produce predictions at points where no data exist i.e. they predict. By removing the points too far from the original data produces a plot where it is clear where the original data lie. If set to FALSE missing data will be interpolated.
- date.pad** For `type = "trend"` (default), `date.pad = TRUE` will pad-out missing data to the beginning of the first year and the end of the last year. The purpose is to ensure that the trend plot begins and ends at the beginning or end of year.
- force.positive** The default is TRUE. Sometimes if smoothing data with steep gradients it is possible for predicted values to be negative. `force.positive = TRUE` ensures that predictions remain positive. This is useful for several reasons. First, with lots of missing data more interpolation is needed and this can result in artefacts because the predictions are too far from the origi-

nal data. Second, if it is known beforehand that the data are all positive, then this option carries that assumption through to the prediction. The only likely time where setting `force.positive = FALSE` would be if background concentrations were first subtracted resulting in data that is legitimately negative. For the vast majority of situations it is expected that the user will not need to alter the default option.

`k` The smoothing value supplied to `gam` for the temporal and wind direction components, respectively. In some cases e.g. a trend plot with less than 1-year of data the smoothing with the default values may become too noisy and affected more by outliers. Choosing a lower value of `k` (say 10) may help produce a better plot.

`normalise` If TRUE concentrations are normalised by dividing by their mean value. This is done *after* fitting the smooth surface. This option is particularly useful if one is interested in the patterns of concentrations for several pollutants on different scales e.g. NO_x and CO. Often useful if more than one pollutant is chosen.

`key.header` Adds additional text/labels to the scale key. For example, passing the options `key.header = "header"`, `key.footer = "footer1"` adds additional text above and below the scale key. These arguments are passed to `drawOpenKey` via `quickText`, applying the `auto.text` argument, to handle formatting.

`key.footer` see `key.footer`.

`key.position` Location where the scale key is to plotted. Allowed arguments currently include "top", "right", "bottom" and "left".

`auto.text` Either TRUE (default) or FALSE. If TRUE titles and axis labels will automatically try and format pollutant names and units properly e.g. by subscripting the '2' in NO₂.

Value

A leaflet object.

See Also

Other directional analysis maps: [freqMap\(\)](#), [percentileMap\(\)](#), [polarMap\(\)](#), [pollroseMap\(\)](#), [windroseMap\(\)](#)

Examples

```
## Not run:
annulusMap(polar_data,
  pollutant = "nox",
  period = "hour",
  provider = "Stamen.Toner"
)

## End(Not run)
```

buildPopup

*Build a Complex Popup for a Leaflet Map***Description**

Group a dataframe together by latitude/longitude columns and create a HTML popup with user-defined columns. By default, the unique values of character columns are collapsed into comma-separated lists, numeric columns are averaged, and date columns are presented as a range. This function returns the input dataframe appended with a "popup" column, which can then be used in the popup argument of a function like `polarMap()`.

Usage

```
buildPopup(
  data,
  cols,
  latitude = NULL,
  longitude = NULL,
  names = NULL,
  control = NULL,
  fun.character = function(x) paste(unique(x), collapse = ", "),
  fun.numeric = function(x) signif(mean(x, na.rm = TRUE), 3),
  fun.dttm = function(x) paste(lubridate::floor_date(range(x, na.rm = TRUE), "day"),
    collapse = " to ")
)
```

Arguments

<code>data</code>	A data frame containing latitude and longitude information that will go on to be used in a function such as <code>polarMap()</code> .
<code>cols</code>	A character vector of column names, the data from which will appear in the popup.
<code>latitude, longitude</code>	The decimal latitude/longitude. If not provided, will be automatically inferred from data by looking for a column named "lat"/"latitude" or "lon"/"lng"/"long"/"longitude". (case-insensitively).
<code>names</code>	Optional. A named vector used to rename certain columns in the popups. See the Example for more information.
<code>control</code>	Optional. Column which will be used for the <code>control</code> argument of other mapping functions. This only needs to be used if <code>control</code> is going to be used in <code>polarMap()</code> or another similar function, and you'd expect different values for the different map layers (for example, if you are calculating a mean pollutant concentration).
<code>fun.character</code>	A function to summarise character and factor columns. Defaults to collapsing unique values into a comma-separated list.

`fun.numeric` A function to summarise numeric columns. Defaults to taking the mean to three significant figures.

`fun.dttm` A function to summarise date columns. Defaults to presenting the date as a range.

Value

a `tibble::tibble()`

Examples

```
## Not run:
buildPopup(
  data = openairmaps::polar_data,
  cols = c("site", "site_type", "date", "nox"),
  names = c("Site" = "site", "Site Type" = "site_type", "Date Range" = "date")
) %>%
  polarMap("nox", popup = "popup")

## End(Not run)
```

freqMap

Polar frequency plots on interactive leaflet maps

Description

`freqMap()` creates a leaflet map using binned polar plots as markers. Any number of pollutants can be specified using the `pollutant` argument, and multiple layers of markers can be added and toggled between using `control`. See `openair::polarFreq()` for more information.

Usage

```
freqMap(
  data,
  pollutant = NULL,
  breaks = NULL,
  statistic = "mean",
  latitude = NULL,
  longitude = NULL,
  control = NULL,
  popup = NULL,
  label = NULL,
  provider = "OpenStreetMap",
  cols = "turbo",
  key = FALSE,
  draw.legend = TRUE,
  collapse.control = FALSE,
  iconWidth = 200,
```

```

    iconHeight = 200,
    fig.width = 3.5,
    fig.height = 3.5,
    type = NULL,
    ...
  )

```

Arguments

data	A data frame. The data frame must contain the data to plot the directional analysis marker, which includes wind speed (ws), wind direction (wd), and the column representing the concentration of a pollutant. In addition, data must include a decimal latitude and longitude.
pollutant	The column name(s) of the pollutant(s) to plot. If multiple pollutants are specified, they can be toggled between using a "layer control" interface.
breaks	The user can provide their own scale. breaks expects a sequence of numbers that define the range of the scale. The sequence could represent one with equal spacing, e.g., breaks = seq(0, 100, 10) - a scale from 0-10 in intervals of 10, or a more flexible sequence, e.g., breaks = c(0, 1, 5, 7, 10), which may be useful for some situations.
statistic	The statistic that should be applied to each wind speed/direction bin. Can be "frequency", "mean", "median", "max" (maximum), "stdev" (standard deviation) or "weighted.mean". The option "frequency" is the simplest and plots the frequency of wind speed/direction in different bins. The scale therefore shows the counts in each bin. The option "mean" (the default) will plot the mean concentration of a pollutant (see next point) in wind speed/direction bins, and so on. Finally, "weighted.mean" will plot the concentration of a pollutant weighted by wind speed/direction. Each segment therefore provides the percentage overall contribution to the total concentration. Note that for options other than "frequency", it is necessary to also provide the name of a pollutant. See function openair::cutData() for further details.
latitude, longitude	The decimal latitude/longitude. If not provided, will be automatically inferred from data by looking for a column named "lat"/"latitude" or "lon"/"lng"/"long"/"longitude" (case-insensitively).
control	Column to be used for splitting the input data into different groups which can be selected between using a "layer control" interface. Appropriate columns could be those added by openair::cutData() or openair::splitByDate() . control cannot be used if multiple pollutant columns have been provided.
popup	Column to be used as the HTML content for marker popups. Popups may be useful to show information about the individual sites (e.g., site names, codes, types, etc.).
label	Column to be used as the HTML content for hover-over labels. Labels are useful for the same reasons as popups, though are typically shorter.
provider	The base map(s) to be used. See http://leaflet-extras.github.io/leaflet-providers/preview/ for a list of all base maps that can be used. If multiple base maps are provided, they can be toggled between using a "layer control" interface.

<code>cols</code>	The colours used for plotting.
<code>key</code>	Should a key for each marker be drawn? Default is FALSE.
<code>draw.legend</code>	When breaks are specified, should a shared legend be created at the side of the map? Default is TRUE.
<code>collapse.control</code>	Should the "layer control" interface be collapsed? Defaults to FALSE.
<code>iconWidth</code>	The actual width of the plot on the map in pixels.
<code>iconHeight</code>	The actual height of the plot on the map in pixels.
<code>fig.width</code>	The width of the plots to be produced in inches.
<code>fig.height</code>	The height of the plots to be produced in inches.
<code>type</code>	Deprecated. Please use <code>label</code> and/or <code>popup</code> to label different sites.
<code>...</code>	Arguments passed on to <code>openair::polarFreq</code>
<code>ws.int</code>	Wind speed interval assumed. In some cases e.g. a low met mast, an interval of 0.5 may be more appropriate.
<code>wd.nint</code>	Number of intervals of wind direction.
<code>grid.line</code>	Radial spacing of grid lines.
<code>trans</code>	Should a transformation be applied? Sometimes when producing plots of this kind they can be dominated by a few high points. The default therefore is TRUE and a square-root transform is applied. This results in a non-linear scale and (usually) a better representation of the distribution. If set to FALSE a linear scale is used.
<code>min.bin</code>	The minimum number of points allowed in a wind speed/wind direction bin. The default is 1. A value of two requires at least 2 valid records in each bin and so on; bins with less than 2 valid records are set to NA. Care should be taken when using a value > 1 because of the risk of removing real data points. It is recommended to consider your data with care. Also, the <code>polarFreq</code> function can be of use in such circumstances.
<code>ws.upper</code>	A user-defined upper wind speed to use. This is useful for ensuring a consistent scale between different plots. For example, to always ensure that wind speeds are displayed between 1-10, set <code>ws.int = 10</code> .
<code>offset</code>	<code>offset</code> controls the size of the 'hole' in the middle and is expressed as a percentage of the maximum wind speed. Setting a higher <code>offset</code> e.g. 50 is useful for <code>statistic = "weighted.mean"</code> when <code>ws.int</code> is greater than the maximum wind speed. See example below.
<code>border.col</code>	The colour of the boundary of each wind speed/direction bin. The default is transparent. Another useful choice sometimes is "white".
<code>key.header</code>	Adds additional text/labels to the scale key. For example, passing the options <code>key.header = "header"</code> , <code>key.footer = "footer1"</code> adds additional text above and below the scale key. These arguments are passed to <code>drawOpenKey</code> via <code>quickText</code> , applying the <code>auto.text</code> argument, to handle formatting.
<code>key.footer</code>	see <code>key.footer</code> .
<code>key.position</code>	Location where the scale key is to be plotted. Allowed arguments currently include "top", "right", "bottom" and "left".

`auto.text` Either TRUE (default) or FALSE. If TRUE titles and axis labels will automatically try and format pollutant names and units properly e.g. by subscripting the '2' in NO2.

Value

A leaflet object.

See Also

Other directional analysis maps: [annulusMap\(\)](#), [percentileMap\(\)](#), [polarMap\(\)](#), [pollroseMap\(\)](#), [windroseMap\(\)](#)

Examples

```
## Not run:
freqMap(polar_data,
  pollutant = "nox",
  statistic = "mean",
  provider = "Stamen.Toner"
)

## End(Not run)
```

networkMap

Create a leaflet map of air quality measurement network sites

Description

This function uses [openair::importMeta\(\)](#) to obtain metadata for measurement sites and uses it to create an attractive leaflet map. By default a map will be created in which readers may toggle between a vector base map and a satellite/aerial image, although users can further customise the control menu using the `provider` and `control` parameters.

Usage

```
networkMap(
  source = "aurn",
  control = NULL,
  date = Sys.Date(),
  cluster = TRUE,
  provider = c("OpenStreetMap", "Esri.WorldImagery"),
  collapse.control = FALSE
)
```

Arguments

source	One or more sources of meta data. Can be aurn, saqn (or saqd), aqe, waqn, ni, local (or lmam), kcl or europe; upper or lower case. See the "details" section for further information about selecting multiple sites.
control	Option to add a "layer control" menu to allow readers to select between different site types. Can choose between effectively any column in the <code>openair::importMeta()</code> output, such as "variable", "site_type", or "agglomeration", as well as "network" when more than one source was specified.
date	By default, <code>networkMap()</code> visualises sites and pollutants which are currently operational. Specifying date will visualise sites which were operational at the chosen date. Dates should be provided in the "YYYY-MM-DD" format. Alternatively, a single year can be provided ("YYYY") and <code>networkMap()</code> will visualise sites which were operational at the <i>end</i> of that year (December 31st).
cluster	When <code>cluster = TRUE</code> , markers are clustered together. This may be useful for sources like "kcl" where there are many markers very close together. Defaults to TRUE, and is forced to be TRUE when <code>source = "europe"</code> due to the large number of sites.
provider	The base map(s) to be used. See http://leaflet-extras.github.io/leaflet-providers/preview/ for a list of all base maps that can be used. If multiple base maps are provided, they can be toggled between using a "layer control" interface.
collapse.control	Should the "layer control" interface be collapsed? Defaults to FALSE.

Details

When selecting multiple data sources using `source`, please be mindful that there can be overlap between the different networks. For example, an air quality site in Scotland may be part of the AURN *and* the SAQN. `networkMap()` will only show one marker for such sites, and uses the order in which `source` arguments are provided as the hierarchy by which to assign sites to networks. The aforementioned AURN & SAQN site will therefore have its SAQN code displayed if `source = c("saqn", "aurn")`, and its AURN code displayed if `source = c("aurn", "saqn")`.

This hierarchy is also reflected when `control = "network"` is used. As leaflet markers cannot be part of multiple groups, the AURN & SAQN site will be part of the "SAQN" layer control group when `source = c("saqn", "aurn")` and the "AURN" layer control group when `source = c("aurn", "saqn")`.

Value

A leaflet object.

Examples

```
## Not run:
# view one network, grouped by site type
networkMap(source = "aurn", control = "site_type")

# view multiple networks, grouped by network
```

```
networkMap(source = c("aurn", "waqn", "saqn"), control = "network")

## End(Not run)
```

percentileMap

Percentile roses on interactive leaflet maps

Description

`percentileMap()` creates a leaflet map using percentile roses as markers. Any number of pollutants can be specified using the `pollutant` argument, and multiple layers of markers can be added and toggled between using `control`. See `openair::percentileRose()` for more information.

Usage

```
percentileMap(
  data,
  pollutant = NULL,
  percentile = c(25, 50, 75, 90, 95),
  latitude = NULL,
  longitude = NULL,
  control = NULL,
  popup = NULL,
  label = NULL,
  provider = "OpenStreetMap",
  cols = "turbo",
  key = FALSE,
  draw.legend = TRUE,
  collapse.control = FALSE,
  iconWidth = 200,
  iconHeight = 200,
  fig.width = 3.5,
  fig.height = 3.5,
  type = NULL,
  ...
)
```

Arguments

<code>data</code>	A data frame. The data frame must contain the data to plot the directional analysis marker, which includes wind speed (<code>ws</code>), wind direction (<code>wd</code>), and the column representing the concentration of a pollutant. In addition, <code>data</code> must include a decimal latitude and longitude.
<code>pollutant</code>	The column name(s) of the pollutant(s) to plot. If multiple pollutants are specified, they can be toggled between using a "layer control" interface.

percentile	The percentile value(s) to plot. Must be between 0–100. If percentile = NA then only a mean line will be shown.
latitude, longitude	The decimal latitude/longitude. If not provided, will be automatically inferred from data by looking for a column named "lat"/"latitude" or "lon"/"lng"/"long"/"longitude" (case-insensitively).
control	Column to be used for splitting the input data into different groups which can be selected between using a "layer control" interface. Appropriate columns could be those added by <code>openair::cutData()</code> or <code>openair::splitByDate()</code> . <code>control</code> cannot be used if multiple pollutant columns have been provided.
popup	Column to be used as the HTML content for marker popups. Popups may be useful to show information about the individual sites (e.g., site names, codes, types, etc.).
label	Column to be used as the HTML content for hover-over labels. Labels are useful for the same reasons as popups, though are typically shorter.
provider	The base map(s) to be used. See http://leaflet-extras.github.io/leaflet-providers/preview/ for a list of all base maps that can be used. If multiple base maps are provided, they can be toggled between using a "layer control" interface.
cols	The colours used for plotting.
key	Should a key for each marker be drawn? Default is FALSE.
draw.legend	Should a shared legend be created at the side of the map? Default is TRUE.
collapse.control	Should the "layer control" interface be collapsed? Defaults to FALSE.
iconWidth	The actual width of the plot on the map in pixels.
iconHeight	The actual height of the plot on the map in pixels.
fig.width	The width of the plots to be produced in inches.
fig.height	The height of the plots to be produced in inches.
type	Deprecated. Please use <code>label</code> and/or <code>popup</code> to label different sites.
...	Arguments passed on to <code>openair::percentileRose</code>
wd	Name of wind direction field.
smooth	Should the wind direction data be smoothed using a cyclic spline?
method	When <code>method = "default"</code> the supplied percentiles by wind direction are calculated. When <code>method = "cpf"</code> the conditional probability function (CPF) is plotted and a single (usually high) percentile level is supplied. The CPF is defined as $CPF = m_y/n_y$, where m_y is the number of samples in the wind sector y with mixing ratios greater than the <i>overall</i> percentile concentration, and n_y is the total number of samples in the same wind sector (see Ashbaugh et al., 1985).
angle	Default angle of "spokes" is when <code>smooth = FALSE</code> .
mean	Show the mean by wind direction as a line?
mean.lty	Line type for mean line.
mean.lwd	Line width for mean line.
mean.col	Line colour for mean line.

- `fill` Should the percentile intervals be filled (default) or should lines be drawn (`fill = FALSE`).
- `intervals` User-supplied intervals for the scale e.g. `intervals = c(0, 10, 30, 50)`
- `angle.scale` Sometimes the placement of the scale may interfere with an interesting feature. The user can therefore set `angle.scale` to any value between 0 and 360 degrees to mitigate such problems. For example `angle.scale = 45` will draw the scale heading in a NE direction.
- `auto.text` Either TRUE (default) or FALSE. If TRUE titles and axis labels will automatically try and format pollutant names and units properly e.g. by subscripting the '2' in NO₂.
- `key.header` Adds additional text/labels to the scale key. For example, passing the options `key.header = "header"`, `key.footer = "footer1"` adds additional text above and below the scale key. These arguments are passed to `drawOpenKey` via `quickText`, applying the `auto.text` argument, to handle formatting.
- `key.footer` see `key.footer`.
- `key.position` Location where the scale key is to plotted. Allowed arguments currently include "top", "right", "bottom" and "left".

Value

A leaflet object.

See Also

Other directional analysis maps: [annulusMap\(\)](#), [freqMap\(\)](#), [polarMap\(\)](#), [pollroseMap\(\)](#), [windroseMap\(\)](#)

Examples

```
## Not run:
percentileMap(polar_data,
  pollutant = "nox",
  provider = "Stamen.Toner"
)

## End(Not run)
```

polarMap

Bivariate polar plots on interactive leaflet maps

Description

[polarMap\(\)](#) creates a leaflet map using bivariate polar plots as markers. Any number of pollutants can be specified using the `pollutant` argument, and multiple layers of markers can be added and toggled between using `control`. See [openair::polarPlot\(\)](#) for more information.

Usage

```

polarMap(
  data,
  pollutant = NULL,
  x = "ws",
  limits = NULL,
  latitude = NULL,
  longitude = NULL,
  control = NULL,
  popup = NULL,
  label = NULL,
  provider = "OpenStreetMap",
  cols = "turbo",
  alpha = 1,
  key = FALSE,
  draw.legend = TRUE,
  collapse.control = FALSE,
  iconWidth = 200,
  iconHeight = 200,
  fig.width = 3.5,
  fig.height = 3.5,
  type = NULL,
  ...
)

```

Arguments

<code>data</code>	A data frame. The data frame must contain the data to plot the directional analysis marker, which includes wind speed (<code>ws</code>), wind direction (<code>wd</code>), and the column representing the concentration of a pollutant. In addition, <code>data</code> must include a decimal latitude and longitude.
<code>pollutant</code>	The column name(s) of the pollutant(s) to plot. If multiple pollutants are specified, they can be toggled between using a "layer control" interface.
<code>x</code>	The radial axis variable to plot.
<code>limits</code>	By default, each individual polar marker has its own colour scale. The <code>limits</code> argument will force all markers to use the same colour scale. The limits are set in the form <code>c(lower, upper)</code> , so <code>limits = c(0, 100)</code> would force the plot limits to span 0-100.
<code>latitude, longitude</code>	The decimal latitude/longitude. If not provided, will be automatically inferred from data by looking for a column named "lat"/"latitude" or "lon"/"lng"/"long"/"longitude" (case-insensitively).
<code>control</code>	Column to be used for splitting the input data into different groups which can be selected between using a "layer control" interface. Appropriate columns could be those added by <code>openair::cutData()</code> or <code>openair::splitByDate()</code> . <code>control</code> cannot be used if multiple pollutant columns have been provided.

popup	Column to be used as the HTML content for marker popups. Popups may be useful to show information about the individual sites (e.g., site names, codes, types, etc.).
label	Column to be used as the HTML content for hover-over labels. Labels are useful for the same reasons as popups, though are typically shorter.
provider	The base map(s) to be used. See http://leaflet-extras.github.io/leaflet-providers/preview/ for a list of all base maps that can be used. If multiple base maps are provided, they can be toggled between using a "layer control" interface.
cols	The colours used for plotting.
alpha	The alpha transparency to use for the plotting surface (a value between 0 and 1 with zero being fully transparent and 1 fully opaque).
key	Should a key for each marker be drawn? Default is FALSE.
draw.legend	When limits are specified, should a shared legend be created at the side of the map? Default is TRUE.
collapse.control	Should the "layer control" interface be collapsed? Defaults to FALSE.
iconWidth	The actual width of the plot on the map in pixels.
iconHeight	The actual height of the plot on the map in pixels.
fig.width	The width of the plots to be produced in inches.
fig.height	The height of the plots to be produced in inches.
type	Deprecated. Please use label and/or popup to label different sites.
...	Arguments passed on to <code>openair::polarPlot</code>
wd	Name of wind direction field.
statistic	The statistic that should be applied to each wind speed/direction bin. Because of the smoothing involved, the colour scale for some of these statistics is only to provide an indication of overall pattern and should not be interpreted in concentration units e.g. for <code>statistic = "weighted.mean"</code> where the bin mean is multiplied by the bin frequency and divided by the total frequency. In many cases using <code>polarFreq</code> will be better. Setting <code>statistic = "weighted.mean"</code> can be useful because it provides an indication of the concentration * frequency of occurrence and will highlight the wind speed/direction conditions that dominate the overall mean. Can be: <ul style="list-style-type: none"> • "mean" (default), "median", "max" (maximum), "frequency". "stdev" (standard deviation), "weighted.mean". • <code>statistic = "nwr"</code> Implements the Non-parametric Wind Regression approach of Henry et al. (2009) that uses kernel smoothers. The <code>openair</code> implementation is not identical because Gaussian kernels are used for both wind direction and speed. The smoothing is controlled by <code>ws_spread</code> and <code>wd_spread</code>. • <code>statistic = "cpf"</code> the conditional probability function (CPF) is plotted and a single (usually high) percentile level is supplied. The CPF is defined as $CPF = m_y/n_y$, where m_y is the number of samples in the y bin (by default a wind direction, wind speed interval) with mixing ratios greater than the <i>overall</i> percentile concentration, and n_y is the total

number of samples in the same wind sector (see Ashbaugh et al., 1985). Note that percentile intervals can also be considered; see `percentile` for details.

- When `statistic = "r"` or `statistic = "Pearson"`, the Pearson correlation coefficient is calculated for *two* pollutants. The calculation involves a weighted Pearson correlation coefficient, which is weighted by Gaussian kernels for wind direction and the radial variable (by default wind speed). More weight is assigned to values close to a wind speed-direction interval. Kernel weighting is used to ensure that all data are used rather than relying on the potentially small number of values in a wind speed-direction interval.
- When `statistic = "Spearman"`, the Spearman correlation coefficient is calculated for *two* pollutants. The calculation involves a weighted Spearman correlation coefficient, which is weighted by Gaussian kernels for wind direction and the radial variable (by default wind speed). More weight is assigned to values close to a wind speed-direction interval. Kernel weighting is used to ensure that all data are used rather than relying on the potentially small number of values in a wind speed-direction interval.
- `"robust_slope"` is another option for pair-wise statistics and `"quantile.slope"`, which uses quantile regression to estimate the slope for a particular quantile level (see also `tau` for setting the quantile level).
- `"york_slope"` is another option for pair-wise statistics which uses the *York regression method* to estimate the slope. In this method the uncertainties in *x* and *y* are used in the determination of the slope. The uncertainties are provided by `x_error` and `y_error` — see below.

`exclude.missing` Setting this option to TRUE (the default) removes points from the plot that are too far from the original data. The smoothing routines will produce predictions at points where no data exist i.e. they predict. By removing the points too far from the original data produces a plot where it is clear where the original data lie. If set to FALSE missing data will be interpolated.

`uncertainty` Should the uncertainty in the calculated surface be shown? If TRUE three plots are produced on the same scale showing the predicted surface together with the estimated lower and upper uncertainties at the 95% confidence interval. Calculating the uncertainties is useful to understand whether features are real or not. For example, at high wind speeds where there are few data there is greater uncertainty over the predicted values. The uncertainties are calculated using the GAM and weighting is done by the frequency of measurements in each wind speed-direction bin. Note that if uncertainties are calculated then the type is set to "default".

`percentile` If `statistic = "percentile"` then `percentile` is used, expressed from 0 to 100. Note that the percentile value is calculated in the wind speed, wind direction 'bins'. For this reason it can also be useful to set `min.bin` to ensure there are a sufficient number of points available to estimate a percentile. See `quantile` for more details of how percentiles are calculated. `percentile` is also used for the Conditional Probability Function (CPF) plots. `percentile` can be of length two, in which case the percentile *in-*

terval is considered for use with CPF. For example, `percentile = c(90, 100)` will plot the CPF for concentrations between the 90 and 100th percentiles. Percentile intervals can be useful for identifying specific sources. In addition, `percentile` can also be of length 3. The third value is the 'trim' value to be applied. When calculating percentile intervals many can cover very low values where there is no useful information. The trim value ensures that values greater than or equal to the `trim * mean` value are considered *before* the percentile intervals are calculated. The effect is to extract more detail from many source signatures. See the manual for examples. Finally, if the trim value is less than zero the percentile range is interpreted as absolute concentration values and subsetting is carried out directly.

`weights` At the edges of the plot there may only be a few data points in each wind speed-direction interval, which could in some situations distort the plot if the concentrations are high. `weights` applies a weighting to reduce their influence. For example and by default if only a single data point exists then the weighting factor is 0.25 and for two points 0.5. To not apply any weighting and use the data as is, use `weights = c(1, 1, 1)`.

An alternative to down-weighting these points they can be removed altogether using `min.bin`.

`min.bin` The minimum number of points allowed in a wind speed/wind direction bin. The default is 1. A value of two requires at least 2 valid records in each bin and so on; bins with less than 2 valid records are set to NA. Care should be taken when using a value > 1 because of the risk of removing real data points. It is recommended to consider your data with care. Also, the `polarFreq` function can be of use in such circumstances.

`mis.col` When `min.bin` is > 1 it can be useful to show where data are removed on the plots. This is done by shading the missing data in `mis.col`. To not highlight missing data when `min.bin` > 1 choose `mis.col = "transparent"`.

`upper` This sets the upper limit wind speed to be used. Often there are only a relatively few data points at very high wind speeds and plotting all of them can reduce the useful information in the plot.

`angle.scale` Sometimes the placement of the scale may interfere with an interesting feature. The user can therefore set `angle.scale` to any value between 0 and 360 degrees to mitigate such problems. For example `angle.scale = 45` will draw the scale heading in a NE direction.

`units` The units shown on the polar axis scale.

`force.positive` The default is TRUE. Sometimes if smoothing data with steep gradients it is possible for predicted values to be negative. `force.positive = TRUE` ensures that predictions remain positive. This is useful for several reasons. First, with lots of missing data more interpolation is needed and this can result in artefacts because the predictions are too far from the original data. Second, if it is known beforehand that the data are all positive, then this option carries that assumption through to the prediction. The only likely time where setting `force.positive = FALSE` would be if background concentrations were first subtracted resulting in data that is legitimately negative. For the vast majority of situations it is expected that the user will not need to alter the default option.

- k** This is the smoothing parameter used by the `gam` function in package `mgcv`. Typically, value of around 100 (the default) seems to be suitable and will resolve important features in the plot. The most appropriate choice of `k` is problem-dependent; but extensive testing of polar plots for many different problems suggests a value of `k` of about 100 is suitable. Setting `k` to higher values will not tend to affect the surface predictions by much but will add to the computation time. Lower values of `k` will increase smoothing. Sometimes with few data to plot `polarPlot` will fail. Under these circumstances it can be worth lowering the value of `k`.
- normalise** If TRUE concentrations are normalised by dividing by their mean value. This is done *after* fitting the smooth surface. This option is particularly useful if one is interested in the patterns of concentrations for several pollutants on different scales e.g. NO_x and CO. Often useful if more than one pollutant is chosen.
- key.header** Adds additional text/labels to the scale key. For example, passing the options `key.header = "header"`, `key.footer = "footer1"` adds addition text above and below the scale key. These arguments are passed to `drawOpenKey` via `quickText`, applying the `auto.text` argument, to handle formatting.
- key.footer** see `key.footer`.
- key.position** Location where the scale key is to plotted. Allowed arguments currently include "top", "right", "bottom" and "left".
- auto.text** Either TRUE (default) or FALSE. If TRUE titles and axis labels will automatically try and format pollutant names and units properly e.g. by subscripting the '2' in NO₂.
- ws_spread** The value of sigma used for Gaussian kernel weighting of wind speed when `statistic = "nwr"` or when correlation and regression statistics are used such as *r*. Default is 0.5.
- wd_spread** The value of sigma used for Gaussian kernel weighting of wind direction when `statistic = "nwr"` or when correlation and regression statistics are used such as *r*. Default is 4.
- x_error** The x error / uncertainty used when `statistic = "york_slope"`.
- y_error** The y error / uncertainty used when `statistic = "york_slope"`.
- kernel** Type of kernel used for the weighting procedure for when correlation or regression techniques are used. Only "gaussian" is supported but this may be enhanced in the future.
- tau** The quantile to be estimated when `statistic` is set to "quantile.slope". Default is 0.5 which is equal to the median and will be ignored if "quantile.slope" is not used.

Value

A leaflet object.

See Also

Other directional analysis maps: [annulusMap\(\)](#), [freqMap\(\)](#), [percentileMap\(\)](#), [pollroseMap\(\)](#), [windroseMap\(\)](#)

Examples

```
## Not run:
polarMap(polar_data,
  pollutant = "nox",
  x = "ws",
  provider = "Stamen.Toner"
)

## End(Not run)
```

polar_data

Example data for polar mapping functions

Description

The polar_data dataset is provided as an example dataset as part of the openairmaps package. The dataset contains hourly measurements of air pollutant concentrations, location and meteorological data.

Format

Data frame with example data from four sites in London in 2009.

date The date and time of the measurement

nox, no2, pm2.5, pm10 Pollutant concentrations

site The site name. Useful for use with the popup and label arguments in openairmaps functions.

latitude, longitude Decimal latitude and longitude of the sites.

site.type Site type of the site (either "Urban Traffic" or "Urban Background").

wd Wind direction, in degrees from North, as a numeric vector.

ws Wind speed, in m/s, as numeric vector.

visibility The visibility in metres.

air_temp Air temperature in degrees Celcius.

Details

polar_data is supplied with the openairmaps package as an example dataset for use with documented examples.

Source

polar_data was compiled from data using the `openair::importAURN()` function from the openair package with meteorological data from the worldmet package.

Examples

```
# basic structure
head(polar_data)
```

pollroseMap

Pollution rose plots on interactive leaflet maps

Description

`pollroseMap()` creates a leaflet map using "pollution roses" as markers. Any number of pollutants can be specified using the `pollutant` argument, and multiple layers of markers can be added and toggled between using `control`. See `openair::pollutionRose()` for more information.

Usage

```
pollroseMap(
  data,
  pollutant = NULL,
  statistic = "prop.count",
  breaks = NULL,
  latitude = NULL,
  longitude = NULL,
  control = NULL,
  popup = NULL,
  label = NULL,
  provider = "OpenStreetMap",
  cols = "turbo",
  key = FALSE,
  draw.legend = TRUE,
  collapse.control = FALSE,
  iconWidth = 200,
  iconHeight = 200,
  fig.width = 3.5,
  fig.height = 3.5,
  type = NULL,
  ...
)
```

Arguments

`data` A data frame. The data frame must contain the data to plot the directional analysis marker, which includes wind speed (`ws`), wind direction (`wd`), and the column representing the concentration of a pollutant. In addition, `data` must include a decimal latitude and longitude.

pollutant	The column name(s) of the pollutant(s) to plot. If multiple pollutants are specified, they can be toggled between using a "layer control" interface.
statistic	The statistic to be applied to each data bin in the plot. Options currently include "prop.count", "prop.mean" and "abs.count". The default "prop.count" sizes bins according to the proportion of the frequency of measurements. Similarly, "prop.mean" sizes bins according to their relative contribution to the mean. "abs.count" provides the absolute count of measurements in each bin.
breaks	Most commonly, the number of break points. If not specified, each marker will independently break its supplied data at approximately 6 sensible break points. When breaks are specified, all markers will use the same break points. Breaks can also be used to set specific break points. For example, the argument <code>breaks = c(0, 1, 10, 100)</code> breaks the data into segments <1 , $1-10$, $10-100$, >100 .
latitude, longitude	The decimal latitude/longitude. If not provided, will be automatically inferred from data by looking for a column named "lat"/"latitude" or "lon"/"lng"/"long"/"longitude" (case-insensitively).
control	Column to be used for splitting the input data into different groups which can be selected between using a "layer control" interface. Appropriate columns could be those added by <code>openair::cutData()</code> or <code>openair::splitByDate()</code> . <code>control</code> cannot be used if multiple pollutant columns have been provided.
popup	Column to be used as the HTML content for marker popups. Popups may be useful to show information about the individual sites (e.g., site names, codes, types, etc.).
label	Column to be used as the HTML content for hover-over labels. Labels are useful for the same reasons as popups, though are typically shorter.
provider	The base map(s) to be used. See http://leaflet-extras.github.io/leaflet-providers/preview/ for a list of all base maps that can be used. If multiple base maps are provided, they can be toggled between using a "layer control" interface.
cols	The colours used for plotting.
key	Should a key for each marker be drawn? Default is FALSE.
draw.legend	When breaks are specified, should a shared legend be created at the side of the map? Default is TRUE.
collapse.control	Should the "layer control" interface be collapsed? Defaults to FALSE.
iconWidth	The actual width of the plot on the map in pixels.
iconHeight	The actual height of the plot on the map in pixels.
fig.width	The width of the plots to be produced in inches.
fig.height	The height of the plots to be produced in inches.
type	Deprecated. Please use <code>label</code> and/or <code>popup</code> to label different sites.
...	Arguments passed on to <code>openair::pollutionRose</code>
key.footer	Adds additional text/labels below the scale key. See <code>key.header</code> for further information.

`key.position` Location where the scale key is to plotted. Allowed arguments currently include “top”, “right”, “bottom” and “left”.

`paddle` Either TRUE or FALSE. If TRUE plots rose using ‘paddle’ style spokes. If FALSE plots rose using ‘wedge’ style spokes.

`seg` When `paddle = TRUE`, `seg` determines with width of the segments. For example, `seg = 0.5` will produce segments $0.5 * \text{angle}$.

`normalise` If TRUE each wind direction segment is normalised to equal one. This is useful for showing how the concentrations (or other parameters) contribute to each wind sector when the proportion of time the wind is from that direction is low. A line showing the probability that the wind directions is from a particular wind sector is also shown.

Value

A leaflet object.

See Also

Other directional analysis maps: [annulusMap\(\)](#), [freqMap\(\)](#), [percentileMap\(\)](#), [polarMap\(\)](#), [windroseMap\(\)](#)

Examples

```
## Not run:
pollroseMap(polar_data,
  pollutant = "nox",
  statistic = "prop.count",
  provider = "Stamen.Toner"
)

## End(Not run)
```

quickTextHTML

Automatic text formatting for openairmaps

Description

Workhorse function that automatically applies routine text formatting to common pollutant names which may be used in the HTML widgets produced by `openairmaps`.

Usage

```
quickTextHTML(text)
```

Arguments

`text` A character vector.

Details

`quickTextHTML()` is routine formatting lookup table. It screens the supplied character vector text and automatically applies formatting to any recognised character sub-series to properly render in HTML.

Value

The function returns an expression for HTML evaluation.

Author(s)

Jack Davison.

Examples

```
labs <- c("no2", "o3", "so2")
quickTextHTML(labs)
```

trajLevelMap

Trajectory level plots in leaflet

Description

This function plots back trajectories on a leaflet map. This function requires that data are imported using the `openair::importTraj()` function.

Usage

```
trajLevelMap(
  data,
  longitude = "lon",
  latitude = "lat",
  pollutant,
  statistic = "frequency",
  percentile = 90,
  lon.inc = 1,
  lat.inc = 1,
  min.bin = 1,
  cols = "default",
  alpha = 0.5,
  tile.border = NA,
  provider = "OpenStreetMap"
)
```

Arguments

data	Data frame, the result of importing a trajectory file using <code>openair::importTraj()</code> .
latitude, longitude	The decimal latitude/longitude.
pollutant	Pollutant to be plotted.
statistic	By default the function will plot the trajectory frequencies. There are also various ways of plotting concentrations. It is also possible to set <code>statistic = "difference"</code> . In this case trajectories where the associated concentration is greater than percentile are compared with the the full set of trajectories to understand the differences in frequencies of the origin of air masses. The comparison is made by comparing the percentage change in gridded frequencies. For example, such a plot could show that the top 10\ concentrations of PM10 tend to originate from air-mass origins to the east. If <code>statistic = "pscf"</code> then a Potential Source Contribution Function map is produced. If <code>statistic = "cwt"</code> then the Concentration Weighted Trajectory approach is used. If <code>statistic = "saqn"</code> then Simplified Quantitative Transport Bias Analysis is used. See "details" of <code>openair::trajLevel()</code> for more information.
percentile	For <code>openair::trajLevel()</code> . The percentile concentration of pollutant against which the all trajectories are compared.
lon.inc	The longitude-interval to be used for binning data.
lat.inc	The latitude-interval to be used for binning data.
min.bin	The minimum number of unique points in a grid cell. Counts below <code>min.bin</code> are set as missing.
cols	Colours to be used for plotting. Options include "default", "increment", "heat", "turbo" and RColorBrewer colours — see the <code>openair::openColours()</code> function for more details. For user defined the user can supply a list of colour names recognised by R (type <code>grDevices::colours()</code> to see the full list). An example would be <code>cols = c("yellow", "green", "blue")</code> .
alpha	Opacity of the tiles. Must be between 0 and 1.
tile.border	Colour to use for the border of binned tiles. Defaults to NA, which draws no border.
provider	The base map(s) to be used. See http://leaflet-extras.github.io/leaflet-providers/preview/ for a list of all base maps that can be used. If multiple base maps are provided, they can be toggled between using a "layer control" interface.

Value

A leaflet object.

See Also

Other trajectory maps: `trajMap()`

Examples

```
## Not run:
trajLevelMap(traj_data, pollutant = "pm2.5", statistic = "pscf", min.bin = 10)

## End(Not run)
```

trajMap

*Trajectory line plots in leaflet***Description**

This function plots back trajectories on a leaflet map. This function requires that data are imported using the `openair::importTraj()` function. Options are provided to colour the individual trajectories (e.g., by pollutant concentrations) or create "layer control" menus to show/hide different layers.

Usage

```
trajMap(
  data,
  longitude = "lon",
  latitude = "lat",
  colour,
  control = "default",
  cols = "default",
  alpha = 0.5,
  npoints = 12,
  provider = "OpenStreetMap",
  collapse.control = FALSE
)
```

Arguments

data	Data frame, the result of importing a trajectory file using <code>openair::importTraj()</code> .
latitude, longitude	The decimal latitude/longitude.
colour	Column to be used for colouring each trajectory. This column may be numeric, character or factor. This will commonly be a pollutant concentration which has been joined (e.g., by <code>dplyr::left_join()</code>) to the trajectory data by "date".
control	Column to be used for splitting the trajectories into different groups which can be selected between using a "layer control" menu.
cols	Colours to be used for plotting. Options include "default", "increment", "heat", "turbo" and RColorBrewer colours — see the <code>openair::openColours()</code> function for more details. For user defined the user can supply a list of colour names recognised by R (type <code>grDevices::colours()</code> to see the full list). An example

	would be <code>cols = c("yellow", "green", "blue")</code> . If the <code>"colour"</code> argument was not used, a single colour can be named which will be used consistently for all lines/points (e.g., <code>cols = "red"</code>).
<code>alpha</code>	Opacity of lines/points. Must be between 0 and 1.
<code>npoints</code>	A dot is placed every <code>npoints</code> along each full trajectory. For hourly back trajectories points are plotted every <code>npoints</code> hours. This helps to understand where the air masses were at particular times and get a feel for the speed of the air (points closer together correspond to slower moving air masses). Defaults to 12.
<code>provider</code>	The base map to be used. See http://leaflet-extras.github.io/leaflet-providers/preview/ for a list of all base maps that can be used.
<code>collapse.control</code>	Should the "layer control" interface be collapsed? Defaults to FALSE.

Value

A leaflet object.

See Also

Other trajectory maps: [trajLevelMap\(\)](#)

Examples

```
## Not run:
trajMap(traj_data, colour = "nox")

## End(Not run)
```

| traj_data | *Example data for trajectory mapping functions* |

Description

The `traj_data` dataset is provided as an example dataset as part of the `openairmaps` package. The dataset contains HYSPLIT back trajectory data for air mass parcels arriving in London in 2009. It has been joined with air quality pollutant concentrations from the "London N. Kensington" AURN urban background monitoring site.

Usage

```
traj_data
```

Format

A data frame with 53940 rows and 10 variables:

date The arrival time of the air-mass

receptor The receptor number

year Trajectory year

month Trajectory month

day Trajectory day

hour Trajectory hour

hour.inc Trajectory hour offset from the arrival date

lat Latitude

lon Longitude

height Height of trajectory in m

pressure Pressure of the trajectory in Pa

date2 Date of the trajectory

nox, no2, o3, pm10, pm2.5 Pollutant concentrations

Details

`traj_data` is supplied with the `openairmaps` package as an example dataset for use with documented examples.

Source

`traj_data` was compiled from data using the `openair::importTraj()` function from the `openair` package with air quality data from `openair::importAURN()` function.

Examples

```
# basic structure
head(traj_data)
```

windroseMap

Wind rose plots on interactive leaflet maps

Description

`windroseMap()` creates a leaflet map using wind roses as markers. Multiple layers of markers can be added and toggled between using `control`. See `openair::windRose()` for more information.

Usage

```

windroseMap(
  data,
  ws.int = 2,
  breaks = 4,
  latitude = NULL,
  longitude = NULL,
  control = NULL,
  popup = NULL,
  label = NULL,
  provider = "OpenStreetMap",
  cols = "turbo",
  key = FALSE,
  draw.legend = TRUE,
  collapse.control = FALSE,
  iconWidth = 200,
  iconHeight = 200,
  fig.width = 3.5,
  fig.height = 3.5,
  type = NULL,
  ...
)

```

Arguments

data	A data frame. The data frame must contain the data to plot a <code>openair::windRose()</code> , which includes wind speed (ws), and wind direction (wd). In addition, data must include a decimal latitude and longitude.
ws.int	The wind speed interval. Default is 2 m/s but for low met masts with low mean wind speeds a value of 1 or 0.5 m/s may be better.
breaks	Most commonly, the number of break points for wind speed in windRose. For windRose and the ws.int default of 2 m/s, the default, 4, generates the break points 2, 4, 6, 8 m/s. Breaks can also be used to set specific break points. For example, the argument <code>breaks = c(0, 1, 10, 100)</code> breaks the data into segments <1, 1-10, 10-100, >100.
latitude, longitude	The decimal latitude/longitude. If not provided, will be automatically inferred from data by looking for a column named "lat"/"latitude" or "lon"/"lng"/"long"/"longitude" (case-insensitively).
control	Column to be used for splitting the input data into different groups which can be selected between using a "layer control" interface. Appropriate columns could be those added by <code>openair::cutData()</code> or <code>openair::splitByDate()</code> . control cannot be used if multiple pollutant columns have been provided.
popup	Column to be used as the HTML content for marker popups. Popups may be useful to show information about the individual sites (e.g., site names, codes, types, etc.).

label	Column to be used as the HTML content for hover-over labels. Labels are useful for the same reasons as popups, though are typically shorter.
provider	The base map(s) to be used. See http://leaflet-extras.github.io/leaflet-providers/preview/ for a list of all base maps that can be used. If multiple base maps are provided, they can be toggled between using a "layer control" interface.
cols	The colours used for plotting.
key	Should a key for each marker be drawn? Default is FALSE.
draw.legend	Should a shared legend be created at the side of the map? Default is TRUE.
collapse.control	Should the "layer control" interface be collapsed? Defaults to FALSE.
iconWidth	The actual width of the plot on the map in pixels.
iconHeight	The actual height of the plot on the map in pixels.
fig.width	The width of the plots to be produced in inches.
fig.height	The height of the plots to be produced in inches.
type	Deprecated. Please use label and/or popup to label different sites.
...	Arguments passed on to <code>openair::windRose</code>
ws	Name of the column representing wind speed.
wd	Name of the column representing wind direction.
ws2, wd2	The user can supply a second set of wind speed and wind direction values with which the first can be compared. See <code>pollutionRose()</code> for more details.
angle	Default angle of "spokes" is 30. Other potentially useful angles are 45 and 10. Note that the width of the wind speed interval may need adjusting using width.
bias.corr	When angle does not divide exactly into 360 a bias is introduced in the frequencies when the wind direction is already supplied rounded to the nearest 10 degrees, as is often the case. For example, if angle = 22.5, N, E, S, W will include 3 wind sectors and all other angles will be two. A bias correction can made to correct for this problem. A simple method according to Applequist (2012) is used to adjust the frequencies.
grid.line	Grid line interval to use. If NULL, as in default, this is assigned based on the available data range. However, it can also be forced to a specific value, e.g. <code>grid.line = 10</code> . <code>grid.line</code> can also be a list to control the interval, line type and colour. For example <code>grid.line = list(value = 10, lty = 5, col = "purple")</code> .
width	For <code>paddle = TRUE</code> , the adjustment factor for width of wind speed intervals. For example, <code>width = 1.5</code> will make the paddle width 1.5 times wider.
seg	When <code>paddle = TRUE</code> , <code>seg</code> determines with width of the segments. For example, <code>seg = 0.5</code> will produce segments $0.5 * \text{angle}$.
auto.text	Either TRUE (default) or FALSE. If TRUE titles and axis labels will automatically try and format pollutant names and units properly, e.g., by subscripting the '2' in NO ₂ .

- offset** The size of the 'hole' in the middle of the plot, expressed as a percentage of the polar axis scale, default 10.
- normalise** If TRUE each wind direction segment is normalised to equal one. This is useful for showing how the concentrations (or other parameters) contribute to each wind sector when the proportion of time the wind is from that direction is low. A line showing the probability that the wind directions is from a particular wind sector is also shown.
- max.freq** Controls the scaling used by setting the maximum value for the radial limits. This is useful to ensure several plots use the same radial limits.
- paddle** Either TRUE or FALSE. If TRUE plots rose using 'paddle' style spokes. If FALSE plots rose using 'wedge' style spokes.
- key.header** Adds additional text/labels above the scale key. For example, passing `windRose(mydata, key.header = "ws")` adds the addition text as a scale header. Note: This argument is passed to `drawOpenKey()` via `quickText()`, applying the `auto.text` argument, to handle formatting.
- key.footer** Adds additional text/labels below the scale key. See `key.header` for further information.
- key.position** Location where the scale key is to be plotted. Allowed arguments currently include "top", "right", "bottom" and "left".
- dig.lab** The number of significant figures at which scientific number formatting is used in break point and key labelling. Default 5.
- include.lowest** Logical. If FALSE (the default), the first interval will be left exclusive and right inclusive. If TRUE, the first interval will be left and right inclusive. Passed to the `include.lowest` argument of `cut()`.
- statistic** The statistic to be applied to each data bin in the plot. Options currently include "prop.count", "prop.mean" and "abs.count". The default "prop.count" sizes bins according to the proportion of the frequency of measurements. Similarly, "prop.mean" sizes bins according to their relative contribution to the mean. "abs.count" provides the absolute count of measurements in each bin.
- pollutant** Alternative data series to be sampled instead of wind speed. The `windRose()` default NULL is equivalent to `pollutant = "ws"`. Use in `pollutionRose()`.
- angle.scale** The scale is by default shown at a 315 degree angle. Sometimes the placement of the scale may interfere with an interesting feature. The user can therefore set `angle.scale` to another value (between 0 and 360 degrees) to mitigate such problems. For example `angle.scale = 45` will draw the scale heading in a NE direction.
- border** Border colour for shaded areas. Default is no border.

Value

A leaflet object.

See Also

Other directional analysis maps: `annulusMap()`, `freqMap()`, `percentileMap()`, `polarMap()`, `pollroseMap()`

Examples

```
## Not run:  
windroseMap(polar_data,  
            provider = "Stamen.Toner"  
            )  
  
## End(Not run)
```

Index

- * **datasets**
 - polar_data, 24
 - traj_data, 31
- * **directional analysis maps**
 - annulusMap, 6
 - freqMap, 11
 - percentileMap, 16
 - polarMap, 18
 - pollroseMap, 25
 - windroseMap, 32
- * **methods**
 - quickTextHTML, 27
- * **trajectory maps**
 - trajLevelMap, 28
 - trajMap, 30
- addPolarMarkers, 2
- addTrajPaths, 4
- addTrajPaths(), 5
- annulusMap, 6, 14, 18, 23, 27, 35
- annulusMap(), 6
- buildPopup, 10
- cut(), 35
- dplyr::left_join(), 30
- drawOpenKey(), 35
- freqMap, 9, 11, 18, 23, 27, 35
- freqMap(), 11
- grDevices::colours(), 29, 30
- leaflet::addCircleMarkers(), 2, 5
- leaflet::addLayersControl(), 3, 4
- leaflet::addMarkers(), 2, 4
- leaflet::addPolylines(), 5
- leaflet::clearGroup(), 3, 4
- leaflet::leaflet(), 2, 4
- networkMap, 14
- networkMap(), 15
- openair::cutData(), 7, 12, 17, 19, 26, 33
- openair::importAURN(), 24, 32
- openair::importMeta(), 14, 15
- openair::importTraj(), 4, 28–30, 32
- openair::openColours(), 29, 30
- openair::percentileRose, 17
- openair::percentileRose(), 3, 16
- openair::polarAnnulus, 7
- openair::polarAnnulus(), 3, 6
- openair::polarFreq, 13
- openair::polarFreq(), 3, 11
- openair::polarPlot, 20
- openair::polarPlot(), 3, 18
- openair::pollutionRose, 26
- openair::pollutionRose(), 3, 25
- openair::splitByDate(), 7, 12, 17, 19, 26, 33
- openair::trajLevel(), 29
- openair::windRose, 34
- openair::windRose(), 3, 32, 33
- percentileMap, 9, 14, 16, 23, 27, 35
- percentileMap(), 16
- polar_data, 24
- polarMap, 9, 14, 18, 18, 27, 35
- polarMap(), 2, 10, 18
- pollroseMap, 9, 14, 18, 23, 25, 35
- pollroseMap(), 25
- pollutionRose(), 34, 35
- quickText(), 35
- quickTextHTML, 27
- quickTextHTML(), 28
- tibble::tibble(), 11
- traj_data, 31
- trajLevelMap, 28, 31

trajMap, [29](#), [30](#)

trajMap(), [4](#)

windRose(), [35](#)

windroseMap, [9](#), [14](#), [18](#), [23](#), [27](#), [32](#)

windroseMap(), [32](#)