

Package ‘pmxTools’

August 26, 2020

Type Package

Title Pharmacometric and Pharmacokinetic Toolkit

Version 1.2.1

Maintainer Justin Wilkins <justin.wilkins@occams.com>

Contact Justin Wilkins <justin.wilkins@occams.com>

Description Pharmacometric tools for common data analytical tasks; closed-form solutions for calculating concentrations at given times after dosing based on compartmental PK models (1-compartment, 2-compartment and 3-compartment, covering infusions, zero- and first-order absorption, and lag times, after single doses and at steady state, per Bertrand & Mentre (2008) <<http://lixoft.com/wp-content/uploads/2016/03/PKPDlibrary.pdf>>); parametric simulation from NONMEM-generated parameter estimates and other output; and parsing, tabulating and plotting results generated by Perl-speaks-NONMEM (PsN).

License GPL-2

URL <https://github.com/kestrel99/pmxTools>

BugReports <https://github.com/kestrel99/pmxTools/issues>

LazyData TRUE

RoxygenNote 7.1.1

Imports ggplot2, ggrepel, gridExtra, chron, xml2, dplyr (>= 0.8.5)

Depends MASS, stringr, magrittr, data.tree, DiagrammeR

Suggests testthat, knitr, rmarkdown

Encoding UTF-8

VignetteBuilder knitr

NeedsCompilation no

Author Justin Wilkins [aut, cre] (<<https://orcid.org/0000-0002-7099-9396>>),
Bill Denney [aut] (<<https://orcid.org/0000-0002-5759-428X>>),
Rik Schoemaker [aut],

Leonid Gibiansky [ctb],
 Andrew Hooker [ctb],
 E. Niclas Jonsson [ctb],
 Mats O. Karlsson [ctb],
 John Johnson [ctb]

Repository CRAN

Date/Publication 2020-08-26 21:10:03 UTC

R topics documented:

calc_derived	3
calc_sd_1cmt	5
calc_sd_2cmt	7
calc_sd_3cmt	9
calc_ss_1cmt	10
calc_ss_2cmt	12
calc_ss_3cmt	14
gcv_convert	15
get_auc	16
get_est_table	17
get_omega	18
get_probinfo	19
get_shrinkage	20
get_sigma	21
get_theta	22
gm	23
pcv	24
pk_curve	24
plot_nmprogress	25
plot_scm	26
read_nm	29
read_nmcov	30
read_nmext	31
read_nmtables	32
read_nm_all	34
read_nm_multi_table	35
read_nm_std_ext	36
read_scm	36
rnm	38
sample_omega	40
sample_sigma	41
sample_uncert	42
table_rtf	43

Index

44

calc_derived	<i>Calculate derived pharmacokinetic parameters for a 1-, 2-, or 3-compartment linear model.</i>
--------------	--

Description

Calculate derived pharmacokinetic parameters for a 1-, 2-, or 3-compartment linear model.

Usage

```
calc_derived(..., verbose = FALSE)
```

```
calc_derived_1cpt(  
  CL,  
  V = NULL,  
  V1 = NULL,  
  ka = NULL,  
  tlag = NULL,  
  type = "all",  
  sigdig = 5  
)
```

```
calc_derived_2cpt(  
  CL,  
  V1 = NULL,  
  V2,  
  Q2 = NULL,  
  V = NULL,  
  Q = NULL,  
  ka = NULL,  
  tlag = NULL,  
  type = "all",  
  sigdig = 5  
)
```

```
calc_derived_3cpt(  
  CL,  
  V1 = NULL,  
  V2,  
  V3,  
  Q2 = NULL,  
  Q3,  
  V = NULL,  
  Q = NULL,  
  ka = NULL,  
  tlag = NULL,  
  type = "all",
```

```
    sigdig = 5
  )
```

Arguments

...	Passed to the other calc_derived_*() functions.
verbose	For calc_derived(), provide a message indicating the type of model detected.
CL	Clearance (volume per time units, e.g. L/h)
V1, V	Central volume of distribution (volume units, e.g. L). Values are synonyms; use only one.
ka	Absorption rate (inverse time units, e.g. 1/h)
tlag	Absorption lag time (time units, e.g. h)
type	Parameters to return. Default is "all". If not "all", this may be a vector from the names of the return value list.
sigdig	Number of significant digits to be returned. Default is 5.
V2	First peripheral volume of distribution (volume units, e.g. L)
Q2, Q	Intercompartmental clearance from central to first peripheral compartment (volume per time units, e.g. L/h). Values are synonyms; use only one.
V3	Second peripheral volume of distribution (volume units, e.g. L)
Q3	Intercompartmental clearance from central to second peripheral compartment (volume per time units, e.g. L/h)

Value

Return a list of derived PK parameters for a 1-, 2-, or 3-compartment linear model given provided clearances and volumes based on the type.

- V_{ss}: Volume of distribution at steady state, V_{ss} (volume units, e.g. L); 1-, 2-, and 3-compartment
- k₁₀: First-order elimination rate, k_{10} (inverse time units, e.g. 1/h); 1-, 2-, and 3-compartment
- k₁₂: First-order rate of transfer from central to first peripheral compartment, k_{12} (inverse time units, e.g. 1/h); 2- and 3-compartment
- k₂₁: First-order rate of transfer from first peripheral to central compartment, k_{21} (inverse time units, e.g. 1/h); 2- and 3-compartment
- k₁₃: First-order rate of transfer from central to second peripheral compartment, k_{13} (inverse time units, e.g. 1/h); 3-compartment
- k₃₁: First-order rate of transfer from second peripheral to central compartment, k_{31} (inverse time units, e.g. 1/h); 3-compartment
- thalf_alpha: $t_{1/2,\alpha}$ (time units, e.g. h); 1-, 2-, and 3-compartment
- thalf_beta: $t_{1/2,\beta}$ (time units, e.g. h); 2- and 3-compartment
- thalf_gamma: $t_{1/2,\gamma}$ (time units, e.g. h); 3-compartment
- alpha: α ; 1-, 2-, and 3-compartment
- beta: β ; 2- and 3-compartment

- gamma: β ; 3-compartment
- trueA: true A; 1-, 2-, and 3-compartment
- trueB: true B; 2- and 3-compartment
- trueC: true C; 3-compartment
- fracA: fractional A; 1-, 2-, and 3-compartment
- fracB: fractional B; 2- and 3-compartment
- fracC: fractional C; 3-compartment

The input parameters with standardized names (V1, V2, V3, CL, Q2, and Q3) are also returned in the list, and if provided, additional PK parameters of 'ka' and 'lag' are also returned in the list. All inputs may be scalars or vectors.

Author(s)

Justin Wilkins, <justin.wilkins@occams.com>

References

Shafer S. L. CONVERT.XLS

Rowland M, Tozer TN. Clinical Pharmacokinetics and Pharmacodynamics: Concepts and Applications (4th). Lippincott Williams & Wilkins, Philadelphia, 2010.

Examples

```
params <- calc_derived(CL=29.4, V1=23.4, V2=114, V3=4614, Q2=270, Q3=73)
params <- calc_derived_1cpt(CL=16, V=25)
params <- calc_derived_2cpt(CL=16, V1=25, V2=50, Q=0.5)
params <- calc_derived_3cpt(CL=29.4, V1=23.4, V2=114, V3=4614, Q2=270, Q3=73)
```

calc_sd_1cmt

Calculate C(t) for a 1-compartment linear model

Description

Calculate C(t) for a 1-compartment linear model

Usage

```
calc_sd_1cmt(t, dose, dur = NULL, tinf = NULL, ...)
```

```
calc_sd_1cmt_linear_bolus(t, dose, ...)
```

```
calc_sd_1cmt_linear_oral_1_lag(t, dose, ...)
```

```
calc_sd_1cmt_linear_infusion(t, dose, tinf, ...)
```

```
calc_sd_1cmt_linear_oral_0(t, dose, dur, ...)
```

```
calc_sd_1cmt_linear_oral_1(t, dose, ...)
```

```
calc_sd_1cmt_linear_oral_0_lag(t, dose, dur, ...)
```

Arguments

t	Time after dose (h)
dose	Dose
dur	Duration of zero-order absorption (h)
tinf	Duration of infusion (h)
...	Passed to 'calc_derived_1cpt()'

Value

Concentration of drug at requested time (t) after a single dose, given provided set of parameters and variables.

Functions

- `calc_sd_1cmt_linear_bolus`: Calculate C(t) for a 1-compartment linear model after a single IV bolus dose
- `calc_sd_1cmt_linear_oral_1_lag`: Calculate C(t) for a 1-compartment linear model with first-order absorption after a single oral dose, with lag time
- `calc_sd_1cmt_linear_infusion`: Calculate C(t) for a 1-compartment linear model after a single IV infusion
- `calc_sd_1cmt_linear_oral_0`: Calculate C(t) for a 1-compartment linear model with zero-order absorption after a single oral dose
- `calc_sd_1cmt_linear_oral_1`: Calculate C(t) for a 1-compartment linear model with first-order absorption after a single oral dose
- `calc_sd_1cmt_linear_oral_0_lag`: Calculate C(t) for a 1-compartment linear model with zero-order absorption after a single oral dose, with lag time

Author(s)

Justin Wilkins, <justin.wilkins@occams.com>

References

Bertrand J & Mentre F (2008). Mathematical Expressions of the Pharmacokinetic and Pharmacodynamic Models implemented in the Monolix software. <http://lixoft.com/wp-content/uploads/2016/03/PKPDlibrary.pdf>

Rowland M, Tozer TN. Clinical Pharmacokinetics and Pharmacodynamics: Concepts and Applications (4th). Lippincott Williams & Wilkins, Philadelphia, 2010.

Examples

```
Ct <- calc_sd_1cmt_linear_bolus(t=0:24, CL=6, V=25, dose=600)
Ct <- calc_sd_1cmt_linear_oral_1_lag(t=0:24, CL=6, V=25, ka=1.1, dose=600, tlag=2)
Ct <- calc_sd_1cmt_linear_infusion(t=0:24, CL=6, V=25, dose=600, tinf=1)
Ct <- calc_sd_1cmt_linear_oral_0(t=0:24, CL=6, V=25, dur=1.5, dose=600)
Ct <- calc_sd_1cmt_linear_oral_1(t=0:24, CL=6, V=25, ka=1.1, dose=600)
Ct <- calc_sd_1cmt_linear_oral_0_lag(t=0:24, CL=6, V=25, dur=1.5, dose=600, tlag=1.5)
```

`calc_sd_2cmt`*Calculate C(t) for a 1-compartment linear model*

Description

Calculate C(t) for a 1-compartment linear model

Usage

```
calc_sd_2cmt(t, dose, dur = NULL, tinf = NULL, ...)
```

```
calc_sd_2cmt_linear_bolus(t, dose, ...)
```

```
calc_sd_2cmt_linear_oral_1_lag(t, dose, ...)
```

```
calc_sd_2cmt_linear_infusion(t, dose, tinf, ...)
```

```
calc_sd_2cmt_linear_oral_0_lag(t, dose, dur, ...)
```

```
calc_sd_2cmt_linear_oral_0_lag(t, dose, dur, ...)
```

```
calc_sd_2cmt_linear_oral_1(t, dose, ...)
```

```
calc_sd_2cmt_linear_oral_0(t, dose, dur, ...)
```

Arguments

t	Time after dose (h)
dose	Dose
dur	Duration of zero-order absorption (h)
tinf	Duration of infusion (h)
...	Passed to 'calc_derived_2cpt()'

Value

Concentration of drug at requested time (t) after a single dose, given provided set of parameters and variables.

Functions

- `calc_sd_2cmt_linear_bolus`: Calculate $C(t)$ for a 2-compartment linear model after a single IV bolus dose
- `calc_sd_2cmt_linear_oral_1_lag`: Calculate $C(t)$ for a 2-compartment linear model after a single first-order oral dose with a lag time
- `calc_sd_2cmt_linear_infusion`: Calculate $C(t)$ for a 2-compartment linear model after a single infusion
- `calc_sd_2cmt_linear_oral_0_lag`: Calculate $C(t)$ for a 2-compartment linear model after a single zero-order oral dose, with lag time
- `calc_sd_2cmt_linear_oral_0_lag`: Calculate $C(t)$ for a 2-compartment linear model after a single zero-order oral dose, with lag time
- `calc_sd_2cmt_linear_oral_1`: Calculate $C(t)$ for a 2-compartment linear model after a single first-order oral dose
- `calc_sd_2cmt_linear_oral_0`: Calculate $C(t)$ for a 2-compartment linear model after a single zero-order oral dose

Author(s)

Justin Wilkins, <justin.wilkins@occams.com>

References

Bertrand J & Mentre F (2008). Mathematical Expressions of the Pharmacokinetic and Pharmacodynamic Models implemented in the Monolix software. <http://lixoft.com/wp-content/uploads/2016/03/PKPDlibrary.pdf>

Rowland M, Tozer TN. Clinical Pharmacokinetics and Pharmacodynamics: Concepts and Applications (4th). Lippincott Williams & Wilkins, Philadelphia, 2010.

Examples

```
Ct <- calc_sd_2cmt_linear_bolus(t = 11.75, CL = 7.5, V1 = 20, V2 = 30, Q = 0.5, dose = 10)
Ct <- calc_sd_2cmt_linear_oral_1_lag(t = 11.75, CL = 7.5, V1 = 20, V2 = 30, Q = 0.5,
  dose = 1000, ka = 1, tlag = 2)
Ctrough <- calc_sd_2cmt_linear_infusion(t = 11.75, CL = 7.5, V1 = 20, V2 = 30, Q = 0.5,
  dose = 10, tinf = 1)
Ctrough <- calc_sd_2cmt_linear_oral_0_lag(t = 11.75, CL = 7.5, V1 = 20, V2 = 30, Q = 0.5,
  dose = 1000, dur = 1, tlag=2)
Ct <- calc_sd_2cmt_linear_oral_0_lag(t = 11.75, CL = 7.5, V1 = 20, V2 = 30, Q = 0.5,
  dose = 1000, dur = 1, tlag=2)
Ct <- calc_sd_2cmt_linear_oral_1(t = 11.75, CL = 7.5, V1 = 20, V2 = 30, Q = 0.5,
  dose = 1000, ka = 1)
Ct <- calc_sd_2cmt_linear_oral_0(t = 11.75, CL = 7.5, V1 = 20, V2 = 30, Q = 0.5,
  dose = 1000, dur = 1)
```

calc_sd_3cmt	<i>Calculate C(t) for a 1-compartment linear model</i>
--------------	--

Description

Calculate C(t) for a 1-compartment linear model

Usage

calc_sd_3cmt(t, dose, dur = NULL, tinf = NULL, ...)

calc_sd_3cmt_linear_bolus(t, dose, ...)

calc_sd_3cmt_linear_oral_1_lag(t, dose, ...)

calc_sd_3cmt_linear_infusion(t, dose, tinf, ...)

calc_sd_3cmt_linear_oral_0(t, dose, dur, ...)

calc_sd_3cmt_linear_oral_0_lag(t, dose, dur, ...)

calc_sd_3cmt_linear_oral_1(t, dose, ...)

Arguments

t	Time after dose (h)
dose	Dose
dur	Duration of zero-order absorption (h)
tinf	Duration of infusion (h)
...	Passed to 'calc_derived_3cpt()'

Value

Concentration of drug at requested time (t) after a single dose, given provided set of parameters and variables.

Functions

- calc_sd_3cmt_linear_bolus: Calculate C(t) for a 3-compartment linear model after a single IV bolus dose
- calc_sd_3cmt_linear_oral_1_lag: Calculate C(t) for a 3-compartment linear model after a single oral dose
- calc_sd_3cmt_linear_infusion: Calculate C(t) for a 3-compartment linear model after a single IV infusion
- calc_sd_3cmt_linear_oral_0: Calculate C(t) for a 3-compartment linear model after a single dose, with zero-order absorption

- `calc_sd_3cmt_linear_oral_0_lag`: Calculate $C(t)$ for a 3-compartment linear model after a single dose, with zero-order absorption and a lag time
- `calc_sd_3cmt_linear_oral_1`: Calculate $C(t)$ for a 3-compartment linear model after a single oral dose

Author(s)

Justin Wilkins, <justin.wilkins@occams.com>

References

Bertrand J & Mentre F (2008). Mathematical Expressions of the Pharmacokinetic and Pharmacodynamic Models implemented in the Monolix software. <http://lixoft.com/wp-content/uploads/2016/03/PKPDlibrary.pdf>

Rowland M, Tozer TN. Clinical Pharmacokinetics and Pharmacodynamics: Concepts and Applications (4th). Lippincott Williams & Wilkins, Philadelphia, 2010.

Examples

```
Ct <- calc_sd_3cmt_linear_bolus(t = 11.75, CL = 3.5, V1 = 20, V2 = 500,
  V3 = 200, Q2 = 0.5, Q3 = 0.05, dose = 100)
Ct <- calc_sd_3cmt_linear_oral_1_lag(t = 11.75, CL = 3.5, V1 = 20, V2 = 500,
  V3 = 200, Q2 = 0.5, Q3 = 0.05, ka = 1, dose = 100, tlag = 1.5)
Ct <- calc_sd_3cmt_linear_infusion(t = 11.75, CL = 3.5, V1 = 20, V2 = 500,
  V3 = 200, Q2 = 0.5, Q3 = 0.05, dose = 100, tinf=1)
Ct <- calc_sd_3cmt_linear_oral_0(t = 11.75, CL = 3.5, V1 = 20, V2 = 500,
  V3 = 200, Q2 = 0.5, Q3 = 0.05, dur = 1, dose = 100)
Ct <- calc_sd_3cmt_linear_oral_0_lag(t = 11.75, CL = 3.5, V1 = 20, V2 = 500,
  V3 = 200, Q2 = 0.5, Q3 = 0.05, dur = 1, dose = 100, tlag=1.5)
Ct <- calc_sd_3cmt_linear_oral_1(t = 11.75, CL = 3.5, V1 = 20, V2 = 500,
  V3 = 200, Q2 = 0.5, Q3 = 0.05, ka = 1, dose = 100)
```

calc_ss_1cmt

Calculate $C(t)$ for a 1-compartment linear model at steady-state

Description

Calculate $C(t)$ for a 1-compartment linear model at steady-state

Usage

```
calc_ss_1cmt(tad, tau, dose, dur = NULL, tinf = NULL, ...)
```

```
calc_ss_1cmt_linear_bolus(tad, tau, dose, ...)
```

```
calc_ss_1cmt_linear_infusion(tad, tau, dose, tinf, ...)
```

```
calc_ss_1cmt_linear_oral_0(tad, tau, dose, dur, ...)
```

```
calc_ss_1cmt_linear_oral_0_lag(tad, tau, dose, dur, ...)
```

```
calc_ss_1cmt_linear_oral_1_lag(tad, tau, dose, ...)
```

```
calc_ss_1cmt_linear_oral_1(tad, tau, dose, ...)
```

Arguments

tad	Time after dose (h)
tau	Dosing interval (h)
dose	Dose
dur	Duration of zero-order absorption (h)
tinf	Duration of infusion (h)
...	Passed to 'calc_derived_1cpt()'

Value

Concentration of drug at requested time (t) after a single dose, given provided set of parameters and variables.

Functions

- `calc_ss_1cmt_linear_bolus`: Calculate C(t) for a 1-compartment linear model with IV bolus dosing at steady state
- `calc_ss_1cmt_linear_infusion`: Calculate C(t) for a 1-compartment linear model with infusion at steady state
- `calc_ss_1cmt_linear_oral_0`: Calculate C(t) for a 1-compartment linear model with zero-order oral absorption at steady state
- `calc_ss_1cmt_linear_oral_0_lag`: Calculate C(t) for a 1-compartment linear model with zero-order oral absorption at steady state, with lag time
- `calc_ss_1cmt_linear_oral_1_lag`: Calculate C(t) for a 1-compartment linear model with first-order oral absorption at steady state, with lag time
- `calc_ss_1cmt_linear_oral_1`: Calculate C(t) for a 1-compartment linear model with first-order oral absorption at steady state

Author(s)

Justin Wilkins, <justin.wilkins@occams.com>

References

Bertrand J & Mentre F (2008). Mathematical Expressions of the Pharmacokinetic and Pharmacodynamic Models implemented in the Monolix software. <http://lixoft.com/wp-content/uploads/2016/03/PKPDlibrary.pdf>

Rowland M, Tozer TN. Clinical Pharmacokinetics and Pharmacodynamics: Concepts and Applications (4th). Lippincott Williams & Wilkins, Philadelphia, 2010.

Examples

```

Ct <- calc_ss_1cmt_linear_bolus(t=0:24, CL=6, V=25, dose=600, tau=24)
Ct <- calc_ss_1cmt_linear_infusion(tad=0:36, CL=2, V=25, dose=600, tinf=1, tau=24)
Ct <- calc_ss_1cmt_linear_oral_0(tad=0:36, CL=2, V=25, dose=600, dur=1, tau=24)
Ct <- calc_ss_1cmt_linear_oral_0_lag(tad=0:36, CL=2, V=25, dose=600, dur=1, tau=24, tlag=1.5)
Ct <- calc_ss_1cmt_linear_oral_1_lag(tad=0:36, CL=2, V=25, dose=600,
  ka=0.25, tlag=0.75, tau=24)
Ct <- calc_ss_1cmt_linear_oral_1(tad=0:36, CL=2, V=25, dose=600, ka=0.25, tau=24)

```

calc_ss_2cmt

Calculate C(t) for a 2-compartment linear model at steady-state

Description

Calculate C(t) for a 2-compartment linear model at steady-state

Usage

```

calc_ss_2cmt(tad, tau, dose, dur = NULL, tinf = NULL, ...)
calc_ss_2cmt_linear_bolus(tad, tau, dose, ...)
calc_ss_2cmt_linear_infusion(tad, tau, dose, tinf, ...)
calc_ss_2cmt_linear_oral_0(tad, tau, dose, dur, ...)
calc_ss_2cmt_linear_oral_1_lag(tad, tau, dose, ...)
calc_ss_2cmt_linear_oral_0_lag(tad, tau, dose, dur, ...)
calc_ss_2cmt_linear_oral_1(tad, tau, dose, ...)

```

Arguments

tad	Time after dose (h)
tau	Dosing interval (h)
dose	Dose
dur	Duration of zero-order absorption (h)
tinf	Duration of infusion (h)
...	Passed to 'calc_derived_2cpt()'

Value

Concentration of drug at requested time (t) at steady-state, given provided set of parameters and variables.

Functions

- `calc_ss_2cmt_linear_bolus`: Calculate C(t) for a 2-compartment linear model with IV bolus dosing at steady-state
- `calc_ss_2cmt_linear_infusion`: Calculate C(t) for a 2-compartment linear model with infusion at steady state
- `calc_ss_2cmt_linear_oral_0`: Calculate C(t) for a 2-compartment linear model at steady-state with zero-order oral dosing
- `calc_ss_2cmt_linear_oral_1_lag`: Calculate C(t) for a 2-compartment linear model at steady-state with first-order oral dosing
- `calc_ss_2cmt_linear_oral_0_lag`: Calculate C(t) for a 2-compartment linear model at steady-state with zero-order oral dosing and a lag time
- `calc_ss_2cmt_linear_oral_1`: Calculate C(t) for a 2-compartment linear model at steady-state with first-order oral dosing

Author(s)

Justin Wilkins, <justin.wilkins@occams.com>

References

Bertrand J & Mentre F (2008). Mathematical Expressions of the Pharmacokinetic and Pharmacodynamic Models implemented in the Monolix software. <http://lixoft.com/wp-content/uploads/2016/03/PKPDlibrary.pdf>

Rowland M, Tozer TN. Clinical Pharmacokinetics and Pharmacodynamics: Concepts and Applications (4th). Lippincott Williams & Wilkins, Philadelphia, 2010.

Examples

```
Ct <- calc_ss_2cmt_linear_bolus(tad = 11.75, CL = 7.5, V1 = 20, V2 = 30, Q = 0.5,
  dose = 10, tau=24)
Ct <- calc_ss_2cmt_linear_infusion(tad = 11.75, CL = 7.5, V1 = 20, V2 = 30, Q = 0.5,
  dose = 10, tinf = 1, tau = 12)
Ct <- calc_ss_2cmt_linear_oral_0(tad = 23, CL = 2.5, V1 = 20, V2 = 30, Q = 0.5,
  dose = 1000, dur = 1, tau = 24)
Ct <- calc_ss_2cmt_linear_oral_1_lag(tad = 11.75, CL = 7.5, V1 = 20, V2 = 30, Q = 0.5,
  dose = 1000, ka = 1, tau=24, tlag=2)
Ct <- calc_ss_2cmt_linear_oral_0_lag(tad = 23, CL = 2.5, V1 = 20, V2 = 30, Q = 0.5,
  dose = 1000, dur = 1, tau = 24, tlag=2)
Ct <- calc_ss_2cmt_linear_oral_1(tad = 11.75, CL = 7.5, V1 = 20, V2 = 30, Q = 0.5,
  dose = 1000, ka = 1, tau=24)
```

`calc_ss_3cmt`*Calculate C(t) for a 3-compartment linear model at steady-state*

Description

Calculate C(t) for a 3-compartment linear model at steady-state

Usage

```
calc_ss_3cmt(tad, tau, dose, dur = NULL, tinf = NULL, ...)
```

```
calc_ss_3cmt_linear_bolus(tad, tau, dose, ...)
```

```
calc_ss_3cmt_linear_oral_1_lag(tad, tau, dose, ...)
```

```
calc_ss_3cmt_linear_infusion(tad, tau, dose, tinf, ...)
```

```
calc_ss_3cmt_linear_oral_0(tad, tau, dose, dur, ...)
```

```
calc_ss_3cmt_linear_oral_0_lag(tad, tau, dose, dur, ...)
```

```
calc_ss_3cmt_linear_oral_1(tad, tau, dose, ...)
```

Arguments

<code>tad</code>	Time after dose (h)
<code>tau</code>	Dosing interval (h)
<code>dose</code>	Dose
<code>dur</code>	Duration of zero-order absorption (h)
<code>tinf</code>	Duration of infusion (h)
<code>...</code>	Passed to 'calc_derived_3cpt()'

Value

Concentration of drug at requested time (t) at steady-state, given provided set of parameters and variables.

Functions

- `calc_ss_3cmt_linear_bolus`: Calculate C(t) for a 3-compartment linear model at steady state with IV bolus dosing
- `calc_ss_3cmt_linear_oral_1_lag`: Calculate C(t) for a 3-compartment linear model at steady-state with first-order oral dosing with a lag time
- `calc_ss_3cmt_linear_infusion`: Calculate C(t) for a 3-compartment linear model at steady state with IV infusions

- `calc_ss_3cmt_linear_oral_0`: Calculate C(t) for a 3-compartment linear model at steady state, with zero-order absorption
- `calc_ss_3cmt_linear_oral_0_lag`: Calculate C(t) for a 3-compartment linear model at steady state, with zero-order absorption and lag time
- `calc_ss_3cmt_linear_oral_1`: Calculate C(t) for a 3-compartment linear model at steady-state with first-order oral dosing

Author(s)

Justin Wilkins, <justin.wilkins@occams.com>

References

Bertrand J & Mentre F (2008). Mathematical Expressions of the Pharmacokinetic and Pharmacodynamic Models implemented in the Monolix software. <http://lixoft.com/wp-content/uploads/2016/03/PKPDlibrary.pdf>

Rowland M, Tozer TN. Clinical Pharmacokinetics and Pharmacodynamics: Concepts and Applications (4th). Lippincott Williams & Wilkins, Philadelphia, 2010.

Examples

```
Ct <- calc_ss_3cmt_linear_bolus(t = 11.75, CL = 3.5, V1 = 20, V2 = 500,
  V3 = 200, Q2 = 0.5, Q3 = 0.05, dose = 100, tau=24)
Ctrough <- calc_ss_3cmt_linear_oral_1_lag(t = 11.75, CL = 3.5, V1 = 20, V2 = 500,
  V3 = 200, Q2 = 0.5, Q3 = 0.05, ka = 1, dose = 100, tau=24, tlag = 1.5)
Ct <- calc_ss_3cmt_linear_infusion(tad = 11.75, CL = 2.5, V1 = 20, V2 = 50,
  V3 = 100, Q2 = 0.5, Q3 = 0.05, dose = 1000, tinf=1, tau=24)
Ct <- calc_ss_3cmt_linear_oral_0(tad = 11.75, CL = 3.5, V1 = 20, V2 = 500,
  V3 = 200, Q2 = 0.5, Q3 = 0.05, dur = 1, dose = 100, tau = 24)
Ct <- calc_ss_3cmt_linear_oral_0_lag(tad = 11.75, CL = 3.5, V1 = 20, V2 = 500,
  V3 = 200, Q2 = 0.5, Q3 = 0.05, dur = 1, dose = 100, tau = 24, tlag = 1.5)
Ct <- calc_ss_3cmt_linear_oral_1(tad = 11.75, CL = 3.5, V1 = 20,
  V2 = 500, V3 = 200, Q2 = 0.5, Q3 = 0.05, ka = 1, dose = 100, tau = 24)
```

`gcv_convert`

Convert geometric variance or standard deviation to a geometric coefficient of variation

Description

The equation used is: $100 \times \sqrt{\exp(\text{gvar}) - 1}$

Usage

```
gcv_convert(gvar = gsd^2, gsd)
```

Arguments

gvar	The geometric variance (note that this is the variance not a vector of values to compute the gcv from)
gsd	The geometric standard deviation

Value

Geometric coefficient of variation

Author(s)

Bill Denney

References

<https://www.cognigen.com/nonmem/nm/99feb042003.html>
<http://onbiostatistics.blogspot.com/2008/07/geometric-statistics-geometric-cv-vs.html>

Examples

```
gcv_convert(0.2)
gcv_convert(gsd=0.2)
```

get_auc	<i>Calculate the area under the curve (AUC) for each subject over the time interval for dependent variables (dv) using the trapezoidal rule.</i>
---------	--

Description

Calculate the area under the curve (AUC) for each subject over the time interval for dependent variables (dv) using the trapezoidal rule.

Usage

```
get_auc(data, time = "TIME", id = "ID", dv = "DV")
```

Arguments

data	A data frame.
time	A string containing the name of the chronologically ordered time variable in data.
id	A string containing the name of the ID column (defining subject level data) in data.
dv	A string containing the name of the dependent variable column in data.

Value

A data frame containing one AUC value for every subject as defined by id.

Based on the AUC function originally written by Leonid Gibiansky in package MIFuns 5.1, from Metrum Institute.

Author(s)

Leonid Gibiansky, <lgibiansky@quantpharm.com>

References

<https://code.google.com/archive/p/mifuns/>

Examples

```
## Not run:  
AUCs <- get_auc(myAUCdata)  
  
## End(Not run)
```

get_est_table	<i>Create a table of model parameter estimates from a NONMEM output object.</i>
---------------	---

Description

Create a table of model parameter estimates from a NONMEM output object.

Usage

```
get_est_table(  
  x,  
  thetaLabels = c(),  
  omegaLabels = c(),  
  sigmaLabels = c(),  
  sigdig = 3  
)
```

Arguments

x	A NONMEM output object generated using read_nm .
thetaLabels	A vector containing labels for THETA parameters.
omegaLabels	A vector containing labels for OMEGA parameters.
sigmaLabels	A vector containing labels for SIGMA parameters.
sigdig	The desired number of significant digits to display.

Value

A named vector of NONMEM model parameter estimates.

Author(s)

Justin Wilkins, <justin.wilkins@occams.com>

See Also

NONMEM (<http://www.iconplc.com/innovation/nonmem/>)

Examples

```
## Not run:
nmOutput <- read_nm("run315.xml")
estTab   <- get_est_table(nmOutput)

## End(Not run)
```

get_omega	<i>Extract variability parameter estimates from a NONMEM output object.</i>
-----------	---

Description

Extract variability parameter estimates from a NONMEM output object.

Usage

```
get_omega(x, output = "est", sigdig = 6, sep = "-", est.step = NULL)
```

Arguments

x	A NONMEM output object generated using read_nm .
output	A flag specifying the matrix or matrices to be output. Valid flag values are est (the default), se, rse, cor, cse, 95ci, or all.
sigdig	Specifies the number of significant digits to be provided (default=6).
sep	Specifies the separator character to use for 95% confidence intervals (default="-").
est.step	Specifies which estimation step to return parameters from (default is the last).

Value

A symmetrical matrix, or a list of symmetrical matrices if all is specified.

Author(s)

Justin Wilkins, <justin.wilkins@occams.com>

est returns the estimated OMEGA variance-covariance matrix. se returns the standard errors for the estimated OMEGA variance-covariance matrix. rse returns the relative standard errors for the estimated OMEGA variance-covariance matrix (se/est*100). cor returns the correlation matrix. cse returns the standard errors for the correlation matrix. 95ci returns the asymptotic 95% confidence intervals for the elements of the OMEGA variance-covariance matrix (est +/- 1.96*se). all returns all available OMEGA matrices.

See Also

NONMEM (<http://www.iconplc.com/innovation/nonmem/>)

Examples

```
## Not run:
nmOutput <- read_nm("run315.xml")
omegas <- get_omega(nmOutput)
omegaRSEs <- get_omega(nmOutput, "rse")

## End(Not run)
```

get_probinfo	<i>Extract problem and estimation information from a NONMEM output object.</i>
--------------	--

Description

Extract problem and estimation information from a NONMEM output object.

Usage

```
get_probinfo(x, sigdig = 6, est.step = NULL)
```

Arguments

x	A NONMEM output object generated using read_nm .
sigdig	Specifies the number of significant digits to be provided (default=6).
est.step	Specifies which estimation step to return parameters from (default is the last).

See Also

NONMEM (<http://www.iconplc.com/innovation/nonmem/>)

Examples

```
## Not run:
nmOutput <- read_nm("run315.xml")
probInfo <- get_probinfo(nmOutput)

## End(Not run)
```

get_shrinkage	<i>Extract shrinkage estimates from a NONMEM output object.</i>
---------------	---

Description

Extract shrinkage estimates from a NONMEM output object.

Usage

```
get_shrinkage(x, output = "eta", type = "sd", sigdig = 3, est.step = NULL)
```

Arguments

x	A NONMEM output object generated using read_nm .
output	A flag specifying the shrinkage estimates to be output. Valid flag values are eta (the default), epsilon, or all.
type	Specifies the type of shrinkage to report. Valid values are sd (standard deviation, the default) or vr (variance, if present in the XML output).
sigdig	Specifies the number of significant digits to be provided (default=3).
est.step	Specifies which estimation step to return parameters from (default is the last).

Value

A named vector of NONMEM shrinkage estimates, or in the case of all, a list of named vectors.

eta returns a vector of ETA shrinkages, as reported by NONMEM. epsilon returns EPSILON shrinkage, as reported by NONMEM. all returns both ETA and EPSILON shrinkage estimates as a list of vectors.

Author(s)

Justin Wilkins, <justin.wilkins@occams.com>

See Also

NONMEM (<http://www.iconplc.com/innovation/nonmem/>)

Examples

```
## Not run:
nmOutput <- read_nm("run315.xml")
shr <- get_shrinkage(nmOutput, output="all")

## End(Not run)
```

get_sigma	<i>Extract residual variability parameter estimates from a NONMEM output object.</i>
-----------	--

Description

Extract residual variability parameter estimates from a NONMEM output object.

Usage

```
get_sigma(x, output = "est", sigdig = 6, sep = "-", est.step = NULL)
```

Arguments

x	A NONMEM output object generated using read_nm .
output	A flag specifying the matrix or matrices to be output. Valid flag values are est (the default), se, rse, cor, cse, 95ci, or all.
sigdig	Specifies the number of significant digits to be provided (default=6).
sep	Specifies the separator character to use for 95% confidence intervals (default="-").
est.step	Specifies which estimation step to return parameters from (default is the last).

Value

A symmetrical matrix, or a list of symmetrical matrices if all is specified.

est returns the estimated SIGMA variance-covariance matrix. se returns the standard errors for the estimated SIGMA variance-covariance matrix. rse returns the relative standard errors for the estimated SIGMA variance-covariance matrix (se/est*100). cor returns the correlation matrix matrix. cse returns the standard errors for the correlation matrix. 95ci returns the asymptotic 95% confidence intervals for the elements of the SIGMA variance-covariance matrix (est +/- 1.96*se). all returns all available SIGMA matrices.

Author(s)

Justin Wilkins, <justin.wilkins@occams.com>

See Also

NONMEM (<http://www.iconplc.com/innovation/nonmem/>)

Examples

```
## Not run:
nmOutput <- read_nm("run315.xml")
sigmas <- get_sigma(nmOutput)
sigmaRSEs <- get_sigma(nmOutput, "rse")

## End(Not run)
```

get_theta	<i>Extract structural model parameter estimates and associated information from a NONMEM output object.</i>
-----------	---

Description

Extract structural model parameter estimates and associated information from a NONMEM output object.

Usage

```
get_theta(x, output = "est", sigdig = 6, sep = "-", est.step = NULL)
```

Arguments

x	A NONMEM output object generated using read_nm .
output	A flag specifying the matrix or matrices to be output. Valid flag values are est (the default), se, rse, 95ci, or all.
sigdig	Specifies the number of significant digits to be provided (default=6).
sep	Specifies the separator character to use for 95% confidence intervals (default="-").
est.step	Specifies which estimation step to return parameters from (default is the last).

Value

A named vector of NONMEM model parameter estimates, or in the case of all, a list of named vectors.

est returns a vector of THETA values. se returns a vector of THETA standard errors. rse returns a vector of THETA relative standard errors (se/est*100). 95ci returns a vector of the asymptotic 95% confidence intervals for the elements of THETA (est +/- 1.96*se). all returns all available THETA information as a list of named vectors.

Author(s)

Justin Wilkins, <justin.wilkins@occams.com>

See Also

NONMEM (<http://www.iconplc.com/innovation/nonmem/>)

Examples

```
## Not run:  
nmOutput <- read_nm("run315.xml")  
thetas <- get_theta(nmOutput)  
  
## End(Not run)
```

gm

Calculate geometric mean

Description

Calculate geometric mean

Usage

```
gm(x)
```

Arguments

x Numeric vector.

Value

The geometric mean. NA is returned if there are any non-positive elements in x.

Author(s)

Justin Wilkins, <justin.wilkins@occams.com>

Examples

```
gm(c(0.5, 7, 8, 5))
```

pcv *Calculate percentage coefficient of variation*

Description

Calculate percentage coefficient of variation

Usage

```
pcv(x, na.rm = FALSE)
```

Arguments

x	Numeric vector.
na.rm	A logical value indicating whether NA values should be stripped before the computation proceeds.

Value

The percentage coefficient of variation.

Author(s)

Justin Wilkins, <justin.wilkins@occams.com>

Examples

```
pcv(rnorm(50, 5, 7.56))
```

pk_curve *Provide concentration-time curves.*

Description

Provide concentration-time curves.

Usage

```
pk_curve(  
  t,  
  model = "1cmt_oral",  
  params = list(ka = 2.77, CL = 2.5, V = 25),  
  dose = 600,  
  ii = 24,  
  addl = 0,  
  ss = F  
)
```


Arguments

t	Observation time in h, specified as a vector.
model	The model to use. Must be one of "1cmt_bolus", "1cmt_infusion", "1cmt_oral", "2cmt_bolus", "2cmt_infusion", "2cmt_oral", "3cmt_bolus", "3cmt_infusion", "3cmt_oral". The default is "1cmt_oral".
params	A named list containing parameter values for the selected model type.
dose	Dose amount.
ii	Interdose interval (or tau), in hours (default 24).
addl	Number of additional doses (default 0).
ss	Assume steady state concentration (default FALSE).

Value

A data frame containing times (t) and concentrations (cp).

Author(s)

Justin Wilkins, <justin.wilkins@occams.com>

Examples

```
plot(pk_curve(t=seq(0,72,by=0.1), model="3cmt_oral", ii=12, addl=5,
  params=list(CL=2.5, V1=25, V2=2, V3=5, Q2=0.5, Q3=0.25, ka=1)), type="l")
```

plot_nmprogress *Plot NONMEM parameter estimation by iteration.*

Description

plot_nmprogress returns a plot or set of plots showing the evolution of parameter estimates by iteration.

Usage

```
plot_nmprogress(  
  fileName,  
  fileExt = ".lst",  
  metric = "perc",  
  lineCol = "#902C10",  
  idlineCol = "black"  
)
```

Arguments

fileName	A NONMEM output file prefix, without extension (e.g. 'run315').
fileExt	The file extension for NONMEM output, set to '.lst' by default.
metric	What to show in the plot. Allowed options are 'est' (the actual estimate) or 'perc' (the percentage change in the estimated or OFV since estimation began). Default is 'perc'.
lineCol	Line color. Default is '#902C10'.
idlineCol	Identity line color (only used if 'perc' metric is selected). Default is black.

Value

A set of plots.

Author(s)

Justin Wilkins, <justin.wilkins@occams.com>

See Also

NONMEM (<http://www.iconplc.com/innovation/nonmem/>)

Examples

```
## Not run:
plot_nmprogress("run315")
plot_nmprogress("run315", ".nmlst")

## End(Not run)
```

plot_scm

Visualize PsN SCM output.

Description

plot_scm returns a visualization of a Perl-speaks-NONMEM (PsN, <https://uopharmacometrics.github.io/PsN/>) SCM (stepwise covariate modeling) procedure. It depends on the presence of scmlog.txt and short_scmlog.txt files in the specified directory.

Usage

```
plot_scm(
  dir,
  startPhase = "forward",
  fwdSuccessCol = "#66C2A5",
  fwdFailCol = "black",
```

```

    bwdSuccessCol = "#FC8D62",
    bwdFailCol = "black",
    defCol = "black",
    fwdSuccessFillCol = "#B3E2CD",
    fwdFailFillCol = "white",
    bwdSuccessFillCol = "#FDCDAC",
    bwdFailFillCol = "white",
    defFillCol = "white",
    fwdSuccessFontCol = "black",
    fwdFailFontCol = "black",
    bwdSuccessFontCol = "black",
    bwdFailFontCol = "black",
    defFontCol = "black",
    fullFwdCol = "#8DA0CB",
    finalCol = "#E78AC3",
    fullFwdFillCol = "#CBD5E8",
    finalFillCol = "#F4CAE4",
    fullFwdFontCol = "black",
    finalFontCol = "black",
    fullFwdWidth = "2px",
    finalWidth = "2px",
    defWidth = "1px",
    nodeStyle = "filled,rounded",
    nodeShape = "box",
    fontname = "helvetica",
    rankdir = "TB",
    layout = "dot",
    lookupDF = NULL,
    ...
)

```

Arguments

<code>dir</code>	A PsN SCM folder (containing <code>scmlog.txt</code> and <code>short_scmlog.txt</code>).
<code>startPhase</code>	Where to start collating the output; can be "forward" (the default) or "backward".
<code>fwdSuccessCol</code>	Node outline color for a model fit matching the forward inclusion criterion.
<code>fwdFailCol</code>	Node outline color for a model fit not matching the forward inclusion criterion.
<code>bwdSuccessCol</code>	Node outline color for a model fit matching the backward elimination criterion.
<code>bwdFailCol</code>	Node outline color for a model fit not matching the backward elimination criterion.
<code>defCol</code>	Default node outline color.
<code>fwdSuccessFillCol</code>	Node fill color for a model fit matching the forward inclusion criterion.
<code>fwdFailFillCol</code>	Node fill color for a model fit not matching the forward inclusion criterion.
<code>bwdSuccessFillCol</code>	Node fill color for a model fit matching the backward elimination criterion.

bwdFailFillCol	Node fill color for a model fit not matching the backward elimination criterion.
defFillCol	Default node fill color.
fwdSuccessFontCol	Node font color for a model fit matching the forward inclusion criterion.
fwdFailFontCol	Node font color for a model fit not matching the forward inclusion criterion.
bwdSuccessFontCol	Node font color for a model fit matching the backward elimination criterion.
bwdFailFontCol	Node font color for a model fit not matching the backward elimination criterion.
defFontCol	Default node font color.
fullFwdCol	Node outline color for the full forward model (i.e. the final model before the backward elimination procedure in SCM).
finalCol	Node outline color for the final reduced model (i.e. the final model reached after the backward elimination procedure in SCM).
fullFwdFillCol	Node fill color for the full forward model (i.e. the final model before the backward elimination procedure in SCM).
finalFillCol	Node fill color for the final reduced model (i.e. the final model reached after the backward elimination procedure in SCM).
fullFwdFontCol	Node font color for the full forward model (i.e. the final model before the backward elimination procedure in SCM).
finalFontCol	Node font color for the final reduced model (i.e. the final model reached after the backward elimination procedure in SCM).
fullFwdWidth	Node outline width for the full forward model (i.e. the final model before the backward elimination procedure in SCM).
finalWidth	Node outline width for the final reduced model (i.e. the final model reached after the backward elimination procedure in SCM).
defWidth	Default node outline width.
nodeStyle	Node style. A string containing a comma-separated list of options (which include "filled", "striped", "wedged", "diagonals" and "rounded"). See the GraphViz documentation for further details.
nodeShape	Node shape. Options include "box" (the default), "oval", "diamond", "egg", "plaintext", "point", "square", "triangle" and many more. See the GraphViz documentation for further details.
fontname	Font for nodes. Options depend heavily on the local system - see the GraphViz documentation for further details.
rankdir	Direction of graph layout. Possible values are "TB" (the default), "LR", "BT", "RL", corresponding to directed graphs drawn from top to bottom, from left to right, from bottom to top, and from right to left, respectively.
layout	Graph layout. Possible values are "dot" (the default), "neato", "twopi", and "circo". Note that of these, "dot" is the easiest to interpret and the others may produce odd results.
lookupDF	A data frame containing a lookup table for node labels. By default, plot_scm will use the PSN model names. If a lookup table containing the fields 'Model' and 'Alias' is provided, model names in 'Model' will be replaced in the output plots by mtaching labels in 'Alias'.

... Additional parameters passed to the underlying [SetNodeStyle](#) and [SetEdgeStyle](#) functions, which in turn rely on [DiagrammeR](#).

Details

This function parses PsN SCM output and displays it as a GraphViz graph (effectively, an HTML widget). It is built on [plot.Node](#) - please refer to documentation for this function for a more detailed overview of what is possible (a lot). For more specific details, see <http://rich-iannone.github.io/DiagrammeR/docs.html>.

Value

A grViz object.

Author(s)

Justin Wilkins, <justin.wilkins@occams.com>

See Also

NONMEM (<http://www.iconplc.com/innovation/nonmem/>)

GraphViz (<https://graphviz.org/Documentation.php>)

Lindbom L, Ribbing J & Jonsson EN (2004). Perl-speaks-NONMEM (PsN) - A Perl module for NONMEM related programming. *Computer Methods and Programs in Biomedicine*, 75(2), 85-94. <https://doi.org/10.1016/j.cmpb.2003.11.003>

Lindbom L, Pihlgren P & Jonsson N (2005). PsN-Toolkit - A collection of computer intensive statistical methods for non-linear mixed effect modeling using NONMEM. *Computer Methods and Programs in Biomedicine*, 79(3), 241-257. <https://doi.org/10.1016/j.cmpb.2005.04.005>

Other NONMEM reading: [read_nm_all\(\)](#), [read_nm_multi_table\(\)](#), [read_nmcov\(\)](#), [read_nmnext\(\)](#), [read_nmtables\(\)](#), [read_nm\(\)](#), [read_scm\(\)](#)

Examples

```
## Not run:  
scm <- plot_scm("E:/DrugX/ModelDevelopment/scm310")  
  
## End(Not run)
```

read_nm

Read NONMEM 7.2+ output into a list of lists.

Description

Read NONMEM 7.2+ output into a list of lists.

Usage

```
read_nm(fileName, directory = NULL, quiet = FALSE, ...)
```

Arguments

fileName	A NONMEM XML output file (e.g. "run315.xml").
directory	The directory to look for files within. If NULL, uses the current directory.
quiet	Flag for displaying intermediate output.
...	Passed to each of the read functions (ignored in the functions).

Value

A list of lists corresponding to a NONMEM output object.

Author(s)

Justin Wilkins, <justin.wilkins@occams.com>

See Also

NONMEM (<http://www.iconplc.com/innovation/nonmem/>)

Other NONMEM reading: [plot_scm\(\)](#), [read_nm_all\(\)](#), [read_nm_multi_table\(\)](#), [read_nmcov\(\)](#), [read_nmext\(\)](#), [read_nmtables\(\)](#), [read_scm\(\)](#)

Examples

```
## Not run:  
nmOutput <- read_nm("run315.xml")  
  
## End(Not run)
```

read_nmcov

Read in the NONMEM variance-covariance matrix.

Description

Read in the NONMEM variance-covariance matrix.

Usage

```
read_nmcov(fileName, quiet = FALSE, directory = NULL, ...)
```

Arguments

fileName	Root filename for the NONMEM run (e.g. "run315"). This function reads the ".cov" NONMEM output table, and will return an error if this is missing.
quiet	Flag for displaying intermediate output.
directory	The directory to look for files within. If NULL, uses the current directory.
...	Passed to each of the read functions (ignored in the functions).

Value

A symmetrical variance-covariance matrix covering all model parameters.

Author(s)

Justin Wilkins, <justin.wilkins@occams.com>

See Also

NONMEM (<http://www.iconplc.com/innovation/nonmem/>)

Other NONMEM reading: [plot_scm\(\)](#), [read_nm_all\(\)](#), [read_nm_multi_table\(\)](#), [read_nmext\(\)](#), [read_nmtables\(\)](#), [read_nm\(\)](#), [read_scm\(\)](#)

Examples

```
## Not run:
nmVcov <- read_nmcov("run315")

## End(Not run)
```

read_nmext

Read NONMEM output into a list.

Description

read_nmext returns a summary of a given NONMEM run, including termination messages, parameter estimates, and precision estimates. Minimally, the NONMEM output and '.ext' files must be available.

Usage

```
read_nmext(
  fileName,
  fileExt = ".lst",
  directory = NULL,
  quiet = FALSE,
  estNo = NULL,
  ...
)
```

Arguments

fileName	A NONMEM output file prefix, without extension (e.g. "run315").
fileExt	The file extension for NONMEM output, set to ".lst" by default.
directory	The directory to look for files within. If NULL, uses the current directory.
quiet	Flag for displaying intermediate output.
estNo	The estimation number to report (by default, if only one estimation step is present, that will be reported; if multiple are reported, the last will be reported by default).
...	Passed to each of the read functions (ignored in the functions).

Value

A list of lists, containing 'Termination' (summary of NONMEM's termination output, including shrinkages and ETABAR estimates), 'OFV' (the objective function value), 'Thetas' (a vector of structural parameter estimates, or THETAs), 'Omega', a list of lists containing the OMEGA matrix, 'Sigma', a list of lists containing the SIGMA matrix, 'seThetas', a vector of standard errors for THETAs, 'seOmega', a list of lists containing standard errors for the OMEGA matrix, and 'seSigma', a list of lists containing standard errors for the SIGMA matrix.

Author(s)

Justin Wilkins, <justin.wilkins@occams.com>

See Also

NONMEM (<http://www.iconplc.com/innovation/nonmem/>)

Other NONMEM reading: [plot_scm\(\)](#), [read_nm_all\(\)](#), [read_nm_multi_table\(\)](#), [read_nmcov\(\)](#), [read_nmtables\(\)](#), [read_nm\(\)](#), [read_scm\(\)](#)

Examples

```
## Not run:
read_nmext("run315")
read_nmext("run315", ".nm1st")

## End(Not run)
```

read_nmtables

Reads NONMEM output tables.

Description

Reads NONMEM output tables.

Usage

```
read_nmtables(
  tableFiles = NULL,
  runNo = NULL,
  tabSuffix = "",
  tableNames = c("sdtab", "mutab", "patab", "catab", "cotab", "mytab", "extra",
    "xptab"),
  quiet = FALSE,
  directory = NULL,
  output_type = c("data.frame", "list"),
  ...
)
```

Arguments

tableFiles	NONMEM table files to be read.
runNo	Run number.
tabSuffix	Table file suffix.
tableNames	List of root table names, using the Xpose naming convention as the default.
quiet	Flag for displaying intermediate output.
directory	The directory to look for files within. If NULL, uses the current directory.
output_type	Should output be a "data.frame" where all results are merged or a "list" of data.frames.
...	Passed to each of the read functions (ignored in the functions).

Value

A data.frame or list of data.frames depending on the output_type argument.

Note

Adapted from Xpose 4 (<https://CRAN.R-project.org/package=xpose4>).

Author(s)

Bill Denney, Justin Wilkins, Niclas Jonsson, Andrew Hooker

References

NONMEM (<http://www.iconplc.com/innovation/nonmem/>)

Jonsson EN, Karlsson MO. Xpose—an S-PLUS based population pharmacokinetic/pharmacodynamic model building aid for NONMEM. *Comput Methods Programs Biomed.* 1999 Jan;58(1):51-64

See Also

Other NONMEM reading: [plot_scm\(\)](#), [read_nm_all\(\)](#), [read_nm_multi_table\(\)](#), [read_nmcov\(\)](#), [read_nmext\(\)](#), [read_nm\(\)](#), [read_scm\(\)](#)

Examples

```
## Not run:  
tables <- read_nmtables(runNo=315)  
  
## End(Not run)
```

read_nm_all	<i>Read all NONMEM files for a single NONMEM run.</i>
-------------	---

Description

Read all NONMEM files for a single NONMEM run.

Usage

```
read_nm_all(runNo, run_prefix = "run", directory = NULL, quiet = FALSE, ...)
```

Arguments

runNo	Run number.
run_prefix	The start to the name of the run.
directory	The directory to look for files within. If NULL, uses the current directory.
quiet	Flag for displaying intermediate output.
...	Passed to each of the read functions (ignored in the functions).

Details

The filename for loading is constructed as `paste(run_prefix, runNo)`. To load a nonstandard file, simply set one of those values to NULL.

See Also

Other NONMEM reading: [plot_scm\(\)](#), [read_nm_multi_table\(\)](#), [read_nmcov\(\)](#), [read_nmext\(\)](#), [read_nmtables\(\)](#), [read_nm\(\)](#), [read_scm\(\)](#)

read_nm_multi_table *Read (single or) multiple NONMEM tables from a single file*

Description

Read (single or) multiple NONMEM tables from a single file

Usage

```
read_nm_multi_table(  
  fileName,  
  header = TRUE,  
  ...,  
  simplify = TRUE,  
  table_start_pattern = "^TABLE NO"  
)
```

Arguments

fileName	The filename to read from
header, ...	Arguments passed to read.table
simplify	If a single table is present, return a data.frame instead of a list of data.frames?
table_start_pattern	What should be found to start a new table?

Value

A list of data.frames, or if only one is present and simplify=TRUE, a data.frame.

Author(s)

Bill Denney

See Also

Other NONMEM reading: [plot_scm\(\)](#), [read_nm_all\(\)](#), [read_nmcov\(\)](#), [read_nmext\(\)](#), [read_nmtables\(\)](#), [read_nm\(\)](#), [read_scm\(\)](#)

Examples

```
## Not run:  
read_nm_multi_table("run1.cov", row.names=1)  
  
## End(Not run)
```

read_nm_std_ext	<i>Read a standard NONMEM extension file</i>
-----------------	--

Description

Read a standard NONMEM extension file

Usage

```
read_nm_std_ext(fileName, extension, directory = NULL, ...)
```

Arguments

fileName	The filename (with directory name, if applicable) to read (with or without the extension)
extension	The file extension to optionally append (preferably starting with a ".")
directory	The directory to look for files within. If NULL, uses the current directory.
...	Passed to read_nm_multi_table()

Value

NULL if the file does not exist or the value of read_nm_multi_table() if it does exist.

Examples

```
## Not run:
read_nm_std_ext("run1", "phi")

## End(Not run)
```

read_scm	<i>Read PsN SCM output into a format suitable for further use.</i>
----------	--

Description

read_scm returns a summary of a Perl-speaks-NONMEM (PsN, <https://uopharmacometrics.github.io/PsN/>) SCM (stepwise covariate modeling) procedure. It depends on the presence of scmlog.txt and short_scmlog.txt files in the specified directory.

Usage

```
read_scm(dir, startPhase = "forward")
```

Arguments

`dir` A PsN SCM folder (containing `scmlog.txt` and `short_scmlog.txt`).
`startPhase` Where to start collating the output; can be "forward" (the default) or "backward".

Value

A list of data frames, containing

`forward` all models evaluated during the forward inclusion step of covariate model building
`forwardSummary` the covariate relationships selected at each forward step
`forwardP` the P-value used for inclusion during the forward inclusion step
`backward` all models evaluated during the backward elimination step of covariate model building
`backwardSummary` the covariate relationships eliminated at each backward step
`backwardP` the P-value used for exclusion during the backward elimination step

Author(s)

Justin Wilkins, <justin.wilkins@occams.com>

See Also

NONMEM (<http://www.iconplc.com/innovation/nonmem/>)

Lindbom L, Ribbing J & Jonsson EN (2004). Perl-speaks-NONMEM (PsN) - A Perl module for NONMEM related programming. *Computer Methods and Programs in Biomedicine*, 75(2), 85-94. <https://doi.org/10.1016/j.cmpb.2003.11.003>

Lindbom L, Pihlgren P & Jonsson N (2005). PsN-Toolkit - A collection of computer intensive statistical methods for non-linear mixed effect modeling using NONMEM. *Computer Methods and Programs in Biomedicine*, 79(3), 241-257. <https://doi.org/10.1016/j.cmpb.2005.04.005>

Other NONMEM reading: [plot_scm\(\)](#), [read_nm_all\(\)](#), [read_nm_multi_table\(\)](#), [read_nmcov\(\)](#), [read_nmext\(\)](#), [read_nmtables\(\)](#), [read_nm\(\)](#)

Examples

```
## Not run:
scm <- read_scm("E:/DrugX/ModelDevelopment/scm310")

## End(Not run)
```

rnm

*Read NONMEM 7.2+ output into an R object.***Description**

Read NONMEM 7.2+ output into an R object.

Usage

```
rnm(
  index,
  prefix = "run",
  pathNM,
  ndig = 3,
  ndigB = 3,
  ndigP = 1,
  Pci = 95,
  ext = ".lst",
  extmod = ".mod",
  Pvalues = TRUE,
  RawCI = FALSE,
  ...
)
```

Arguments

index	The NONMEM model index, i.e. the numeric part of the filename assuming it follows the convention 'run123.mod'.
prefix	The NONMEM model prefix, assuming it follows the convention 'run123.mod'. The default is "run".
pathNM	The path to the NONMEM output. This should not contain a trailing slash.
ndig	Number of significant digits to use. The default is 3.
ndigB	Number of significant digits to use. The default is 3.
ndigP	Number of digits after the decimal point to use for percentages. The default is 1.
Pci	Asymptotic confidence interval to apply when reporting parameter uncertainty. The default is 95.
ext	NONMEM output file extension. The default is ".lst".
extmod	NONMEM control stream file extension. The default is "mod".
Pvalues	Report P-values for parameters? The default is TRUE.
RawCI	Report confidence intervals without estimate? The default is FALSE.
...	Additional arguments.

Details

The output list is composed of the following objects:

- "Theta" A data frame describing the structural (fixed-effect) parameters, containing parameter name, estimated value, standard error (SE), coefficient of variation (CV), lower and upper confidence limits (CIL and CIU, based on P_{ci}), and P-value, calculated as $2 * (1 - \text{pnorm}(\text{abs}(\text{theta}/\text{theta.se})))$.
- "Eta" A data frame describing the interindividual random-effects parameters, containing estimated value, standard error (SE), coefficient of variation (CV, calculated as $\text{abs}(100 * (\text{SE}/\text{OMEGA}))$), coefficient of variation (EtaCV, calculated as $100 * \text{sqrt}(\text{OMEGA})$), and shrinkage.
- "Epsilon" A data frame describing the residual random-effects parameters, containing estimated value, standard error (SE), coefficient of variation (CV, calculated as $\text{abs}(100 * (\text{SE}/\text{OMEGA}))$), coefficient of variation (EtaCV, calculated as $100 * \text{sqrt}(\text{SIGMA})$), and shrinkage.
- "CorTheta" A data frame containing the correlation matrix for fixed effects ("THETA").
- "CorOmega" A data frame containing the correlation matrix for interindividual random effects ("OMEGA").
- "CorSigma" A data frame containing the correlation matrix for residual random effects ("OMEGA").
- "OmegaMatrix" A data frame containing the "OMEGA" matrix.
- "SigmaMatrix" A data frame containing the "OMEGA" matrix.
- "CovMatrixTheta" A data frame containing the variance-covariance matrix for structural parameters (THETA).
- "CovMatrix" A data frame containing the complete variance-covariance matrix.
- "OFV" The objective function value.
- "ThetaString" A data frame containing all relevant fixed-effects parameter information, suitable for use in a table of parameter estimates. Contains parameter name, estimate, standard error, coefficient of variation, combined estimate and asymptotic confidence interval, and P-value.
- "EtaString" A data frame containing all relevant interindividual random-effects parameter information, suitable for use in a table of parameter estimates. Contains parameter name, estimate (variance), standard error, coefficient of variation, percentage value (calculated as $100 * \text{sqrt}(\text{OMEGA})$), and shrinkage.
- "EpsString" A data frame containing all relevant residual random-effects parameter information, suitable for use in a table of parameter estimates. Contains parameter name, estimate (variance), standard error, coefficient of variation, percentage value (calculated as $100 * \text{sqrt}(\text{SIGMA})$), and shrinkage.
- "RunTime" Run time.
- "ConditionN" Condition number.

Value

A list containing information extracted from the NONMEM output.

Author(s)

Rik Schoemaker, <rik.schoemaker@occams.com>

Justin Wilkins, <justin.wilkins@occams.com>

See Also

NONMEM (<http://www.iconplc.com/innovation/nonmem/>)

Examples

```
## Not run:  
nmOutput <- rnm("run315.lst")  
  
## End(Not run)
```

sample_omega	<i>Sample from the multivariate normal distribution using the OMEGA variance-covariance matrix to generate new sets of simulated ETAs from NONMEM output.</i>
--------------	---

Description

Sample from the multivariate normal distribution using the OMEGA variance-covariance matrix to generate new sets of simulated ETAs from NONMEM output.

Usage

```
sample_omega(nmRun, n, seed)
```

Arguments

nmRun	Root filename for the NONMEM run (e.g. "run315").
n	Number of samples required.
seed	Random seed.

Value

A data frame containing n samples from the multivariate normal distribution, using the estimated NONMEM OMEGA variance-covariance matrix. This provides n sets of ETA estimates suitable for simulation of new patients.

Author(s)

Justin Wilkins, <justin.wilkins@occams.com>

See Also

NONMEM (<http://www.iconplc.com/innovation/nonmem/>)

Examples

```
## Not run:
omDist <- sample_omega("run315", 5000, seed=740727)

## End(Not run)
```

sample_sigma	<i>Sample from the multivariate normal distribution using the SIGMA variance-covariance matrix to generate new sets of simulated EPSILONs from NONMEM output.</i>
--------------	---

Description

Sample from the multivariate normal distribution using the SIGMA variance-covariance matrix to generate new sets of simulated EPSILONs from NONMEM output.

Usage

```
sample_sigma(nmRun, n, seed)
```

Arguments

nmRun	Root filename for the NONMEM run (e.g. "run315").
n	Number of samples required.
seed	Random seed.

Value

A data frame containing n samples from the multivariate normal distribution, using the estimated NONMEM SIGMA variance-covariance matrix. This provides n sets of EPSILON estimates suitable for simulation of new datasets.

Author(s)

Justin Wilkins, <justin.wilkins@occams.com>

See Also

NONMEM (<http://www.iconplc.com/innovation/nonmem/>)

Examples

```
## Not run:
sigDist <- sample_sigma("run315", 5000, seed=740727)

## End(Not run)
```

sample_uncert	<i>Sample from the multivariate normal distribution to generate new sets of parameters from NONMEM output.</i>
---------------	--

Description

Sample from the multivariate normal distribution to generate new sets of parameters from NONMEM output.

Usage

```
sample_uncert(nmRun, n, seed)
```

Arguments

nmRun	Root filename for the NONMEM run (e.g. "run315").
n	Number of samples required.
seed	Random seed.

Value

A data frame containing n samples from the multivariate normal distribution, using NONMEM typical parameter estimates the NONMEM variance-covariance matrix (from the *.cov file). This provides n sets of parameter estimates sampled from the uncertainty distribution, suitable for simulation under model uncertainty.

Author(s)

Justin Wilkins, <justin.wilkins@occams.com>

See Also

NONMEM (<http://www.iconplc.com/innovation/nonmem/>)

Examples

```
## Not run:  
nmMatrix <- sample_uncert("run315", 5000, seed=740727)  
  
## End(Not run)
```

table_rtf	<i>Read NONMEM output into a list.</i>
-----------	--

Description

table_rtf generates an RTF table from a data frame.

Usage

```
table_rtf(  
  df,  
  outFile = NULL,  
  rtfFile = TRUE,  
  boldHeader = TRUE,  
  rowNames = FALSE,  
  ...  
)
```

Arguments

df	A data frame.
outFile	A filename for writing the table to. If NULL, writes to console.
rtfFile	If TRUE (the default), then add RTF tabs to generate a fully formatted RTF file.
boldHeader	If TRUE, make the header bold.
rowNames	If TRUE, include row names in the table. Default is FALSE.
...	Other formatting options for the table body.

Value

An RTF table based on the data frame provided.

Author(s)

John Johnson, <johndjohnson@gmail.com>

References

<https://www.r-bloggers.com/another-solution-to-the-r-to-word-table-problem/>

Examples

```
## Not run:  
scm <- read_scm("E:/DrugX/ModelDevelopment/scm310")  
myRTF <- table_rtf(scm$forwardSummary)  
  
## End(Not run)
```

Index

* NONMEM reading

- plot_scm, 26
 - read_nm, 29
 - read_nm_all, 34
 - read_nm_multi_table, 35
 - read_nmcov, 30
 - read_nmext, 31
 - read_nmtables, 32
 - read_scm, 36
-
- calc_derived, 3
 - calc_derived_1cpt (calc_derived), 3
 - calc_derived_2cpt (calc_derived), 3
 - calc_derived_3cpt (calc_derived), 3
 - calc_sd_1cmt, 5
 - calc_sd_1cmt_linear_bolus (calc_sd_1cmt), 5
 - calc_sd_1cmt_linear_infusion (calc_sd_1cmt), 5
 - calc_sd_1cmt_linear_oral_0 (calc_sd_1cmt), 5
 - calc_sd_1cmt_linear_oral_0_lag (calc_sd_1cmt), 5
 - calc_sd_1cmt_linear_oral_1 (calc_sd_1cmt), 5
 - calc_sd_1cmt_linear_oral_1_lag (calc_sd_1cmt), 5
 - calc_sd_2cmt, 7
 - calc_sd_2cmt_linear_bolus (calc_sd_2cmt), 7
 - calc_sd_2cmt_linear_infusion (calc_sd_2cmt), 7
 - calc_sd_2cmt_linear_oral_0 (calc_sd_2cmt), 7
 - calc_sd_2cmt_linear_oral_0_lag (calc_sd_2cmt), 7
 - calc_sd_2cmt_linear_oral_1 (calc_sd_2cmt), 7
 - calc_sd_2cmt_linear_oral_1_lag (calc_sd_2cmt), 7
 - calc_sd_3cmt, 9
 - calc_sd_3cmt_linear_bolus (calc_sd_3cmt), 9
 - calc_sd_3cmt_linear_infusion (calc_sd_3cmt), 9
 - calc_sd_3cmt_linear_oral_0 (calc_sd_3cmt), 9
 - calc_sd_3cmt_linear_oral_0_lag (calc_sd_3cmt), 9
 - calc_sd_3cmt_linear_oral_1 (calc_sd_3cmt), 9
 - calc_sd_3cmt_linear_oral_1_lag (calc_sd_3cmt), 9
 - calc_ss_1cmt, 10
 - calc_ss_1cmt_linear_bolus (calc_ss_1cmt), 10
 - calc_ss_1cmt_linear_infusion (calc_ss_1cmt), 10
 - calc_ss_1cmt_linear_oral_0 (calc_ss_1cmt), 10
 - calc_ss_1cmt_linear_oral_0_lag (calc_ss_1cmt), 10
 - calc_ss_1cmt_linear_oral_1 (calc_ss_1cmt), 10
 - calc_ss_1cmt_linear_oral_1_lag (calc_ss_1cmt), 10
 - calc_ss_2cmt, 12
 - calc_ss_2cmt_linear_bolus (calc_ss_2cmt), 12
 - calc_ss_2cmt_linear_infusion (calc_ss_2cmt), 12
 - calc_ss_2cmt_linear_oral_0 (calc_ss_2cmt), 12
 - calc_ss_2cmt_linear_oral_0_lag (calc_ss_2cmt), 12
 - calc_ss_2cmt_linear_oral_1 (calc_ss_2cmt), 12
 - calc_ss_2cmt_linear_oral_1_lag (calc_ss_2cmt), 12

`calc_ss_3cmt`, 14
`calc_ss_3cmt_linear_bolus`
 (`calc_ss_3cmt`), 14
`calc_ss_3cmt_linear_infusion`
 (`calc_ss_3cmt`), 14
`calc_ss_3cmt_linear_oral_0`
 (`calc_ss_3cmt`), 14
`calc_ss_3cmt_linear_oral_0_lag`
 (`calc_ss_3cmt`), 14
`calc_ss_3cmt_linear_oral_1`
 (`calc_ss_3cmt`), 14
`calc_ss_3cmt_linear_oral_1_lag`
 (`calc_ss_3cmt`), 14

`DiagrammeR`, 29

`gcv_convert`, 15
`get_auc`, 16
`get_est_table`, 17
`get_omega`, 18
`get_probinf`, 19
`get_shrinkage`, 20
`get_sigma`, 21
`get_theta`, 22
`gm`, 23

`pcv`, 24
`pk_curve`, 24
`plot.Node`, 29
`plot_nmprogress`, 25
`plot_scm`, 26, 30–35, 37

`read_nm`, 17–22, 29, 29, 31–35, 37
`read_nm_all`, 29–33, 34, 35, 37
`read_nm_multi_table`, 29–34, 35, 37
`read_nm_std_ext`, 36
`read_nmcov`, 29, 30, 30, 32–35, 37
`read_nmext`, 29–31, 31, 33–35, 37
`read_nmtables`, 29–32, 32, 34, 35, 37
`read_scm`, 29–35, 36
`rnm`, 38

`sample_omega`, 40
`sample_sigma`, 41
`sample_uncert`, 42
`SetEdgeStyle`, 29
`SetNodeStyle`, 29

`table_rtf`, 43